



Safety Data Sheet according to Regulation (EC) No 1907/2006

Page 1 of 14

SDS No. : 477599
V003.2

TEROSON PU 9225 SF ME

Revision: 25.06.2019
printing date: 13.08.2020
Replaces version from: 14.11.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

TEROSON PU 9225 SF ME

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

2-Component polyurethane adhesive

1.3. Details of the supplier of the safety data sheet

Henkel Ltd

Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 1442 278000

Fax-no.: +44 1442 278071

ua-productsafety.uk@henkel.com

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 0 8701 906777 - For further general health & safety, technical and practical advice on this product, please call +44 (0) 1606 593933 or write to: Technical Services; Henkel Limited; Road 5; Winsford Industrial Estate; Winsford; Cheshire; CW7 3QY- Email: technical.services@henkel.co.uk

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Serious eye irritation

Category 2

H319 Causes serious eye irritation.

Chronic hazards to the aquatic environment

Category 3

H412 Harmful to aquatic life with long lasting effects.

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Signal word:

Warning

Hazard statement: H319 Causes serious eye irritation.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statement: P273 Avoid release to the environment.
Prevention P280 Wear eye protection.

2.3. Other hazards

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General chemical description:

Polyurethane adhesive

Base substances of preparation:

Polyether polyols

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
1,1',1'',1'''-Ethylenedinitrilotetrapropan-2-ol 102-60-3	203-041-4 01-2119552434-41	10- < 20 %	Eye Irrit. 2 H319
Butane-1,4-diol 110-63-4	203-786-5 01-2119471849-20	1- < 3 %	Acute Tox. 4; Oral H302 STOT SE 3 H336
Diethylmethylbenzenediamine 68479-98-1	270-877-4 01-2119486805-25	0,25- < 2,5 %	Acute Tox. 4; Oral H302 STOT RE 2 H373 Eye Irrit. 2 H319 Aquatic Acute 1 H400 Aquatic Chronic 1 H410 Acute Tox. 4; Dermal H312

For full text of the H - statements and other abbreviations see section 16 "Other information".
Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Move to fresh air, consult doctor if complaint persists.

Skin contact:

Rinse with running water and soap. Apply replenishing cream. Change all contaminated clothing.

Eye contact:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

EYE: Irritation, conjunctivitis.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media:**

All common extinguishing agents are suitable.

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In case of fire toxic gases can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus.

Wear protective equipment.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Wear protective equipment.

Keep unprotected persons away.

Avoid contact with skin and eyes.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

Inform authorities in the event of product spillage to water courses or sewage systems.

6.3. Methods and material for containment and cleaning up

Remove mechanically.

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Hygiene measures:

Do not eat, drink or smoke while working.

Wash hands before work breaks and after finishing work.

7.2. Conditions for safe storage, including any incompatibilities

Ensure good ventilation/extraction.

Store in a cool, dry place.

Temperatures between + 10 °C and + 25 °C

Protect from direct sun-light and temperature above 50°C in any case.

7.3. Specific end use(s)

2-Component polyurethane adhesive

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for
Great Britain

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Limestone 1317-65-3 [CALCIUM CARBONATE, INHALABLE DUST]		10	Time Weighted Average (TWA):		EH40 WEL
Limestone 1317-65-3 [CALCIUM CARBONATE, RESPIRABLE DUST]		4	Time Weighted Average (TWA):		EH40 WEL
Limestone 1317-65-3 [LIMESTONE, RESPIRABLE MARBLE, RESPIRABLE]		4	Time Weighted Average (TWA):		EH40 WEL
Limestone 1317-65-3 [LIMESTONE, TOTAL INHALABLE MARBLE, TOTAL INHALABLE]		10	Time Weighted Average (TWA):		EH40 WEL
Calcium carbonate 471-34-1 [CALCIUM CARBONATE, INHALABLE DUST]		10	Time Weighted Average (TWA):		EH40 WEL
Calcium carbonate 471-34-1 [CALCIUM CARBONATE, RESPIRABLE DUST]		4	Time Weighted Average (TWA):		EH40 WEL
Calcium carbonate 471-34-1 [LIMESTONE, RESPIRABLE MARBLE, RESPIRABLE]		4	Time Weighted Average (TWA):		EH40 WEL
Calcium carbonate 471-34-1 [LIMESTONE, TOTAL INHALABLE MARBLE, TOTAL INHALABLE]		10	Time Weighted Average (TWA):		EH40 WEL
Zeolites 68989-22-0 [ALUMINIUM OXIDES, INHALABLE DUST]		10	Time Weighted Average (TWA):		EH40 WEL
Zeolites 68989-22-0 [ALUMINIUM OXIDES, RESPIRABLE DUST]		4	Time Weighted Average (TWA):		EH40 WEL

Occupational Exposure Limits

Valid for
Ireland

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Limestone 1317-65-3 [CALCIUM CARBONATE, RESPIRABLE DUST]		4	Time Weighted Average (TWA):		IR_OEL
Limestone 1317-65-3 [CALCIUM CARBONATE, TOTAL INHALABLE DUST]		10	Time Weighted Average (TWA):		IR_OEL
Calcium carbonate 471-34-1 [CALCIUM CARBONATE, RESPIRABLE DUST]		4	Time Weighted Average (TWA):		IR_OEL
Calcium carbonate 471-34-1		10	Time Weighted Average (TWA):		IR_OEL

[CALCIUM CARBONATE, TOTAL INHALABLE DUST]					
---	--	--	--	--	--

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
1,1',1'',1'''-Ethylenedinitrilotetrapropan-2-ol 102-60-3	aqua (freshwater)		0,085 mg/l				
1,1',1'',1'''-Ethylenedinitrilotetrapropan-2-ol 102-60-3	aqua (marine water)		0,0085 mg/l				
1,1',1'',1'''-Ethylenedinitrilotetrapropan-2-ol 102-60-3	aqua (intermittent releases)		1,51 mg/l				
1,1',1'',1'''-Ethylenedinitrilotetrapropan-2-ol 102-60-3	sewage treatment plant (STP)		70 mg/l				
1,1',1'',1'''-Ethylenedinitrilotetrapropan-2-ol 102-60-3	sediment (freshwater)				0,193 mg/kg		
1,1',1'',1'''-Ethylenedinitrilotetrapropan-2-ol 102-60-3	sediment (marine water)				0,0193 mg/kg		
1,1',1'',1'''-Ethylenedinitrilotetrapropan-2-ol 102-60-3	Soil				0,0183 mg/kg		
Butane-1,4-diol 110-63-4	aqua (marine water)		0,0813 mg/l				
Butane-1,4-diol 110-63-4	aqua (intermittent releases)		8,13 mg/l				
Butane-1,4-diol 110-63-4	sediment (freshwater)				3,61 mg/kg		
Butane-1,4-diol 110-63-4	sediment (marine water)				0,361 mg/kg		
Butane-1,4-diol 110-63-4	Soil				0,244 mg/kg		
Butane-1,4-diol 110-63-4	sewage treatment plant (STP)		1554 mg/l				
Butane-1,4-diol 110-63-4	aqua (freshwater)		0,813 mg/l				
Diethylmethylbenzenediamine 68479-98-1	aqua (freshwater)		0,0005 mg/l				
Diethylmethylbenzenediamine 68479-98-1	sediment (freshwater)				0,029 mg/kg		
Diethylmethylbenzenediamine 68479-98-1	aqua (marine water)		0,00005 mg/l				
Diethylmethylbenzenediamine 68479-98-1	sediment (marine water)				0,0029 mg/kg		
Diethylmethylbenzenediamine 68479-98-1	Soil				0,0056 mg/kg		
Diethylmethylbenzenediamine 68479-98-1	sewage treatment plant (STP)		17 mg/l				
Diethylmethylbenzenediamine 68479-98-1	aqua (intermittent releases)		0,005 mg/l				
Diethylmethylbenzenediamine 68479-98-1	oral				2 mg/kg		

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
1,1',1'',1'''-Ethylenedinitrilotetrapropan-2-ol 102-60-3	Workers	dermal	Long term exposure - systemic effects		4,2 mg/kg	
1,1',1'',1'''-Ethylenedinitrilotetrapropan-2-ol 102-60-3	Workers	Inhalation	Long term exposure - systemic effects		29,4 mg/m ³	
1,1',1'',1'''-Ethylenedinitrilotetrapropan-2-ol 102-60-3	General population	dermal	Long term exposure - systemic effects		2,5 mg/kg	
1,1',1'',1'''-Ethylenedinitrilotetrapropan-2-ol 102-60-3	General population	Inhalation	Long term exposure - systemic effects		8,7 mg/m ³	
1,1',1'',1'''-Ethylenedinitrilotetrapropan-2-ol 102-60-3	General population	oral	Long term exposure - systemic effects		2,5 mg/kg	
Butane-1,4-diol 110-63-4	Workers	dermal	Long term exposure - systemic effects		19 mg/kg	
Butane-1,4-diol 110-63-4	Workers	Inhalation	Long term exposure - systemic effects		136 mg/m ³	
Butane-1,4-diol 110-63-4	Workers	inhalation	Acute/short term exposure - systemic effects		958 mg/m ³	
Butane-1,4-diol 110-63-4	General population	Inhalation	Acute/short term exposure - systemic effects		340 mg/m ³	
Butane-1,4-diol 110-63-4	General population	inhalation	Long term exposure - systemic effects		29 mg/m ³	
Butane-1,4-diol 110-63-4	General population	dermal	Long term exposure - systemic effects		8 mg/kg	
Butane-1,4-diol 110-63-4	General population	oral	Long term exposure - systemic effects		8 mg/kg	
Diethylmethylbenzenediamine 68479-98-1	Workers	inhalation	Long term exposure - systemic effects		0,13 mg/m ³	
Diethylmethylbenzenediamine 68479-98-1	Workers	dermal	Long term exposure - systemic effects		1 mg/kg	
Diethylmethylbenzenediamine 68479-98-1	General population	oral	Long term exposure - systemic effects		0,1 mg/kg	
Diethylmethylbenzenediamine 68479-98-1	General population	dermal	Long term exposure - systemic effects		1 mg/kg	
Diethylmethylbenzenediamine 68479-98-1	General population	inhalation	Long term exposure - systemic effects		0,1 mg/m ³	

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

Ensure good ventilation/suction at the workplace.

Hand protection:

Chemical-resistant protective gloves (EN 374). Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374): Polychloroprene (CR; ≥ 1 mm thickness) or natural rubber (NR; ≥ 1 mm thickness) Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374): Polychloroprene (CR; ≥ 1 mm thickness) or natural rubber (NR; ≥ 1 mm thickness) This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Goggles which can be tightly sealed.

Protective eye equipment should conform to EN166.

Skin protection:

Protective clothing that covers arms and legs.

Wear protective equipment.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

Use only personal protection that's CE-labelled according to Directive 89/686/EEC (Europe) or to Regulation No. 819 of 19 August 1994 (Norway).

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.

Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	paste paste grey
Odor	characteristic
Odour threshold	No data available / Not applicable
pH	No data available / Not applicable
Melting point	No data available / Not applicable
Solidification temperature	No data available / Not applicable
Initial boiling point	No data available / Not applicable
Flash point	> 130 °C (> 266 °F)
Evaporation rate	No data available / Not applicable
Flammability	No data available / Not applicable
Explosive limits	No data available / Not applicable
Vapour pressure	No data available / Not applicable
Relative vapour density:	No data available / Not applicable
Density (20 °C (68 °F))	1,6 - 1,7 g/cm ³
Bulk density	No data available / Not applicable
Solubility	No data available / Not applicable
Solubility (qualitative)	No data available / Not applicable
Partition coefficient: n-octanol/water	No data available / Not applicable
Auto-ignition temperature	No data available / Not applicable
Decomposition temperature	No data available / Not applicable
Viscosity (Bingham; 35 °C (95 °F))	16.000 mPa.s
Viscosity (kinematic)	No data available / Not applicable
Explosive properties	No data available / Not applicable
Oxidising properties	No data available / Not applicable

9.2. Other information

No data available / Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

None if used for intended purpose.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

None if used for intended purpose.

10.5. Incompatible materials

None if used properly.

10.6. Hazardous decomposition products

No decomposition if used according to specifications.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
1,1',1'',1'''- Ethylenedinitrilotetraprop an-2-ol 102-60-3	LD50	2.890 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Butane-1,4-diol 110-63-4	LD50	1.500 mg/kg	rat	BASF Test
Diethylmethylbenzenedia mine 68479-98-1	LD50	738 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
1,1',1'',1'''- Ethylenedinitrilotetraprop an-2-ol 102-60-3	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Butane-1,4-diol 110-63-4	LD50	> 2.000 mg/kg	rat	BASF Test

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
Butane-1,4-diol 110-63-4	LC50	> 5,1 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
1,1',1'',1'''- Ethylenedinitrilotetraprop an-2-ol 102-60-3	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
1,1',1'',1'''- Ethylenedinitrilotetraprop an-2-ol 102-60-3	irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
1,1',1'',1'''- Ethylenedinitrilotetraprop an-2-ol 102-60-3	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
1,1',1'',1'''- Ethylenedinitrilotetraprop an-2-ol 102-60-3	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
1,1',1'',1'''- Ethylenedinitrilotetraprop an-2-ol 102-60-3	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
1,1',1'',1'''- Ethylenedinitrilotetraprop an-2-ol 102-60-3	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Butane-1,4-diol 110-63-4	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)

Carcinogenicity

No data available.

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
1,1',1'',1'''- Ethylenedinitrilotetraprop an-2-ol 102-60-3	NOAEL P 1.000 mg/kg NOAEL F1 1.000 mg/kg	screening	oral: gavage	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

STOT-single exposure:

No data available.

STOT-repeated exposure::

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
1,1',1'',1'''- Ethylenedinitrilotetraprop an-2-ol 102-60-3	NOAEL 300 mg/kg	oral: gavage	30-49 d daily	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Diethylmethylbenzenedia mine 68479-98-1	NOAEL >= 8 mg/kg	oral: feed	90 days Daily for 90 days	rat	EU Method B.26 (Sub- Chronic Oral Toxicity Test: Repeated Dose 90- Day Oral Toxicity Study in Rodents)

Aspiration hazard:

No data available.

SECTION 12: Ecological information

General ecological information:

Do not empty into drains, soil or bodies of water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
1,1',1'',1'''- Ethylenedinitrilotetrapropan- 2-ol 102-60-3	LC50	> 2.000 mg/l	96 h	Leuciscus idus	OECD Guideline 203 (Fish, Acute Toxicity Test)
Butane-1,4-diol 110-63-4	LC50	> 10.000 mg/l	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
Diethylmethylbenzenediamine 68479-98-1	LC50	194 mg/l	48 h	Leuciscus idus	OECD Guideline 203 (Fish, Acute Toxicity Test)

Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Butane-1,4-diol 110-63-4	EC50	> 500 mg/l	24 h	other aquatic arthropod:	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Diethylmethylbenzenediamine 68479-98-1	EC50	0,5 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Butane-1,4-diol 110-63-4	NOEC	> 85 mg/l	21 d	Daphnia magna	not specified

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Butane-1,4-diol 110-63-4	EC50	> 500 mg/l	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Butane-1,4-diol 110-63-4	EC10	83 mg/l	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
1,1',1'',1'''- Ethylenedinitrilotetrapropan- 2-ol 102-60-3	EC0	> 1.000 mg/l			not specified
Butane-1,4-diol 110-63-4	EC10	10.000 mg/l	16 h		not specified
Diethylmethylbenzenediamine 68479-98-1	EC10	170 mg/l	24 h		not specified

12.2. Persistence and degradability

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
1,1',1'',1'''- Ethylenedinitrilotetrapropan- 2-ol 102-60-3	not readily biodegradable.	aerobic	49 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Butane-1,4-diol 110-63-4	readily biodegradable	aerobic	74 - 96 %	14 d	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))
Butane-1,4-diol 110-63-4	inherently biodegradable	aerobic	90 - 100 %	7 d	OECD Guideline 302 B (Inherent biodegradability: Zahn- Wellens/EMPA Test)
Diethylmethylbenzenediamine 68479-98-1		aerobic	0 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

Hazardous substances CAS-No.	LogPow	Temperature	Method
1,1',1'',1'''-Ethylenedinitrilotetrapropan-2-ol 102-60-3	-2,08		not specified
Butane-1,4-diol 110-63-4	-0,88	25 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)

12.5. Results of PBT and vPvB assessment

Hazardous substances CAS-No.	PBT / vPvB
1,1',1'',1'''-Ethylenedinitrilotetrapropan-2-ol 102-60-3	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Butane-1,4-diol 110-63-4	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Diethylmethylbenzenediamine 68479-98-1	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

In consultation with the responsible local authority, must be subjected to special treatment.

Waste code

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.
080409

SECTION 14: Transport information

14.1. UN number

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.2. UN proper shipping name

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.3. Transport hazard class(es)

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.4. Packing group

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.5. Environmental hazards

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.6. Special precautions for user

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

VOC content	0 %
(VOCV 814.018 VOC regulation CH)	
VOC content	3 %
(2010/75/EU)	

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (ua-productsafety.de@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.



Safety Data Sheet according to Regulation (EC) No 1907/2006

Page 1 of 14

TEROSON PU 9225 SF ME

SDS No. : 456429

V003.2

Revision: 25.06.2019

printing date: 13.08.2020

Replaces version from: 14.11.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

TEROSON PU 9225 SF ME

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Part B for 2-K-Polyurethane adhesive and sealant

1.3. Details of the supplier of the safety data sheet

Henkel Ltd

Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 1442 278000

Fax-no.: +44 1442 278071

ua-productsafety.uk@henkel.com

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 0 8701 906777 - For further general health & safety, technical and practical advice on this product, please call +44 (0) 1606 593933 or write to: Technical Services; Henkel Limited; Road 5; Winsford Industrial Estate; Winsford; Cheshire; CW7 3QY- Email: technical.services@henkel.co.uk

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Acute toxicity

Category 4

H332 Harmful if inhaled.

Route of Exposure: Inhalation

Skin sensitizer

Category 1

H317 May cause an allergic skin reaction.

Specific target organ toxicity - single exposure

Category 3

H335 May cause respiratory irritation.

Target organ: respiratory tract irritation

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Contains

Hexane, 1,6-diisocyanato-, homopolymer, V=2750-4250 mPas/23

Hexamethylene diisocyanate

Signal word:	Warning
Hazard statement:	H317 May cause an allergic skin reaction. H332 Harmful if inhaled. H335 May cause respiratory irritation.
Precautionary statement:	P261 Avoid breathing vapors.
Prevention	P280 Wear protective gloves.

2.3. Other hazards

Persons suffering from allergic reactions to isocyanates should avoid contact with the product.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****General chemical description:**

2-Component polyurethane adhesive

Base substances of preparation:

Polyurethane prepolymer with isocyanate groups

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Hexane, 1,6-diisocyanato-, homopolymer, V=2750-4250 mPas/23 28182-81-2	500-060-2 01-2119485796-17	60- 80 %	Acute Tox. 4 H332 STOT SE 3 H335 Skin Sens. 1 H317
Cristobalite, (RCS >=1% - <10%) 14464-46-1	238-455-4	1- < 5 %	STOT RE 2; Inhalation H373
Hexamethylene diisocyanate 822-06-0	212-485-8 01-2119457571-37	0,1- < 0,2 %	Acute Tox. 4; Oral H302 Acute Tox. 1; Inhalation - vapour H330 Skin Irrit. 2 H315 Skin Sens. 1 H317 Resp. Sens. 1 H334 STOT SE 3 H335 Eye Irrit. 2 H319

For full text of the H - statements and other abbreviations see section 16 "Other information".

Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures**4.1. Description of first aid measures**

Inhalation:

Fresh air, oxygen supply, warmth; seek specialist medical attention.

Skin contact:

IF ON SKIN: Wash with plenty of soap and water.

In case of adverse health effects seek medical advice.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

SKIN: Rash, Urticaria.

RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media:**

All common extinguishing agents are suitable.

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In case of fire toxic gases can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus.

Wear protective equipment.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Avoid contact with skin and eyes.

Wear protective equipment.

Keep unprotected persons away.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Remove mechanically.

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Hygiene measures:**

Do not eat, drink or smoke while working.

Wash hands before work breaks and after finishing work.

7.2. Conditions for safe storage, including any incompatibilities

Ensure good ventilation/extraction.

Store in a cool, dry place.

Temperatures between + 10 °C and + 25 °C

Protect from direct sun-light and temperature above 50°C in any case.

7.3. Specific end use(s)

Part B for 2-K-Polyurethane adhesive and sealant

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for
Great Britain

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Silicon dioxide 112926-00-8 [SILICA, AMORPHOUS, INHALABLE DUST]		6	Time Weighted Average (TWA):		EH40 WEL
Silicon dioxide 112926-00-8 [SILICA, AMORPHOUS, RESPIRABLE DUST]		2,4	Time Weighted Average (TWA):		EH40 WEL
Zeolites 1318-02-1 [ALUMINIUM OXIDES, INHALABLE DUST]		10	Time Weighted Average (TWA):		EH40 WEL
Zeolites 1318-02-1 [ALUMINIUM OXIDES, RESPIRABLE DUST]		4	Time Weighted Average (TWA):		EH40 WEL
Cristobalite 14464-46-1 [SILICA, RESPIRABLE CRYSTALLINE]		0,1	Time Weighted Average (TWA):		EH40 WEL
Cristobalite 14464-46-1 [RESPIRABLE CRYSTALLINE SILICA DUST, RESPIRABLE FRACTION]		0,1	Time Weighted Average (TWA):		EU OELIII
Hexamethylene diisocyanate 822-06-0 [ISOCYANATES, ALL (AS -NCO)]		0,07	Short Term Exposure Limit (STEL):		EH40 WEL
Hexamethylene diisocyanate 822-06-0 [ISOCYANATES, ALL (AS -NCO)]		0,02	Time Weighted Average (TWA):		EH40 WEL

Occupational Exposure Limits

Valid for
Ireland

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Silicon dioxide 112926-00-8 [SILICA, AMORPHOUS, TOTAL INHALABLE DUST]		6	Time Weighted Average (TWA):		IR_OEL
Silicon dioxide 112926-00-8 [SILICA, AMORPHOUS, RESPIRABLE DUST]		2,4	Time Weighted Average (TWA):		IR_OEL
Cristobalite 14464-46-1 [CRISTOBALITE, RESPIRABLE DUST (SEE CRYSTALLINE SILICA)]		0,1	Time Weighted Average (TWA):		IR_OEL
Cristobalite 14464-46-1 [RESPIRABLE CRYSTALLINE SILICA DUST, RESPIRABLE FRACTION]		0,1	Time Weighted Average (TWA):		EU OELIII
Hexamethylene diisocyanate 822-06-0 [HEXAMETHYLENE DIISOCYANATE (AS -NCO)]	0,005		Time Weighted Average (TWA):		IR_OEL

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
Hexane, 1,6-diisocyanato-, homopolymer 28182-81-2	aqua (freshwater)		0,127 mg/l				
Hexane, 1,6-diisocyanato-, homopolymer 28182-81-2	aqua (marine water)		0,013 mg/l				
Hexane, 1,6-diisocyanato-, homopolymer 28182-81-2	aqua (intermittent releases)		1,27 mg/l				
Hexane, 1,6-diisocyanato-, homopolymer 28182-81-2	sediment (freshwater)				266701 mg/kg		
Hexane, 1,6-diisocyanato-, homopolymer 28182-81-2	sediment (marine water)				26670 mg/kg		
Hexane, 1,6-diisocyanato-, homopolymer 28182-81-2	Soil				53183 mg/kg		
Hexane, 1,6-diisocyanato-, homopolymer 28182-81-2	sewage treatment plant (STP)		88 mg/l				
Hexamethylene diisocyanate 822-06-0	aqua (freshwater)		> 0,0774 mg/l				
Hexamethylene diisocyanate 822-06-0	aqua (marine water)		> 0,00774 mg/l				
Hexamethylene diisocyanate 822-06-0	sewage treatment plant (STP)		8,42 mg/l				
Hexamethylene diisocyanate 822-06-0	sediment (freshwater)				> 0,01334 mg/kg		
Hexamethylene diisocyanate 822-06-0	sediment (marine water)				> 0,001334 mg/kg		
Hexamethylene diisocyanate 822-06-0	Soil				> 0,0026 mg/kg		
Hexamethylene diisocyanate 822-06-0	aqua (intermittent releases)		0,774 mg/l				

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Hexane, 1,6-diisocyanato-, homopolymer 28182-81-2	Workers	inhalation	Acute/short term exposure - local effects		1 mg/m3	
Hexane, 1,6-diisocyanato-, homopolymer 28182-81-2	Workers	inhalation	Long term exposure - local effects		0,5 mg/m3	
Hexamethylene diisocyanate 822-06-0	Workers	inhalation	Acute/short term exposure - systemic effects		0,07 mg/m3	
Hexamethylene diisocyanate 822-06-0	Workers	inhalation	Long term exposure - systemic effects		0,035 mg/m3	
Hexamethylene diisocyanate 822-06-0	Workers	inhalation	Long term exposure - local effects		0,035 mg/m3	
Hexamethylene diisocyanate 822-06-0	Workers	inhalation	Acute/short term exposure - local effects		0,07 mg/m3	

Biological Exposure Indices:

Ingredient [Regulated substance]	Parameters	Biological specimen	Sampling time	Conc.	Basis of biol. exposure index	Remark	Additional Information
Hexamethylene diisocyanate 822-06-0 [ISOCYANATES (APPLIES TO HDI, IPDI, TDI AND MDI)]	Isocyanate-derived diamine	Creatinine in urine	Sampling time: At the end of the period of exposure.		UKEH40BMG V		

8.2. Exposure controls:

Engineering controls:

Use only in well ventilated areas.

Respiratory protection:

Ensure good ventilation/suction at the workplace.

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Goggles which can be tightly sealed.

Protective eye equipment should conform to EN166.

Skin protection:

Wear protective equipment.

Protective clothing that covers arms and legs.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

Use only personal protection that's CE-labelled according to Directive 89/686/EEC (Europe) or to Regulation No. 819 of 19 August 1994 (Norway).

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.

Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

paste

paste

white

Odor

characteristic

Odour threshold

No data available / Not applicable

pH

No data available / Not applicable

Melting point

No data available / Not applicable

Solidification temperature

No data available / Not applicable

Initial boiling point

No data available / Not applicable

Flash point

> 130 °C (> 266 °F)

Evaporation rate

No data available / Not applicable

Flammability	No data available / Not applicable
Explosive limits	No data available / Not applicable
Vapour pressure	No data available / Not applicable
Relative vapour density:	No data available / Not applicable
Density (20 °C (68 °F))	1,22 - 1,3 g/cm ³
Bulk density	No data available / Not applicable
Solubility	No data available / Not applicable
Solubility (qualitative)	No data available / Not applicable
Partition coefficient: n-octanol/water	No data available / Not applicable
Auto-ignition temperature	No data available / Not applicable
Decomposition temperature	No data available / Not applicable
Viscosity (Bingham; 35 °C (95 °F); speed of rotation: 20 min ⁻¹)	4.000 mPa.s
Viscosity (kinematic)	No data available / Not applicable
Explosive properties	No data available / Not applicable
Oxidising properties	No data available / Not applicable

9.2. Other information

No data available / Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

Reaction with water, alcohols, amines.

Reacts with water: Pressure built up in closed vessel (CO₂).

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

Humidity

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

At higher temperatures isocyanate may be released.

Carbon dioxide is generated under contact with moisture, leading to pressure in the cans. Danger of cans bursting!

SECTION 11: Toxicological information

General toxicological information:

Persons suffering from allergic reactions to isocyanates should avoid contact with the product.

11.1. Information on toxicological effects

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Hexane, 1,6-diisocyanato-, homopolymer, V=2750-4250 mPas/23 28182-81-2	LD50	> 2.500 mg/kg	rat	OECD Guideline 423 (Acute Oral toxicity)
Cristobalite, (RCS >=1% - <10%) 14464-46-1	LD50	3.160 mg/kg	rat	not specified
Hexamethylene diisocyanate 822-06-0	LD50	959 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Hexane, 1,6-diisocyanato-, homopolymer, V=2750-4250 mPas/23 28182-81-2	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Hexamethylene diisocyanate 822-06-0	LD50	> 7.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
Hexane, 1,6-diisocyanato-, homopolymer, V=2750-4250 mPas/23 28182-81-2	Acute toxicity estimate (ATE)	1,5 mg/l	dust/mist			Expert judgement
Hexamethylene diisocyanate 822-06-0	LC50	0,124 mg/l	vapour	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)

Skin corrosion/irritation:

No data available.

Serious eye damage/irritation:

No data available.

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
Hexamethylene diisocyanate 822-06-0	sensitising	Respiratory sensitisation	guinea pig	not specified
Hexamethylene diisocyanate 822-06-0	sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Hexamethylene diisocyanate 822-06-0	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Hexamethylene diisocyanate 822-06-0	negative	mammalian cell gene mutation assay	with and without		not specified
Hexamethylene diisocyanate 822-06-0	negative	inhalation: vapour		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
Hexamethylene diisocyanate 822-06-0	not carcinogenic	inhalation: vapour	2 y 6 h/d, 5 d/w	rat	male/female	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
Hexamethylene diisocyanate 822-06-0	NOAEL P 0.3 ppm NOAEL F1 0.3 ppm	screening	inhalation: vapour	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

STOT-single exposure:

No data available.

STOT-repeated exposure::

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
Hexamethylene diisocyanate 822-06-0	NOAEL 0.005 ppm	inhalation: vapour	2 y 6 h/d, 5 d/w	rat	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

Aspiration hazard:

No data available.

SECTION 12: Ecological information

General ecological information:

Do not empty into drains, soil or bodies of water.

12.1. Toxicity**Toxicity (Fish):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Hexane, 1,6-diisocyanato-, homopolymer, V=2750-4250 mPas/23 28182-81-2	LC50	> 100 mg/l	96 h	Brachydanio rerio (new name: Danio rerio)	OECD Guideline 203 (Fish, Acute Toxicity Test)
Cristobalite, (RCS >=1% - <10%) 14464-46-1	LC50				OECD Guideline 203 (Fish, Acute Toxicity Test)
Hexamethylene diisocyanate 822-06-0	LC50	> 82,8 mg/l	96 h	Brachydanio rerio (new name: Danio rerio)	EU Method C.1 (Acute Toxicity for Fish)

Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Hexane, 1,6-diisocyanato-, homopolymer, V=2750-4250 mPas/23 28182-81-2	EC50	> 100 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Hexamethylene diisocyanate 822-06-0	EC50	> 89,1 mg/l	48 h	Daphnia magna	EU Method C.2 (Acute Toxicity for Daphnia)

Chronic toxicity to aquatic invertebrates

No data available.

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Hexane, 1,6-diisocyanato-, homopolymer, V=2750-4250 mPas/23 28182-81-2	EC50	> 1.000 mg/l	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Algal Growth Inhibition Test)
Hexamethylene diisocyanate 822-06-0	EC50	> 77,4 mg/l	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	EU Method C.3 (Algal Inhibition test)
Hexamethylene diisocyanate 822-06-0	NOEC	11,7 mg/l	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	EU Method C.3 (Algal Inhibition test)

Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Hexane, 1,6-diisocyanato-, homopolymer, V=2750-4250 mPas/23 28182-81-2	EC 50	> 1.000 mg/l	3 h		OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Cristobalite, (RCS >=1% - <10%) 14464-46-1	EC0	> 1.000 mg/l			ISO 8192 (Test for Inhibition of Oxygen Consumption by Activated Sludge)
Hexamethylene diisocyanate 822-06-0	EC 50	842 mg/l	3 h	activated sludge	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

12.2. Persistence and degradability

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Hexane, 1,6-diisocyanato-, homopolymer, V=2750-4250 mPas/23 28182-81-2		aerobic	0 %	28 d	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))
Hexamethylene diisocyanate 822-06-0	not readily biodegradable.	aerobic	42 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)

12.3. Bioaccumulative potential

Hazardous substances CAS-No.	Bioconcentration factor (BCF)	Exposure time	Temperature	Species	Method
Hexane, 1,6-diisocyanato-, homopolymer, V=2750-4250 mPas/23 28182-81-2	3,2			calculation	OECD Guideline 305 (Bioconcentration: Flow-through Fish Test)
Hexamethylene diisocyanate 822-06-0	57,6			calculated	QSAR (Quantitative Structure Activity Relationship)

12.4. Mobility in soil

Hazardous substances CAS-No.	LogPow	Temperature	Method
Hexamethylene diisocyanate 822-06-0	3,20	25 °C	QSAR (Quantitative Structure Activity Relationship)

12.5. Results of PBT and vPvB assessment

Hazardous substances CAS-No.	PBT / vPvB
Hexane, 1,6-diisocyanato-, homopolymer, V=2750-4250 mPas/23 28182-81-2	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Hexamethylene diisocyanate 822-06-0	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

In consultation with the responsible local authority, must be subjected to special treatment.

Waste code

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

080409

SECTION 14: Transport information

14.1. UN number

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.2. UN proper shipping name

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.3. Transport hazard class(es)

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.4. Packing group

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.5. Environmental hazards

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.6. Special precautions for user

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

VOC content	0 %
(VOCV 814.018 VOC regulation CH)	
VOC content	0 %
(2010/75/EU)	

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H302 Harmful if swallowed.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H330 Fatal if inhaled.
H332 Harmful if inhaled.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335 May cause respiratory irritation.
H373 May cause damage to organs through prolonged or repeated exposure.

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (ua-productsafety.de@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.