

# Safety Data Sheet according to Regulation (EC) No 1907/2006

Page 1 of 15

SDS No.: 173274 V005.0

Revision: 06.09.2018

printing date: 13.08.2020

Replaces version from: 24.03.2015

LOCTITE SF 7240 known as Loctite 7240

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

LOCTITE SF 7240 known as Loctite 7240

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: activator

# ${f 1.3.}$ Details of the supplier of the safety data sheet

Henkel Ltd Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 1442 278000 Fax-no.: +44 1442 278071

ua-productsafety.uk@henkel.com

# 1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

## **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

#### Classification (CLP):

Skin sensitizer Category 1

H317 May cause an allergic skin reaction.

Chronic hazards to the aquatic environment Category 3

H412 Harmful to aquatic life with long lasting effects.

### 2.2. Label elements

#### Label elements (CLP):



Contains Hydroxypropyl methacrylate

2,2'-Ethylenedioxydiethyl dimethacrylate

Limonene, D-

Signal word:	Warning
Hazard statement:	H317 May cause an allergic skin reaction. H412 Harmful to aquatic life with long lasting effects.
Precautionary statement: Prevention	P273 Avoid release to the environment. P280 Wear protective gloves.
Precautionary statement: Response	P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

### 2.3. Other hazards

None if used properly.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

# **SECTION 3: Composition/information on ingredients**

## 3.2. Mixtures

## General chemical description:

Activator

### Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components	EC Number	content	Classification
CAS-No.	REACH-Reg No.	2.5 10.0/	01: 0 1
Hydroxypropyl methacrylate	248-666-3	2,5-< 10 %	Skin Sens. 1
27813-02-1	01-2119490226-37		H317
			Eye Irrit. 2 H319
2.21 Eduator di condicatori di conde condete	203-652-6	50 100 o/	Skin Sens. 1B
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0		50- 100 %	H317
109-16-0	01-2119969287-21		H317
Limonene, D-	227-813-5	0,25-< 1 %	Flam. Liq. 3
5989-27-5	01-2119529223-47		H226
			Aquatic Acute 1
			H400
			Skin Irrit. 2
			H315
			Skin Sens. 1
			H317
			Aquatic Chronic 1
			H410
			Asp. Tox. 1
			H304
Copper naphthenate	215-657-0	0,25-< 1 %	Flam. Liq. 3
1338-02-9			H226
			Acute Tox. 4; Oral
			H302
			Aquatic Acute 1
			H400
			Aquatic Chronic 1
			H410

For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

# **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Seek medical advice.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.

Ingestion:

Rinse out mouth, drink 1-2 glasses of water, do not induce vomiting.

Seek medical advice.

#### 4.2. Most important symptoms and effects, both acute and delayed

SKIN: Rash, Urticaria.

Prolonged or repeated contact may cause eye irritation.

#### 4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

## **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

#### Suitable extinguishing media:

Carbon dioxide, foam, powder

#### Extinguishing media which must not be used for safety reasons:

None known

#### 5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx) can be released.

#### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

#### Additional information:

In case of fire, keep containers cool with water spray.

### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes.

Wear protective equipment.

Ensure adequate ventilation.

### 6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

#### 6.3. Methods and material for containment and cleaning up

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

Dispose of contaminated material as waste according to Section 13.

#### 6.4. Reference to other sections

See advice in section 8

## **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Avoid skin and eye contact.

See advice in section 8

Use only in well-ventilated areas.

Prolonged or repeated skin contact should be avoided to minimise any risk of sensitisation.

Hygiene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

Good industrial hygiene practices should be observed.

### 7.2. Conditions for safe storage, including any incompatibilities

Refer to Technical Data Sheet

### 7.3. Specific end use(s)

activator

# **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

## **Occupational Exposure Limits**

Valid for

Great Britain

None

## **Occupational Exposure Limits**

Valid for

Ireland

None

# $\label{eq:predicted} \textbf{Predicted No-Effect Concentration (PNEC):}$

Name on list	on list Environmental Exposure Value Compartment period				Remarks		
	•		mg/l	ppm	mg/kg	others	
Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1	aqua (freshwater)		0,904 mg/l				
Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1	aqua (marine water)		0,904 mg/l				
Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1	sewage treatment plant (STP)		10 mg/l				
Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1	aqua (intermittent releases)		0,972 mg/l				
Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1	sediment (freshwater)				6,28 mg/kg		
Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1	sediment (marine water)				6,28 mg/kg		
Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1	Soil				0,727 mg/kg		
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	aqua (freshwater)		0,164 mg/l				
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	aqua (marine water)		0,0164 mg/l				
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	sewage treatment plant (STP)		10 mg/l				
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	aqua (intermittent releases)		0,164 mg/l				
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	sediment (freshwater)				1,85 mg/kg		
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	sediment (marine water)				0,185 mg/kg		
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	Soil				0,274 mg/kg		
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	Air						
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	Predator						

#### **Derived No-Effect Level (DNEL):**

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1	Workers	dermal	Long term exposure - systemic effects		4,2 mg/kg	
Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1	Workers	Inhalation	Long term exposure - systemic effects		14,7 mg/m3	
Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1	General population	dermal	Long term exposure - systemic effects		2,5 mg/kg	
Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1	General population	Inhalation	Long term exposure - systemic effects		8,8 mg/m3	
Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1	General population	oral	Long term exposure - systemic effects		2,5 mg/kg	
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	Workers	inhalation	Long term exposure - systemic effects		48,5 mg/m3	
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	Workers	dermal	Long term exposure - systemic effects		13,9 mg/kg	
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	General population	inhalation	Long term exposure - systemic effects		14,5 mg/m3	
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	General population	dermal	Long term exposure - systemic effects		8,33 mg/kg	
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	General population	oral	Long term exposure - systemic effects		8,33 mg/kg	

#### **Biological Exposure Indices:**

None

## 8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

Use only in well-ventilated areas.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

### Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Wear protective glasses.

Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

### **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Appearance liquid liquid

green

Odor Acrylic

Odour threshold No data available / Not applicable

pH No data available / Not applicable
Melting point No data available / Not applicable
Solidification temperature No data available / Not applicable

Initial boiling point Not applicable Flash point 95 °C (203 °F)

Evaporation rate No data available / Not applicable Flammability No data available / Not applicable Explosive limits No data available / Not applicable

Vapour pressure Not applicable

Relative vapour density: No data available / Not applicable

Density 1,07 g/cm3

()
Bulk density
No data available / Not applicable
Solubility
No data available / Not applicable

Solubility (qualitative) Not miscible

(Solvent: Water)

Solubility (qualitative) Partially soluble

(Solvent: Acetone)

Partition coefficient: n-octanol/water

Auto-ignition temperature

Decomposition temperature

Viscosity

Viscosity

No data available / Not applicable

Viscosity (kinematic)

No data available / Not applicable

Explosive properties

No data available / Not applicable

Oxidising properties

No data available / Not applicable

### 9.2. Other information

No data available / Not applicable

## **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

Reaction with strong acids. Reacts with strong oxidants.

#### 10.2. Chemical stability

Stable under recommended storage conditions.

### 10.3. Possibility of hazardous reactions

See section reactivity

# 10.4. Conditions to avoid

Stable

#### 10.5. Incompatible materials

See section reactivity.

#### 10.6. Hazardous decomposition products

Irritating organic vapours.

# **SECTION 11: Toxicological information**

#### General toxicological information:

Prolonged or repeated contact may cause eye irritation.

## 11.1. Information on toxicological effects

### Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Species	Method
CAS-No.	type			
Hydroxypropyl	LD50	> 2.000  mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
methacrylate				
27813-02-1				
2,2'-Ethylenedioxydiethyl	LD50	10.837 mg/kg	rat	not specified
	LD30	10.657 mg/kg	Tat	not specified
dimethacrylate				
109-16-0				
Limonene, D-	LD50	> 5.000  mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
5989-27-5				` '
Copper naphthenate	LD50	2.000 mg/kg	rat	not specified
1338-02-9	2200	2.000 mg ng		not openied

### Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Hydroxypropyl methacrylate 27813-02-1	LD50	> 5.000 mg/kg	rabbit	not specified
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	LD50	> 2.000 mg/kg	mouse	not specified
Limonene, D- 5989-27-5	LD50	> 5.000 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
Copper naphthenate 1338-02-9	LD50	> 5.000 mg/kg	rabbit	
Copper naphthenate 1338-02-9	LD50	> 7.940 mg/kg	rabbit	

### Acute inhalative toxicity:

No data available.

### Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Result	Exposure	Species	Method
CAS-No.		time		
Hydroxypropyl	not irritating	24 h	rabbit	Draize Test
methacrylate				
27813-02-1				
2,2'-Ethylenedioxydiethyl	not irritating	24 h	rabbit	Draize Test
dimethacrylate				
109-16-0				
Limonene, D-	moderately	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
5989-27-5	irritating			

## Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Result	Exposure	Species	Method
CAS-No.		time		
2,2'-Ethylenedioxydiethyl	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
dimethacrylate				
109-16-0				
Limonene, D-	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
5989-27-5				

## Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances	Result	Test type	Species	Method
CAS-No.				
2,2'-Ethylenedioxydiethyl	sensitising	Mouse local lymphnode	mouse	OECD Guideline 429 (Skin Sensitisation:
dimethacrylate		assay (LLNA)		Local Lymph Node Assay)
109-16-0		•		
Limonene, D-	sensitising	Mouse local lymphnode	mouse	OECD Guideline 429 (Skin Sensitisation:
5989-27-5		assay (LLNA)		Local Lymph Node Assay)

## Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Hydroxypropyl methacrylate 27813-02-1	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Hydroxypropyl methacrylate 27813-02-1	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	negative	in vitro mammalian cell micronucleus test	with and without		OECD Guideline 487 (In vitro Mammalian Cell Micronucleus Test)
Limonene, D- 5989-27-5	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Limonene, D- 5989-27-5	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Limonene, D- 5989-27-5	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Limonene, D- 5989-27-5	negative	sister chromatid exchange assay in mammalian cells	with and without		OECD Guideline 479 (Genetic Toxicology: In Vitro Sister Chromatid Exchange Assay in Mammalian Cells)

## Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
Hydroxypropyl methacrylate 27813-02-1	not carcinogenic	inhalation	2 years (102 weeks) 6 hours/day, 5 days/week	rat	male	OECD Guideline 451 (Carcinogenicity Studies)

# Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances	Result / Value	Test type	Route of	Species	Method
CAS-No.			application		
Hydroxypropyl	NOAEL P 400 mg/kg	two-	oral: gavage	rat	OECD Guideline 416 (Two-
methacrylate		generation			Generation Reproduction
27813-02-1		study			Toxicity Study)
2,2'-Ethylenedioxydiethyl	NOAEL P 1.000 mg/kg		oral: gavage	rat	OECD Guideline 422
dimethacrylate					(Combined Repeated Dose
109-16-0	NOAEL F1 1.000 mg/kg				Toxicity Study with the
					Reproduction /
					Developmental Toxicity
					Screening Test)

## STOT-single exposure:

No data available.

# STOT-repeated exposure::

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
Hydroxypropyl methacrylate 27813-02-1	NOAEL 300 mg/kg	oral: gavage		rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	NOAEL 1.000 mg/kg	oral: gavage	daily	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Limonene, D- 5989-27-5	NOAEL 825 mg/kg	oral: gavage	16 d Once per day; 5 days/week	rat	OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)
Limonene, D- 5989-27-5	NOAEL 600 mg/kg	oral: gavage	13 w Once per day; 5 days/week	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

## Aspiration hazard:

No data available.

# **SECTION 12: Ecological information**

# General ecological information:

Do not empty into drains / surface water / ground water.

## 12.1. Toxicity

## **Toxicity (Fish):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Hydroxypropyl methacrylate 27813-02-1	LC50	493 mg/l	48 h	Leuciscus idus melanotus	DIN 38412-15
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	LC50	16,4 mg/l	96 h	Danio rerio	OECD Guideline 203 (Fish, Acute Toxicity Test)
Limonene, D- 5989-27-5	LC50	0,702 mg/l	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
Copper naphthenate 1338-02-9	LC50	0,161 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)

## Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Hydroxypropyl methacrylate	EC50	> 143 mg/l	48 h	Daphnia magna	OECD Guideline 202
27813-02-1					(Daphnia sp. Acute
					Immobilisation Test)
Limonene, D-	EC50	577 μg/l	48 h	Daphnia magna	OECD Guideline 202
5989-27-5					(Daphnia sp. Acute
					Immobilisation Test)

## Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Hydroxypropyl methacrylate	NOEC	45,2 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia
27813-02-1					magna, Reproduction Test)
2,2'-Ethylenedioxydiethyl	NOEC	32 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia
dimethacrylate					magna, Reproduction Test)
109-16-0					

## Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Hydroxypropyl methacrylate 27813-02-1	EC50	> 97,2 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Hydroxypropyl methacrylate 27813-02-1	NOEC	> 97,2 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	EC50	> 100 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	NOEC	18,6 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)

## Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Hydroxypropyl methacrylate	EC10	1.140 mg/l	16 h		not specified
27813-02-1					

## 12.2. Persistence and degradability

No data available.

Hazardous substances	Result	Test type	Degradability	Exposure	Method
CAS-No.				time	
Hydroxypropyl methacrylate	readily biodegradable	aerobic	94,2 %	28 d	OECD Guideline 301 E (Ready
27813-02-1					biodegradability: Modified OECD
					Screening Test)
2,2'-Ethylenedioxydiethyl	readily biodegradable	aerobic	85 %	28 d	OECD Guideline 301 B (Ready
dimethacrylate					Biodegradability: CO2 Evolution
109-16-0					Test)
Limonene, D-	readily biodegradable		41 - 98 %	14 d	OECD Guideline 301 C (Ready
5989-27-5					Biodegradability: Modified MITI
					Test (I))

### 12.3. Bioaccumulative potential

Does not bioaccumulate.

No substance data available.

# 12.4. Mobility in soil

Cured adhesives are immobile.

Hazardous substances	LogPow	Temperature	Method
CAS-No.			
Hydroxypropyl methacrylate 27813-02-1	0,97	20 °C	not specified
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	2,3		OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
Limonene, D- 5989-27-5	4,57		not specified

#### 12.5. Results of PBT and vPvB assessment

Hazardous substances	PBT / vPvB
CAS-No.	
Hydroxypropyl methacrylate	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
27813-02-1	Bioaccumulative (vPvB) criteria.
2,2'-Ethylenedioxydiethyl dimethacrylate	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
109-16-0	Bioaccumulative (vPvB) criteria.

#### 12.6. Other adverse effects

No data available.

# **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Product disposal:

Dispose of in accordance with local and national regulations.

Collection and delivery to recycling enterprise or other registered elimination institution.

#### Disposal of uncleaned packages:

will be happy to advise you.

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

### Waste code

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances
The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes
for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We

# **SECTION 14: Transport information**

### 14.1. UN number

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

#### 14.2. UN proper shipping name

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

#### 14.3. Transport hazard class(es)

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

## 14.4. Packing group

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

#### 14.5. Environmental hazards

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

### 14.6. Special precautions for user

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

## **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC content <3 % (2010/75/EC)

## 15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

## **SECTION 16: Other information**

The labelling of the product is indicated in Section 2. The full text

of all abbreviations indicated by codes in this safety data sheet are as follows:

H226 Flammable liquid and vapor.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

#### **Further information:**

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (ua-productsafety.de@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.