



Safety Data Sheet according to Regulation (EC) No 1907/2006

Page 1 of 15

SDS No. : 179512
V009.0

LOCTITE SF 7063 known as Loctite 7063

Revision: 05.06.2019
printing date: 16.01.2020
Replaces version from: 30.04.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE SF 7063 known as Loctite 7063

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:
Solvent based cleaner

1.3. Details of the supplier of the safety data sheet

Henkel Ltd
Wood Lane End
HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 1442 278000
Fax-no.: +44 1442 278071

ua-productsafety.uk@henkel.com

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Flammable aerosols	Category 1
H222 Extremely flammable aerosol.	
H229 Pressurized container: May burst if heated.	
Skin irritation	Category 2
H315 Causes skin irritation.	
Specific target organ toxicity - single exposure	Category 3
H336 May cause drowsiness or dizziness.	
Target organ: Central nervous system	
Chronic hazards to the aquatic environment	Category 2
H411 Toxic to aquatic life with long lasting effects.	

2.2. Label elements

Label elements (CLP):

Hazard pictogram:**Contains**

Naphtha, hydrotreated light, <0,1% benzene

Signal word:

Danger

Hazard statement:

H222 Extremely flammable aerosol.
 H229 Pressurized container: May burst if heated.
 H315 Causes skin irritation.
 H336 May cause drowsiness or dizziness.
 H411 Toxic to aquatic life with long lasting effects.

Precautionary statement:

P251 Do not pierce or burn, even after use.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
 P211 Do not spray on an open flame or other ignition source.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P102 Keep out of reach of children.
 "****" ***For consumer use only: P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P501 Dispose of waste and residues in accordance with local authority requirements***

**Precautionary statement:
Prevention**

P261 Avoid breathing spray.
 P273 Avoid release to the environment.

**Precautionary statement:
Response**

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

2.3. Other hazards

The aerosol container is under pressure. Do not expose to high temperatures.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures**General chemical description:**

Solvent cleaner

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Naphtha, hydrotreated light, <0,1% benzene 64742-49-0	265-151-9	50- 100 %	Flam. Liq. 2 H225 Asp. Tox. 1 H304 Skin Irrit. 2 H315 STOT SE 3 H336 Aquatic Chronic 2 H411
Ethanol 64-17-5	200-578-6 01-2119457610-43	10- < 20 %	Eye Irrit. 2 H319 Flam. Liq. 2 H225
Methylal 109-87-5	203-714-2 01-2119664781-31	10- 20 %	Flam. Liq. 2 H225
Carbon dioxide 124-38-9	204-696-9	5- < 10 %	Press. Gas

For full text of the H - statements and other abbreviations see section 16 "Other information".
Substances without classification may have community workplace exposure limits available.

Declaration of ingredients according to Detergent Regulation 648/2004/EC

> 30 % aliphatic hydrocarbons

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation:**

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

SKIN: Redness, inflammation.

Vapors may cause drowsiness and dizziness.

Prolonged or repeated contact may cause eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media:**

Foam, extinguishing powder, carbon dioxide.

Extinguishing media which must not be used for safety reasons:

None known

5.2. Special hazards arising from the substance or mixture

Vapours may accumulate in low or confined areas, travel considerable distance to source of ignition, and flash back.
Oxides of carbon, oxides of nitrogen, irritating organic vapors.

5.3. Advice for firefighters

Wear self-contained breathing apparatus.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Remove sources of ignition.

Ensure adequate ventilation.

6.2. Environmental precautions

Do not let product enter drains.

6.3. Methods and material for containment and cleaning up

Wipe up using absorbent material.

Store in a partly filled, closed container until disposal.

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Keep away from sources of ignition - no smoking.

Vapours should be extracted to avoid inhalation.

Use only in well-ventilated areas.

Avoid skin and eye contact.

See advice in section 8

Hygiene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

Good industrial hygiene practices should be observed.

7.2. Conditions for safe storage, including any incompatibilities

Store in a cool, dry place.

Do not store near sources of heat or ignition, or reactive materials.

Refer to Technical Data Sheet

7.3. Specific end use(s)

Solvent based cleaner

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for
Great Britain

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Ethanol 64-17-5 [ETHANOL]	1.000	1.920	Time Weighted Average (TWA):		EH40 WEL
Dimethoxymethane 109-87-5 [DIMETHOXYMETHANE]	1.250	3.950	Short Term Exposure Limit (STEL):		EH40 WEL
Dimethoxymethane 109-87-5 [DIMETHOXYMETHANE]	1.000	3.160	Time Weighted Average (TWA):		EH40 WEL
Carbon dioxide 124-38-9					
Carbon dioxide 124-38-9 [CARBON DIOXIDE]	15.000	27.400	Short Term Exposure Limit (STEL):		EH40 WEL
Carbon dioxide 124-38-9 [CARBON DIOXIDE]	5.000	9.150	Time Weighted Average (TWA):		EH40 WEL
Carbon dioxide 124-38-9 [CARBON DIOXIDE]	5.000	9.000	Time Weighted Average (TWA):	Indicative	ECTLV

Occupational Exposure Limits

Valid for
Ireland

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Ethanol 64-17-5 [ETHANOL]	1.000		Short Term Exposure Limit (STEL):	15 minutes	IR_OEL
Dimethoxymethane 109-87-5 [METHYLAL]	1.000	3.100	Time Weighted Average (TWA):		IR_OEL
Carbon dioxide 124-38-9					
Carbon dioxide 124-38-9 [CARBON DIOXIDE]	5.000	9.000	Time Weighted Average (TWA):	Indicative OELV	IR_OEL
Carbon dioxide 124-38-9 [CARBON DIOXIDE]	5.000	9.000	Time Weighted Average (TWA):	Indicative	ECTLV
Carbon dioxide 124-38-9 [CARBON DIOXIDE]	15.000	27.000	Short Term Exposure Limit (STEL):	15 minutes Indicative OELV	IR_OEL

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
Ethanol 64-17-5	aqua (freshwater)		0,96 mg/l				
Ethanol 64-17-5	aqua (marine water)		0,79 mg/l				
Ethanol 64-17-5	aqua (intermittent releases)		2,75 mg/l				
Ethanol 64-17-5	sewage treatment plant (STP)		580 mg/l				
Ethanol 64-17-5	sediment (freshwater)				3,6 mg/kg		
Ethanol 64-17-5	sediment (marine water)				2,9 mg/kg		
Ethanol 64-17-5	Soil				0,63 mg/kg		
Ethanol 64-17-5	oral				380 mg/kg		
Dimethoxymethane 109-87-5	aqua (freshwater)		14,577 mg/l				
Dimethoxymethane 109-87-5	aqua (marine water)		1,4577 mg/l				
Dimethoxymethane 109-87-5	sediment (freshwater)				13,135 mg/kg		
Dimethoxymethane 109-87-5	sediment (marine water)				1,3135 mg/kg		
Dimethoxymethane 109-87-5	Soil				4,6538 mg/kg		
Dimethoxymethane 109-87-5	Sewage treatment plant		10000 mg/l				

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Ethanol 64-17-5	Workers	dermal	Long term exposure - systemic effects		343 mg/kg	
Ethanol 64-17-5	Workers	inhalation	Long term exposure - systemic effects		950 mg/m3	
Ethanol 64-17-5	General population	dermal	Long term exposure - systemic effects		206 mg/kg	
Ethanol 64-17-5	General population	inhalation	Long term exposure - systemic effects		114 mg/m3	
Ethanol 64-17-5	General population	oral	Long term exposure - systemic effects		87 mg/kg	

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.

Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	aerosol colourless
Odor	hydrocarbons
Odour threshold	No data available / Not applicable
pH	Not applicable
Melting point	No data available / Not applicable
Solidification temperature	No data available / Not applicable
Initial boiling point	-78 °C (-108.4 °F)
Flash point	-18 °C (0.4 °F)
Evaporation rate	No data available / Not applicable
Flammability	No data available / Not applicable
Explosive limits	
lower	0,8 % (V)
upper	15 % (V)
Vapour pressure (20 °C (68 °F))	440 hPa
Relative vapour density:	No data available / Not applicable
Density (20 °C (68 °F))	0,742 g/cm ³
Bulk density	No data available / Not applicable
Solubility	No data available / Not applicable
Solubility (qualitative) (Solvent: Water)	Not miscible
Solubility (qualitative) (Solvent: Acetone)	Miscible
Partition coefficient: n-octanol/water	No data available / Not applicable

Auto-ignition temperature	No data available / Not applicable
Decomposition temperature	No data available / Not applicable
Viscosity	No data available / Not applicable
Viscosity (kinematic)	No data available / Not applicable
Explosive properties	No data available / Not applicable
Oxidising properties	No data available / Not applicable

9.2. Other information

Ignition temperature 200 °C (392 °F)

SECTION 10: Stability and reactivity

10.1. Reactivity

Strong oxidizing agents.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

No decomposition if used according to specifications.

Heat, flames, sparks and other sources of ignition.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

None if used for intended purpose.

SECTION 11: Toxicological information

General toxicological information:

Prolonged or repeated contact may cause eye irritation.

11.1. Information on toxicological effects**Acute oral toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Naphtha, hydrotreated light, <0,1% benzene 64742-49-0	LD50	> 5.000 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
Ethanol 64-17-5	LD50	10.470 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Methylal 109-87-5	LD50	6.423 mg/kg	rat	not specified

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Naphtha, hydrotreated light, <0,1% benzene 64742-49-0	LD50	> 2.000 mg/kg	rabbit	equivalent or similar to OECD Guideline 402 (Acute Dermal Toxicity)
Ethanol 64-17-5	LD50	> 2.000 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
Methylal 109-87-5	LD50	> 5.000 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
Naphtha, hydrotreated light, <0,1% benzene 64742-49-0	LC50	> 5,61 mg/l	dust/mist	4 h	rat	equivalent or similar to OECD Guideline 403 (Acute Inhalation Toxicity)
Ethanol 64-17-5	LC50	124,7 mg/l	vapour	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)
Methylal 109-87-5	LC50	15.000 mg/l	vapour	4 h	rat	not specified

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Ethanol 64-17-5	not irritating		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Ethanol 64-17-5	irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Ethanol 64-17-5	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
Ethanol 64-17-5	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Ethanol 64-17-5	not sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Ethanol 64-17-5	negative	bacterial reverse mutation assay (e.g Ames test)			OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Ethanol 64-17-5	negative	in vitro mammalian chromosome aberration test	without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Ethanol 64-17-5	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
Ethanol 64-17-5		oral: unspecified		rat		not specified
Ethanol 64-17-5		dermal		mouse	female	not specified
Ethanol 64-17-5		inhalation		mouse	male	not specified

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
Ethanol 64-17-5	NOAEL P 13.800 mg/kg	Two generation study	oral: unspecified	mouse	OECD Guideline 416 (Two- Generation Reproduction Toxicity Study)

STOT-single exposure:

No data available.

STOT-repeated exposure::

No data available.

Aspiration hazard:

No data available.

SECTION 12: Ecological information

General ecological information:

Do not empty into drains / surface water / ground water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Naphtha, hydrotreated light, <0,1% benzene 64742-49-0	LL50	8,2 mg/l	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
Ethanol 64-17-5	LC50	14.200 mg/l	96 h	Pimephales promelas	EPA-660 (Methods for Acute Toxicity Tests with Fish, Macroinvertebrates and Amphibians)
Ethanol 64-17-5	NOEC	250 mg/l	120 h	Danio rerio	OECD Guideline 212 (Fish, Short-term Toxicity Test on Embryo and Sac-Fry Stages)
Methylal 109-87-5	LC50	6.990 mg/l	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)

Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Naphtha, hydrotreated light, <0,1% benzene 64742-49-0	EL50	4,5 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Ethanol 64-17-5	EC50	5.012 mg/l	48 h	Ceriodaphnia dubia	other guideline:
Methylal 109-87-5	EC50	> 500 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Naphtha, hydrotreated light, <0,1% benzene 64742-49-0	NOELR	2,6 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Ethanol 64-17-5	NOEC	9,6 mg/l	9 d	Daphnia magna	not specified

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Naphtha, hydrotreated light, <0,1% benzene 64742-49-0	EL50	3,1 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Naphtha, hydrotreated light, <0,1% benzene 64742-49-0	NOELR	0,5 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Ethanol 64-17-5	EC50	275 mg/l	72 h	Chlorella vulgaris	OECD Guideline 201 (Alga, Growth Inhibition Test)
Ethanol 64-17-5	EC10	11,5 mg/l	72 h	Chlorella vulgaris	OECD Guideline 201 (Alga, Growth Inhibition Test)
Methylal 109-87-5	EC10	> 500 mg/l	96 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Ethanol 64-17-5	IC50	> 1.000 mg/l	3 h	activated sludge	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Methylal 109-87-5	EC10	3.000 mg/l	17 h		DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm- Test)

12.2. Persistence and degradability

No data available.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Naphtha, hydrotreated light, <0,1% benzene 64742-49-0	readily biodegradable	aerobic	77,05 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Ethanol 64-17-5	readily biodegradable	aerobic	80 - 85 %	30 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Methylal 109-87-5			88 %	30 d	OECD 301 A - F

12.3. Bioaccumulative potential

No data available.

No substance data available.

12.4. Mobility in soil

The product evaporates readily.

Hazardous substances CAS-No.	LogPow	Temperature	Method
Naphtha, hydrotreated light, <0,1% benzene 64742-49-0	4 - 5,7		OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
Ethanol 64-17-5	-0,35	24 °C	not specified

12.5. Results of PBT and vPvB assessment

Hazardous substances CAS-No.	PBT / vPvB
Naphtha, hydrotreated light, <0,1% benzene 64742-49-0	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Ethanol 64-17-5	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Dispose of according to regulations.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

Waste code

14 06 03 Other solvents and solvent mixtures

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information

14.1. UN number

ADR	1950
RID	1950
ADN	1950
IMDG	1950
IATA	1950

14.2. UN proper shipping name

ADR	AEROSOLS
RID	AEROSOLS
ADN	AEROSOLS
IMDG	AEROSOLS (Solvent Naphtha (Petroleum), Light Aromatic)
IATA	Aerosols, flammable

14.3. Transport hazard class(es)

ADR	2.1
RID	2.1
ADN	2.1
IMDG	2.1
IATA	2.1

14.4. Packing group

ADR
RID
ADN
IMDG
IATA

14.5. Environmental hazards

ADR	Environmentally Hazardous
RID	Environmentally Hazardous
ADN	Environmentally Hazardous
IMDG	Marine pollutant
IATA	not applicable

14.6. Special precautions for user

ADR	not applicable Tunnelcode: (D)
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC content 95 %
(2010/75/EC)

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

- H225 Highly flammable liquid and vapor.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (ua-productsafety.de@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.