

# Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 22

LOCTITE SI 5980 known as Loctite SI 5980 40 ML SFDN

SDS No. : 317263 V007.0 Revision: 05.06.2020 printing date: 13.08.2020 Replaces version from: 03.11.2017

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

LOCTITE SI 5980 known as Loctite SI 5980 40 ML SFDN

- **1.2. Relevant identified uses of the substance or mixture and uses advised against** Intended use: Silicone sealant
- **1.3. Details of the supplier of the safety data sheet** Henkel Ltd Wood Lane End HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 1442 278000 Fax-no.: +44 1442 278071

ua-productsafety.uk@henkel.com

#### **1.4. Emergency telephone number**

24 Hours Emergency Tel: +44 (0)1442 278497

# **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

#### Classification (CLP):

The substance or mixture is not hazardous according to Regulation (EC) No 1272/2008 (CLP).

#### 2.2. Label elements

#### Label elements (CLP):

The substance or mixture is not hazardous according to Regulation (EC) No 1272/2008 (CLP).

Supplemental information	Contains: 3-aminopropyltriethoxysilane May produce an allergic reaction.
	Safety data sheet available on request.

#### 2.3. Other hazards

None if used properly.

This mixture contains components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB).

# **SECTION 3: Composition/information on ingredients**

## 3.2. Mixtures

## General chemical description:

Silicone sealant

## Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number	content	Classification
Hexamethyldisilizane	<b>REACH-Reg No.</b> 213-668-5	1- < 3 %	Flam. Liq. 2
999-97-3	01-2119438176-38		H225 Acute Tox. 4; Oral
			H302
			Acute Tox. 3; Dermal
			H311
			Acute Tox. 4; Inhalation
			H332
			Aquatic Chronic 3
			H412
Trimethoxyvinylsilane	220-449-8	1-< 3 %	Flam. Liq. 3
2768-02-7	01-2119513215-52		H226
			Acute Tox. 4; Inhalation
			H332
			STOT RE 2
	212.040.4	0.1 1.0/	H373
3-aminopropyltriethoxysilane	213-048-4	0,1-< 1 %	Skin Sens. 1
919-30-2	01-2119480479-24		H317 Shin Correct D
			Skin Corr. 1B H314
			Acute Tox. 4; Oral
			H302
octamethylcyclotetrasiloxane	209-136-7	0.1-< 1 %	Flam. Liq. 3
556-67-2	01-2119529238-36	0,1- < 1 /0	H226
550 07 2	01 211/32/230 30		Repr. 2
			H361f
			Aquatic Chronic 4
			H413
			=====
			EU. REACH Candidate List of Substances of
			Very High Concern for Authorization
			(SVHC)
Dodecamethylcyclohexasiloxane	208-762-8	0,1-<1%	Aquatic Chronic 4
540-97-6	01-2119517435-42		H413
			=====
			EU. REACH Candidate List of Substances of
			Very High Concern for Authorization
	200.764.0	0.1- < 1 %	(SVHC)
Decamethylcyclopentasiloxane 541-02-6	208-764-9	0,1-<1%	Aquatic Chronic 4
541-02-0	01-2119511367-43		H413
			===== EU. REACH Candidate List of Substances of
			Very High Concern for Authorization
			(SVHC)
			(SVIIC)

For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

# **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

Inhalation: Move to fresh air. If symptoms persist, seek medical advice.

Skin contact: Rinse with running water and soap. Obtain medical attention if irritation persists.

#### Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

#### 4.2. Most important symptoms and effects, both acute and delayed

Prolonged or repeated contact may cause skin irritation.

Prolonged or repeated contact may cause eye irritation.

#### 4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

#### **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

**Suitable extinguishing media:** Carbon dioxide, foam, powder

**Extinguishing media which must not be used for safety reasons:** High pressure waterjet

#### 5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx) can be released.

#### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

#### Additional information:

In case of fire, keep containers cool with water spray.

#### **SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures** Avoid contact with skin and eyes. Ensure adequate ventilation.

Wear protective equipment.

**6.2.** Environmental precautions

Do not empty into drains / surface water / ground water.

#### 6.3. Methods and material for containment and cleaning up

For small spills wipe up with paper towel and place in container for disposal. For large spills absorb onto inert absorbent material and place in sealed container for disposal. Dispose of contaminated material as waste according to Section 13.

#### 6.4. Reference to other sections

See advice in section 8

## **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Use only in well-ventilated areas. Avoid skin and eye contact. Prolonged or repeated skin contact should be avoided to minimise any risk of sensitisation. See advice in section 8

Hygiene measures:

Good industrial hygiene practices should be observed. Wash hands before work breaks and after finishing work. Do not eat, drink or smoke while working. **7.2. Conditions for safe storage, including any incompatibilities** Refer to Technical Data Sheet

**7.3. Specific end use(s)** Silicone sealant

# **SECTION 8: Exposure controls/personal protection**

# 8.1. Control parameters

# **Occupational Exposure Limits**

# Valid for

Great Britain

Ingredient [Regulated substance]	ррт	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
Limestone 1317-65-3 [CALCIUM CARBONATE, INHALABLE DUST]		10	Time Weighted Average (TWA):		EH40 WEL
Limestone 1317-65-3 [CALCIUM CARBONATE, RESPIRABLE DUST]		4	Time Weighted Average (TWA):		EH40 WEL
Limestone 1317-65-3 [LIMESTONE, RESPIRABLE MARBLE, RESPIRABLE]		4	Time Weighted Average (TWA):		EH40 WEL
Limestone 1317-65-3 [LIMESTONE, TOTAL INHALABLE MARBLE, TOTAL INHALABLE]		10	Time Weighted Average (TWA):		EH40 WEL
Calcium carbonate 471-34-1 [CALCIUM CARBONATE, INHALABLE DUST]		10	Time Weighted Average (TWA):		EH40 WEL
Calcium carbonate 471-34-1 [CALCIUM CARBONATE, RESPIRABLE DUST]		4	Time Weighted Average (TWA):		EH40 WEL
Calcium carbonate 471-34-1 [LIMESTONE, RESPIRABLE MARBLE, RESPIRABLE]		4	Time Weighted Average (TWA):		EH40 WEL
Calcium carbonate 471-34-1 [LIMESTONE, TOTAL INHALABLE MARBLE, TOTAL INHALABLE]		10	Time Weighted Average (TWA):		EH40 WEL

# **Occupational Exposure Limits**

Valid for

Ireland

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
Limestone 1317-65-3 [CALCIUM CARBONATE, RESPIRABLE DUST]		4	Time Weighted Average (TWA):		IR_OEL
Limestone 1317-65-3 [CALCIUM CARBONATE, TOTAL INHALABLE DUST]		10	Time Weighted Average (TWA):		IR_OEL
Calcium carbonate 471-34-1 [CALCIUM CARBONATE, RESPIRABLE DUST]		4	Time Weighted Average (TWA):		IR_OEL
Calcium carbonate 471-34-1 [CALCIUM CARBONATE, TOTAL INHALABLE DUST]		10	Time Weighted Average (TWA):		IR_OEL

# Predicted No-Effect Concentration (PNEC):

Name on list	Environmental		Value			Remarks	
	Compartment	period				a	
1,1,1,3,3,3-Hexamethyldisilazane	aqua		<b>mg/l</b> 0,25 mg/l	ppm	mg/kg	others	
999-97-3	(freshwater)		0,25 mg/1				
1,1,1,3,3,3-Hexamethyldisilazane 999-97-3	aqua (marine water)		0,025 mg/l				
1,1,1,3,3,3-Hexamethyldisilazane 999-97-3	sediment (freshwater)				0,45 mg/kg		
1,1,1,3,3,3-Hexamethyldisilazane 999-97-3	sediment (marine water)				0,045		
1,1,1,3,3,3-Hexamethyldisilazane	Soil				mg/kg 0,22 mg/kg		
1,1,1,3,3,3-Hexamethyldisilazane	sewage		67 mg/l				
999-97-3	treatment plant (STP)						
Trimethoxyvinylsilane 2768-02-7	aqua (freshwater)		0,4 mg/l				
Trimethoxyvinylsilane 2768-02-7	aqua (marine water)		0,04 mg/l				
Trimethoxyvinylsilane	aqua		2,4 mg/l				
2768-02-7	(intermittent releases)						
Trimethoxyvinylsilane 2768-02-7	sewage treatment plant		6,6 mg/l				
2708-02-7	(STP)						
Trimethoxyvinylsilane 2768-02-7	sediment (freshwater)				1,5 mg/kg		
Trimethoxyvinylsilane 2768-02-7	sediment (marine water)				0,15 mg/kg		
Trimethoxyvinylsilane 2768-02-7	Soil				0,06 mg/kg		
3-Aminopropyltriethoxysilane 919-30-2	aqua (freshwater)		0,33 mg/l				
3-Aminopropyltriethoxysilane 919-30-2	aqua (marine water)		0,033 mg/l				
3-Aminopropyltriethoxysilane 919-30-2	aqua (intermittent releases)		3,3 mg/l				
3-Aminopropyltriethoxysilane 919-30-2	Soil				0,05 mg/kg		
3-Aminopropyltriethoxysilane	sewage		13 mg/l				
919-30-2	treatment plant (STP)						
3-Aminopropyltriethoxysilane 919-30-2	sediment (freshwater)				1,2 mg/kg		
3-Aminopropyltriethoxysilane 919-30-2	sediment (marine water)				0,12 mg/kg		
Octamethylcyclotetrasiloxane	aqua		0,0015				
556-67-2 Octamethylcyclotetrasiloxane	(freshwater) aqua (marine		mg/l 0.00015				
556-67-2	water)		mg/l				
Octamethylcyclotetrasiloxane 556-67-2	sewage treatment plant		10 mg/l				
Octamethylcyclotetrasiloxane	(STP) sediment				3 mg/kg		
556-67-2	(freshwater)				0.0		
Octamethylcyclotetrasiloxane 556-67-2	sediment (marine water)				0,3 mg/kg		
Octamethylcyclotetrasiloxane 556-67-2	oral				41 mg/kg		
Octamethylcyclotetrasiloxane 556-67-2	Soil				0,54 mg/kg		
Dodecamethylcyclohexasiloxane 540-97-6	sewage treatment plant (STP)		1 mg/l				
Dodecamethylcyclohexasiloxane 540-97-6	sediment (freshwater)				13 mg/kg		
Dodecamethylcyclohexasiloxane 540-97-6	Soil				3,77 mg/kg		
Dodecamethylcyclohexasiloxane	oral				66,7 mg/kg		
540-97-6							

Dodecamethylcyclohexasiloxane 540-97-6	sediment (marine water)		1,3 mg/kg	
Decamethylcyclopentasiloxane 541-02-6	aqua (freshwater)	0,0012 mg/l		
Decamethylcyclopentasiloxane 541-02-6	aqua (marine water)	0,00012 mg/l		
Decamethylcyclopentasiloxane 541-02-6	sewage treatment plant (STP)	10 mg/l		
Decamethylcyclopentasiloxane 541-02-6	sediment (freshwater)		11 mg/kg	
Decamethylcyclopentasiloxane 541-02-6	Soil		2,54 mg/kg	
Decamethylcyclopentasiloxane 541-02-6	oral		16 mg/kg	
Decamethylcyclopentasiloxane 541-02-6	sediment (marine water)		1,1 mg/kg	

# Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
1,1,1,3,3,3-Hexamethyldisilazane 999-97-3	Workers	inhalation	Long term exposure - systemic effects		53 mg/m3	
1,1,1,3,3,3-Hexamethyldisilazane 999-97-3	Workers	inhalation	Acute/short term exposure - systemic effects	exposure -		
1,1,1,3,3,3-Hexamethyldisilazane 999-97-3	Workers	inhalation	Long term exposure - local effects		133 mg/m3	
1,1,1,3,3,3-Hexamethyldisilazane 999-97-3	Workers	inhalation	Acute/short term exposure - local effects		133 mg/m3	
1,1,1,3,3,3-Hexamethyldisilazane 999-97-3	Workers	dermal	Long term exposure - systemic effects		7,5 mg/kg	
1,1,1,3,3,3-Hexamethyldisilazane 999-97-3	Workers	dermal	Acute/short term exposure - systemic effects		7,5 mg/kg	
1,1,1,3,3,3-Hexamethyldisilazane 999-97-3	General population	inhalation	Long term exposure - systemic effects		3,7 mg/m3	
1,1,1,3,3,3-Hexamethyldisilazane 999-97-3	General population	inhalation	Acute/short term exposure - systemic effects		3,7 mg/m3	
1,1,1,3,3,3-Hexamethyldisilazane 999-97-3	General population	inhalation	Long term exposure - local effects		1,7 mg/m3	
1,1,1,3,3,3-Hexamethyldisilazane 999-97-3	General population	inhalation	Acute/short term exposure - local effects		1,7 mg/m3	
1,1,1,3,3,3-Hexamethyldisilazane 999-97-3	General population	oral	Long term exposure - systemic effects		1,1 mg/kg	
1,1,1,3,3,3-Hexamethyldisilazane 999-97-3	General population	oral	Acute/short term exposure - systemic effects		1,1 mg/kg	
Trimethoxyvinylsilane 2768-02-7	Workers	dermal	Long term exposure - systemic effects		3,9 mg/kg	
Trimethoxyvinylsilane 2768-02-7	Workers	inhalation	Long term exposure - systemic effects		27,6 mg/m3	
Trimethoxyvinylsilane 2768-02-7	General population	dermal	Long term exposure - systemic effects		7,8 mg/kg	
Trimethoxyvinylsilane 2768-02-7	General population	inhalation	Long term exposure - systemic effects		6,7 mg/m3	
Trimethoxyvinylsilane 2768-02-7	General population	oral	Long term exposure - systemic effects		0,3 mg/kg	
3-Aminopropyltriethoxysilane 919-30-2	Workers	dermal	Acute/short term exposure - systemic effects		8,3 mg/kg	
3-Aminopropyltriethoxysilane 919-30-2	Workers	Inhalation	Acute/short term exposure - systemic effects		59 mg/m3	
3-Aminopropyltriethoxysilane 919-30-2	Workers	dermal	Long term exposure - systemic effects		8,3 mg/kg	
3-Aminopropyltriethoxysilane 919-30-2	Workers	Inhalation	Long term exposure - systemic effects		59 mg/m3	
3-Aminopropyltriethoxysilane 919-30-2	General population	oral	Acute/short term exposure - systemic effects		5 mg/kg	
3-Aminopropyltriethoxysilane 919-30-2	General population	dermal	Acute/short term exposure - systemic effects		5 mg/kg	
3-Aminopropyltriethoxysilane 919-30-2	General population	Inhalation	Acute/short term exposure -		17,4 mg/m3	

	1	I	systemic effects	1	
3-Aminopropyltriethoxysilane	General	oral	Long term	5 mg/kg	
919-30-2	population	orui	exposure - systemic effects	5 116/16	
3-Aminopropyltriethoxysilane	General	dermal	Long term	5 mg/kg	
919-30-2	population		exposure - systemic effects		
3-Aminopropyltriethoxysilane	General	Inhalation	Long term	17 mg/m3	
919-30-2	population		exposure - systemic effects		
Octamethylcyclotetrasiloxane	Workers	inhalation	Long term	73 mg/m3	
556-67-2			exposure -	6	
Octamethylcyclotetrasiloxane	Workers	inhalation	systemic effects Long term	73 mg/m3	
556-67-2	WORKETS	minalation	exposure - local effects	75 mg/m5	
Octamethylcyclotetrasiloxane	General	inhalation	Long term	13 mg/m3	
556-67-2	population		exposure - systemic effects		
Octamethylcyclotetrasiloxane	General	inhalation	Long term	13 mg/m3	
556-67-2	population		exposure - local effects		
Octamethylcyclotetrasiloxane	General	oral	Long term	3,7 mg/kg	
556-67-2	population		exposure - systemic effects		
Octamethylcyclotetrasiloxane	Workers	inhalation	Acute/short term	73 mg/m3	
556-67-2			exposure - local effects		
Octamethylcyclotetrasiloxane	Workers	inhalation	Acute/short term	73 mg/m3	
556-67-2			exposure - systemic effects		
Octamethylcyclotetrasiloxane	General	inhalation	Acute/short term	13 mg/m3	
556-67-2	population		exposure - local	C .	
			effects	10 ( 0	
Octamethylcyclotetrasiloxane 556-67-2	General population	inhalation	Acute/short term exposure -	13 mg/m3	
550 07 2	population		systemic effects		
Octamethylcyclotetrasiloxane	General	oral	Acute/short term	3,7 mg/kg	
556-67-2	population		exposure - systemic effects		
Dodecamethylcyclohexasiloxane	Workers	inhalation	Long term	11 mg/m3	
540-97-6			exposure - systemic effects		
Dodecamethylcyclohexasiloxane	Workers	inhalation	Long term	1,22 mg/m3	
540-97-6			exposure - local		
Dodecamethylcyclohexasiloxane	Workers	inhalation	effects Acute/short term	6,1 mg/m3	
540-97-6	WORKERS	minaration	exposure - local effects	0,1 mg/m3	
Dodecamethylcyclohexasiloxane	General	inhalation	Long term	2,7 mg/m3	
540-97-6	population		exposure -	,	
Dodecamethylcyclohexasiloxane	General	inhalation	systemic effects Long term	0,3 mg/m3	
540-97-6	population	minanation	exposure - local	0,3 mg/m3	
Deducer that 11 '		11 . 1 . 1	effects	15. / 2	
Dodecamethylcyclohexasiloxane 540-97-6	General population	inhalation	Acute/short term exposure - local effects	1,5 mg/m3	
Dodecamethylcyclohexasiloxane	General	oral	Long term	1,7 mg/kg	
540-97-6	population		exposure -	.,,	
		1	systemic effects	1.7. 4	
Dodecamethylcyclohexasiloxane 540-97-6	General population	oral	Acute/short term exposure -	1,7 mg/kg	
	population		systemic effects		
Decamethylcyclopentasiloxane	Workers	inhalation	Acute/short term	97,3 mg/m3	
541-02-6			exposure - systemic effects		
Decamethylcyclopentasiloxane	Workers	inhalation	Acute/short term	24,2 mg/m3	
541-02-6			exposure - local effects		
Decamethylcyclopentasiloxane	Workers	inhalation	Long term	97,3 mg/m3	
541-02-6			exposure -		
			systemic effects Long term	24.2	
Decemethylayelementeeil					
Decamethylcyclopentasiloxane 541-02-6	Workers	inhalation	exposure - local	24,2 mg/m3	

Decamethylcyclopentasiloxane 541-02-6	General population	inhalation	Acute/short term exposure - systemic effects	17,3 mg/m3	
Decamethylcyclopentasiloxane 541-02-6	General population	inhalation	Acute/short term exposure - local effects	4,3 mg/m3	
Decamethylcyclopentasiloxane 541-02-6	General population	oral	Long term exposure - systemic effects	5 mg/kg	
Decamethylcyclopentasiloxane 541-02-6	General population	inhalation	Long term exposure - systemic effects	17,3 mg/m3	
Decamethylcyclopentasiloxane 541-02-6	General population	inhalation	Long term exposure - local effects	4,3 mg/m3	
Decamethylcyclopentasiloxane 541-02-6	General population	oral	Acute/short term exposure - systemic effects	5 mg/kg	

#### **Biological Exposure Indices:**

None

#### **8.2. Exposure controls:**

Engineering controls: Ensure good ventilation/extraction.

Respiratory protection: Ensure adequate ventilation. An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area Filter type: A (EN 14387)

Hand protection: Chemical-resistant protective gloves (EN 374). Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374): nitrile rubber (NBR; >= 0.4 mm thickness) Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374): nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection: Wear protective glasses. Protective eye equipment should conform to EN166.

Skin protection: Wear suitable protective clothing. Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

# **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties Appearance paste

11	paste
	paste black
Odor	alcohol-like
Odour threshold	No data available / Not applicable
рН	Not available.
Melting point	No data available / Not applicable
Solidification temperature	No data available / Not applicable
Initial boiling point	No data available / Not applicable
Flash point	> 100,00 °C (> 212 °F)
Evaporation rate	No data available / Not applicable
Flammability	No data available / Not applicable
Explosive limits	No data available / Not applicable
Vapour pressure	No data available / Not applicable
Relative vapour density:	No data available / Not applicable
Density	1,3200 g/cm3
0	
Bulk density	No data available / Not applicable
Solubility	No data available / Not applicable
Solubility (qualitative)	No data available / Not applicable
Partition coefficient: n-octanol/water	No data available / Not applicable
Auto-ignition temperature	No data available / Not applicable
Decomposition temperature	No data available / Not applicable
Viscosity	No data available / Not applicable
Viscosity (kinematic)	No data available / Not applicable
Explosive properties	No data available / Not applicable
Oxidising properties	No data available / Not applicable

#### 9.2. Other information

No data available / Not applicable

# **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

None if used for intended purpose.

#### 10.2. Chemical stability

Stable under recommended storage conditions.

# 10.3. Possibility of hazardous reactions

See section reactivity

### **10.4.** Conditions to avoid

Stable under normal conditions of storage and use.

# **10.5. Incompatible materials** None if used properly.

**10.6. Hazardous decomposition products** carbon oxides.

# **SECTION 11: Toxicological information**

# **11.1. Information on toxicological effects**

# Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Species	Method
CAS-No.	type			
Hexamethyldisilizane 999-97-3	LD50	851 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Trimethoxyvinylsilane 2768-02-7	LD50	7.120 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
3- aminopropyltriethoxysilan e 919-30-2	LD50	1.457 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
octamethylcyclotetrasilox ane 556-67-2	LD50	> 4.800 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
Dodecamethylcyclohexasi loxane 540-97-6	LD50	> 2.000 mg/kg	rat	OECD Guideline 423 (Acute Oral toxicity)
Decamethylcyclopentasilo xane 541-02-6	LD50	> 5.000 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)

## Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Hexamethyldisilizane 999-97-3	LD50	547 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Trimethoxyvinylsilane 2768-02-7	LD50	3.200 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
3- aminopropyltriethoxysilan e 919-30-2	LD50	4.076 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
octamethylcyclotetrasilox ane 556-67-2	LD50	> 2.375 mg/kg	rat	equivalent or similar to OECD Guideline 402 (Acute Dermal Toxicity)
Dodecamethylcyclohexasi loxane 540-97-6	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Decamethylcyclopentasilo xane 541-02-6	LD50	> 2.000 mg/kg	rabbit	equivalent or similar to OECD Guideline 402 (Acute Dermal Toxicity)

## Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
Hexamethyldisilizane 999-97-3	Acute toxicity estimate (ATE)	10,1 mg/l	vapour			Expert judgement
Trimethoxyvinylsilane 2768-02-7	LC50	16,8 mg/l	vapour	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)
3- aminopropyltriethoxysilan e 919-30-2	LC50	> 7,35 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)
octamethylcyclotetrasilox ane 556-67-2	LC50	36 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)
Decamethylcyclopentasilo xane 541-02-6	LC50	8,67 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)

## Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Trimethoxyvinylsilane 2768-02-7	not irritating		rabbit	other guideline:
3- aminopropyltriethoxysilan e 919-30-2	corrosive	1 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
octamethylcyclotetrasilox ane 556-67-2	not irritating		rabbit	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Dodecamethylcyclohexasi loxane 540-97-6	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Decamethylcyclopentasilo xane 541-02-6	not irritating	24 h	rabbit	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

## Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Trimethoxyvinylsilane 2768-02-7	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
3- aminopropyltriethoxysilan e 919-30-2	highly irritating		rabbit	equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion)
octamethylcyclotetrasilox ane 556-67-2	not irritating		rabbit	equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Dodecamethylcyclohexasi loxane 540-97-6	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Decamethylcyclopentasilo xane 541-02-6	not irritating	24 h	rabbit	equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion)

# Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances	Result	Test type	Species	Method
CAS-No.			_	
Trimethoxyvinylsilane	not sensitising	Guinea pig maximisation	guinea pig	OECD Guideline 406 (Skin Sensitisation)
2768-02-7		test		
3-	sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
aminopropyltriethoxysilan				
e				
919-30-2				
octamethylcyclotetrasilox	not sensitising	Guinea pig maximisation	guinea pig	OECD Guideline 406 (Skin Sensitisation)
ane		test		
556-67-2				
Dodecamethylcyclohexasi	not sensitising	Guinea pig maximisation	guinea pig	OECD Guideline 406 (Skin Sensitisation)
loxane		test		
540-97-6				
Decamethylcyclopentasilo	not sensitising	Mouse local lymphnode	mouse	equivalent or similar to OECD Guideline
xane		assay (LLNA)		429 (Skin Sensitisation: Local Lymph
541-02-6				Node Assay)

# Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances	Result	Type of study /	Metabolic	Species	Method
CAS-No.		Route of	activation /		
		administration	Exposure time		
Hexamethyldisilizane	negative	bacterial reverse	with and without		OECD Guideline 471
999-97-3		mutation assay (e.g			(Bacterial Reverse Mutation
Havemathyldisilizana	nogotivo	Ames test) mammalian cell	with and without		Assay) OECD Guideline 476 (In vitro
Hexamethyldisilizane 999-97-3	negative	gene mutation assay	with and without		Mammalian Cell Gene
333-31-3		gene mutation assay			Mutation Test)
Trimethoxyvinylsilane	negative	bacterial reverse	with and without		OECD Guideline 471
2768-02-7	negative	mutation assay (e.g	with and without		(Bacterial Reverse Mutation
		Ames test)			Assay)
Trimethoxyvinylsilane	positive	in vitro mammalian	with and without		OECD Guideline 473 (In vitro
2768-02-7	•	chromosome			Mammalian Chromosome
		aberration test			Aberration Test)
Trimethoxyvinylsilane	negative	mammalian cell	with and without		OECD Guideline 476 (In vitro
2768-02-7		gene mutation assay			Mammalian Cell Gene
-					Mutation Test)
3-	negative	bacterial reverse	with and without		OECD Guideline 471
aminopropyltriethoxysilan		mutation assay (e.g			(Bacterial Reverse Mutation
e 919-30-2		Ames test)			Assay)
3-	negative	in vitro mammalian	with and without		OECD Guideline 473 (In vitro
3- aminopropyltriethoxysilan	negative	chromosome	with and without		Mammalian Chromosome
e		aberration test			Aberration Test)
919-30-2		aborration toot			Leonution rest/
3-	negative	mammalian cell	with and without	1	OECD Guideline 476 (In vitro
aminopropyltriethoxysilan		gene mutation assay			Mammalian Cell Gene
e		· ·			Mutation Test)
919-30-2					
octamethylcyclotetrasilox	negative	bacterial gene	with and without		OECD Guideline 471
ane		mutation assay			(Bacterial Reverse Mutation
556-67-2					Assay)
octamethylcyclotetrasilox	negative	in vitro mammalian	with and without		equivalent or similar to OECD
ane		chromosome			Guideline 473 (In vitro
556-67-2		aberration test			Mammalian Chromosome
			with and without		Aberration Test)
octamethylcyclotetrasilox ane	negative	mammalian cell gene mutation assay	with and without		equivalent or similar to OECD Guideline 476 (In vitro
556-67-2		gene mutation assay			Mammalian Cell Gene
550-07-2					Mutation Test)
Dodecamethylcyclohexasi	negative	bacterial reverse	with and without		OECD Guideline 471
loxane		mutation assay (e.g			(Bacterial Reverse Mutation
540-97-6		Ames test)			Assay)
Dodecamethylcyclohexasi	negative	mammalian cell	with and without		OECD Guideline 476 (In vitro
loxane		gene mutation assay			Mammalian Cell Gene
540-97-6					Mutation Test)
Decamethylcyclopentasilo	negative	bacterial reverse	with and without		OECD Guideline 471
xane		mutation assay (e.g			(Bacterial Reverse Mutation
541-02-6		Ames test)		-	Assay)
Decamethylcyclopentasilo xane	negative	in vitro mammalian chromosome	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome
541-02-6		aberration test			Aberration Test)
Decamethylcyclopentasilo	negative	mammalian cell	with and without		OECD Guideline 476 (In vitro
xane	negutive	gene mutation assay	with and without		Mammalian Cell Gene
541-02-6		Serie metation assay			Mutation Test)
Trimethoxyvinylsilane	negative	intraperitoneal		mouse	other guideline:
2768-02-7		T. T			0
3-	negative	intraperitoneal		mouse	OECD Guideline 474
aminopropyltriethoxysilan					(Mammalian Erythrocyte
e					Micronucleus Test)
919-30-2	L				
octamethylcyclotetrasilox	negative	inhalation		rat	equivalent or similar to OECD
ane					Guideline 475 (Mammalian
556-67-2					Bone Marrow Chromosome
	. <u> </u>				Aberration Test)
octamethylcyclotetrasilox	negative	oral: gavage		rat	equivalent or similar to OECD
ane					Guideline 478 (Genetic
556-67-2					Toxicology: Rodent Dominant
Ded		1		 	Lethal Test)
Dodecamethylcyclohexasi	negative	intraperitoneal	1	mouse	OECD Guideline 474

loxane 540-97-6				(Mammalian Erythrocyte Micronucleus Test)
Decamethylcyclopentasilo xane 541-02-6	negative	inhalation	rat	OECD Guideline 486 (Unscheduled DNA Synthesis (UDS) Test with Mammalian Liver Cells in vivo)
Decamethylcyclopentasilo xane 541-02-6	negative	inhalation: vapour	rat	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

# Carcinogenicity

No data available.

# **Reproductive toxicity:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
Trimethoxyvinylsilane 2768-02-7	NOAEL P 250 mg/kg	one- generation study	oral: gavage	rat	OECD Combined Repeated Dose and Reproductive / Developmental Toxicity Screening Test (Precursor Protocol of GL 422)
Trimethoxyvinylsilane 2768-02-7	NOAEL P 1.000 mg/kg	one- generation study	oral: gavage	rat	OECD Combined Repeated Dose and Reproductive / Developmental Toxicity Screening Test (Precursor Protocol of GL 422)
Trimethoxyvinylsilane 2768-02-7	NOAEL F1 1.000 mg/kg	one- generation study	oral: gavage	rat	OECD Combined Repeated Dose and Reproductive / Developmental Toxicity Screening Test (Precursor Protocol of GL 422)
octamethylcyclotetrasilox ane 556-67-2	NOAEL P 300 ppm NOAEL F1 300 ppm	two- generation study	inhalation	rat	equivalent or similar to OECD Guideline 416 (Two- Generation Reproduction Toxicity Study)
Dodecamethylcyclohexasi loxane 540-97-6	NOAEL P 1.000 mg/kg NOAEL F1 1.000 mg/kg	screening	oral: gavage	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Decamethylcyclopentasilo xane 541-02-6	NOAEL P >= 160 ppm NOAEL F1 >= 160 ppm NOAEL F2 >= 160 ppm	two- generation study	inhalation: vapour	rat	EPA OPPTS 870.3800 (Reproduction and Fertility Effects)

## STOT-single exposure:

No data available.

# STOT-repeated exposure::

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
Trimethoxyvinylsilane 2768-02-7	NOAEL < 62,5 mg/kg	oral: gavage	42d daily	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Trimethoxyvinylsilane 2768-02-7	NOAEL 0,605 mg/l	inhalation: vapour	5 days/week for 14 weeks 6 hours/day	rat	not specified
3- aminopropyltriethoxysilan e 919-30-2	NOAEL 200 mg/kg	oral: gavage	90 d daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
octamethylcyclotetrasilox ane 556-67-2	LOAEL 35 ppm	inhalation	6 h nose only inhalation 5 days/week for 13 weeks	rat	OECD Guideline 412 (Repeated Dose Inhalation Toxicity: 28/14-Day)
octamethylcyclotetrasilox ane 556-67-2	NOAEL 960 mg/kg	dermal	3 w 5 d/w	rabbit	equivalent or similar to OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
Dodecamethylcyclohexasi loxane 540-97-6	NOAEL 1.000 mg/kg	oral: gavage	29 d daily, 7 d/w	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Decamethylcyclopentasilo xane 541-02-6	NOAEL >= 1.000 mg/kg	oral: gavage	13 w daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

## Aspiration hazard:

No data available.

# **SECTION 12: Ecological information**

# General ecological information:

Do not empty into drains / surface water / ground water.

#### 12.1. Toxicity

## Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Hexamethyldisilizane	LC50	88 mg/l	96 h	Brachydanio rerio (new name:	OECD Guideline 203 (Fish,
999-97-3				Danio rerio)	Acute Toxicity Test)
Trimethoxyvinylsilane	LC50	191 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish,
2768-02-7					Acute Toxicity Test)
3-aminopropyltriethoxysilane	LC50	> 934 mg/l	96 h	Brachydanio rerio (new name:	OECD Guideline 203 (Fish,
919-30-2				Danio rerio)	Acute Toxicity Test)
octamethylcyclotetrasiloxane	NOEC	0,0044 mg/l	93 d	Salmo gairdneri (new name:	other guideline:
556-67-2				Oncorhynchus mykiss)	
octamethylcyclotetrasiloxane	LC50		96 h	Oncorhynchus mykiss	EPA OTS 797.1400 (Fish
556-67-2					Acute Toxicity Test)
Decamethylcyclopentasiloxan	LC50		96 h	Leuciscus idus	OECD Guideline 203 (Fish,
e					Acute Toxicity Test)
541-02-6					
Decamethylcyclopentasiloxan	NOEC		90 d	Oncorhynchus mykiss	OECD Guideline 210 (fish
e					early lite stage toxicity test)
541-02-6					

# Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type		-	-	
Hexamethyldisilizane	EC50	80 mg/l	48 h	Daphnia magna	OECD Guideline 202
999-97-3					(Daphnia sp. Acute
					Immobilisation Test)
Trimethoxyvinylsilane	EC50	168,7 mg/l	48 h	Daphnia magna	EU Method C.2 (Acute
2768-02-7					Toxicity for Daphnia)
3-aminopropyltriethoxysilane	EC50	331 mg/l	48 h	Daphnia magna	OECD Guideline 202
919-30-2					(Daphnia sp. Acute
					Immobilisation Test)
octamethylcyclotetrasiloxane	EC50		48 h	Daphnia magna	EPA OTS 797.1300
556-67-2					(Aquatic Invertebrate Acute
					Toxicity Test, Freshwater
					Daphnids)
Decamethylcyclopentasiloxan	EC50		48 h	Daphnia magna	OECD Guideline 202
e					(Daphnia sp. Acute
541-02-6					Immobilisation Test)

#### Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Trimethoxyvinylsilane 2768-02-7	NOEC	28,1 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
octamethylcyclotetrasiloxane 556-67-2	NOEC	7.9 μg/l	21 d	Daphnia magna	EPA OTS 797.1330 (Daphnid Chronic Toxicity Test)
Dodecamethylcyclohexasiloxa ne 540-97-6	NOEC			Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Decamethylcyclopentasiloxan e 541-02-6	NOEC		21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type		-	•	
Hexamethyldisilizane 999-97-3	NOEC	2,7 mg/l	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Hexamethyldisilizane 999-97-3	EC50	19 mg/l	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Trimethoxyvinylsilane 2768-02-7	EC50	> 957 mg/l	72 h	Desmodesmus subspicatus	EU Method C.3 (Algal Inhibition test)
Trimethoxyvinylsilane 2768-02-7	NOEC	957 mg/l	72 h	Desmodesmus subspicatus	EU Method C.3 (Algal Inhibition test)
3-aminopropyltriethoxysilane 919-30-2	EC50	603 mg/l	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
3-aminopropyltriethoxysilane 919-30-2	NOEC	1,3 mg/l	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
octamethylcyclotetrasiloxane 556-67-2	EC50		96 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	EPA OTS 797.1050 (Algal Toxicity, Tiers I and II)
octamethylcyclotetrasiloxane 556-67-2	NOEC	< 0,022 mg/l	96 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	EPA OTS 797.1050 (Algal Toxicity, Tiers I and II)
Dodecamethylcyclohexasiloxa ne 540-97-6	NOEC			Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Dodecamethylcyclohexasiloxa ne 540-97-6	EC50			Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Decamethylcyclopentasiloxan e 541-02-6	NOEC		96 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Decamethylcyclopentasiloxan e 541-02-6	EC50		96 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

## Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Trimethoxyvinylsilane 2768-02-7	EC50	> 100 mg/l	3 h	predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
3-aminopropyltriethoxysilane 919-30-2	EC10	13 mg/l	5 h	not specified	other guideline:
octamethylcyclotetrasiloxane 556-67-2	EC50		3 h		ISO 8192 (Test for Inhibition of Oxygen Consumption by Activated Sludge)
Decamethylcyclopentasiloxan e 541-02-6	EC0	> 10.000 mg/l	30 min	Pseudomonas putida	DIN 38412, part 27 (Bacterial oxygen consumption test)

# 12.2. Persistence and degradability

The product is not biodegradable.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Hexamethyldisilizane 999-97-3	not readily biodegradable.	no data	15,3 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Trimethoxyvinylsilane 2768-02-7	not readily biodegradable.	aerobic	51 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
3-aminopropyltriethoxysilane 919-30-2	not readily biodegradable.	aerobic	67 %	28 d	OECD Guideline 301 A (new version) (Ready Biodegradability: DOC Die Away Test)
octamethylcyclotetrasiloxane 556-67-2	not readily biodegradable.	aerobic	3,7 %	29 d	OECD Guideline 310 (Ready BiodegradabilityCO2 in Sealed Vessels (Headspace Test)
Dodecamethylcyclohexasiloxa ne 540-97-6	not readily biodegradable.	aerobic	4,47 %	28 d	OECD Guideline 310 (Ready BiodegradabilityCO2 in Sealed Vessels (Headspace Test)
Decamethylcyclopentasiloxan e 541-02-6	not readily biodegradable.	aerobic	0,14 %	28 d	OECD Guideline 310 (Ready BiodegradabilityCO2 in Sealed Vessels (Headspace Test)

# 12.3. Bioaccumulative potential

Hazardous substances CAS-No.	Bioconcentratio n factor (BCF)	Exposure time	Temperature	Species	Method
octamethylcyclotetrasiloxane 556-67-2	12.400	28 d		Pimephales promelas	EPA OTS 797.1520 (Fish Bioconcentration Test-Rainbow Trout)
Dodecamethylcyclohexasiloxa ne 540-97-6	1.160	49 d		Pimephales promelas	OECD Guideline 305 (Bioconcentration: Flow-through Fish Test)
Decamethylcyclopentasiloxan e 541-02-6	7.060	35 d		Pimephales promelas	OECD Guideline 305 (Bioconcentration: Flow-through Fish Test)

# 12.4. Mobility in soil

Cured adhesives are immobile.

Hazardous substances	LogPow	Temperature	Method
CAS-No.			
octamethylcyclotetrasiloxane	6,488	25,1 °C	OECD Guideline 123 (Partition Coefficient (1-Octanol / Water), Slow-
556-67-2			Stirring Method)
Dodecamethylcyclohexasiloxa	8,87	23,6 °C	other guideline:
ne			
540-97-6			
Decamethylcyclopentasiloxan	8,023	25,3 °C	OECD Guideline 123 (Partition Coefficient (1-Octanol / Water), Slow-
e			Stirring Method)
541-02-6			

### 12.5. Results of PBT and vPvB assessment

Hazardous substances CAS-No.	PBT / vPvB		
Hexamethyldisilizane 999-97-3	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.		
Trimethoxyvinylsilane 2768-02-7	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.		
3-aminopropyltriethoxysilane 919-30-2	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.		
octamethylcyclotetrasiloxane 556-67-2	Fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.		
Dodecamethylcyclohexasiloxane 540-97-6	Fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.		
Decamethylcyclopentasiloxane 541-02-6	very Persistent and very Bioaccumulative (vPvB)		

## 12.6. Other adverse effects

No data available.

Product disposal:

Contribution of this product to waste is very insignificant in comparison to article in which it is used

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

Waste code

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

## **SECTION 14: Transport information**

14.1.	UN number
	Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
14.2.	UN proper shipping name
	Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
14.3.	Transport hazard class(es)
	Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
14.4.	Packing group
	Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
14.5.	Environmental hazards
	Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
14.6.	Special precautions for user
	Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
14.7.	Transport in bulk according to Annex II of Marpol and the IBC Code
	not applicable

**SECTION 15: Regulatory information** 

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC content (2010/75/EC) < 5 %

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

# SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text

- of all abbreviations indicated by codes in this safety data sheet are as follows:
  - H225 Highly flammable liquid and vapor.
  - H226 Flammable liquid and vapor.
  - H302 Harmful if swallowed.
  - H311 Toxic in contact with skin.
  - H314 Causes severe skin burns and eye damage.
  - H317 May cause an allergic skin reaction.
  - H332 Harmful if inhaled.
  - H361f Suspected of damaging fertility.

H373 May cause damage to organs through prolonged or repeated exposure.

- H412 Harmful to aquatic life with long lasting effects.
- H413 May cause long lasting harmful effects to aquatic life.

#### **Further information:**

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (ua-productsafety.de@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

#### Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your\_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.