

# Safety Data Sheet according to Regulation (EC) No 1907/2006

Page 1 of 7

# LOCTITE SI 595 CL TB100ML SFDN

SDS No.: 162662 V003.5 Revision: 10.04.2017 printing date: 19.07.2021 Replaces version from: 15.01.2015

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1. Product identifier LOCTITE SI 595 CL TB100ML SFDN
- **1.2. Relevant identified uses of the substance or mixture and uses advised against** Intended use: Silicone sealant
- 1.3. Details of the supplier of the safety data sheet

Henkel Ltd Wood Lane End HP24RQ Hemel Hempstead

Great Britain

Phone:+44 1442 278000Fax-no.:+44 1442 278071

ua-productsafety.uk@henkel.com

# **1.4. Emergency telephone number**

24 Hours Emergency Tel: +44 (0)1442 278497

# **SECTION 2: Hazards identification**

# 2.1. Classification of the substance or mixture

# Classification (CLP):

The substance or mixture is not hazardous according to Regulation (EC) No 1272/2008 (CLP).

### 2.2. Label elements

### Label elements (CLP):

The substance or mixture is not hazardous according to Regulation (EC) No 1272/2008 (CLP).

# 2.3. Other hazards

# None if used properly.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

# SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

General chemical description: Acetoxy curing silicone Contains no dangerous substances exceeding the limits of the EU-Regulation

### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

Inhalation: Move to fresh air. If symptoms persist, seek medical advice.

Skin contact: Rinse with running water and soap. Obtain medical attention if irritation persists.

Eye contact: Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion: Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

Prolonged or repeated contact may cause skin irritation.

Prolonged or repeated contact may cause eye irritation.

# 4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

# **SECTION 5: Firefighting measures**

**5.1. Extinguishing media Suitable extinguishing media:** Carbon dioxide, foam, powder Fine water spray

Extinguishing media which must not be used for safety reasons: None known

**5.2.** Special hazards arising from the substance or mixture carbon oxides. Silica fume Formaldehyde

**5.3. Advice for firefighters** Wear self-contained breathing apparatus.

Additional information:

In case of fire, keep containers cool with water spray.

**SECTION 6: Accidental release measures** 

# **6.1. Personal precautions, protective equipment and emergency procedures** Avoid contact with skin and eyes.

Ensure adequate ventilation.

#### **6.2. Environmental precautions**

Do not let product enter drains.

### 6.3. Methods and material for containment and cleaning up

Scrape up as much material as possible. Store in a partly filled, closed container until disposal.

### 6.4. Reference to other sections

See advice in section 8

# **SECTION 7: Handling and storage**

# 7.1. Precautions for safe handling

Use only in well-ventilated areas. Vapours should be extracted to avoid inhalation. Avoid skin and eye contact. See advice in section 8

#### Hygiene measures:

Good industrial hygiene practices should be observed. Wash hands before work breaks and after finishing work. Do not eat, drink or smoke while working.

# 7.2. Conditions for safe storage, including any incompatibilities

Store in a cool, well-ventilated place. Refer to Technical Data Sheet Never allow product to get in contact with water during storage

### 7.3. Specific enduse(s)

Silicone sealant

# SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

# **Occupational Exposure Limits**

Valid for Great Britain

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Shortterm exposure limit category / Remarks	Regulatorylist
Silicon dioxide 112945-52-5 [SILICA, AMORPHOUS, INHALABLE DUST]		6	Time Weighted Average (TWA):		EH40 WEL
Silicon dioxide 112945-52-5 [SILICA, AMORPHOUS, RESPIRABLE DUST]		2,4	Time Weighted Average (TWA):		EH40 WEL

### **Occupational Exposure Limits**

Valid for Ireland

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit	Regulatorylist
				category/Remarks	
Silicon dioxide 112945-52-5 [SILICA, AMORPHOUS, TOTAL INHALABLE DUST]		6	Time Weighted Average (TWA):		IR_OEL
Silicon dioxide 112945-52-5 [SILICA, AMORPHOUS, RESPIRABLE DUST]		2,4	Time Weighted Average (TWA):		IR_OEL

#### 8.2. Exposure controls:

Engineering controls: Ensure good ventilation/extraction.

Respiratory protection: Ensure adequate ventilation. An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR;  $\geq 0.4$  mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection: Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing. Protective eye equipment should conform to EN166.

Skin protection: Wear suitable protective clothing. Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

Viscosity

Viscosity (kinematic)

Explosive properties Solubility (qualitative)

Solubility (qualitative)

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

# **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Appearance	paste
	colourless
Odor	Acetic acid
Odour threshold	No data available / Not applicable
pH	Not applicable
Initial boiling point	Not determined
Flash point	> 100 °C (> 212 °F)
Decomposition temperature	No data available / Not applicable
Vapour pressure	Not determined
Density	1,02 g/cm3
0	
Bulk density	No data available / Not applicable

No data available / Not applicable Polymerises in presence of water. Insoluble

### No data available / Not applicable No data available / Not applicable

# 9.2. Other information

No data available / Not applicable

# **SECTION 10: Stability and reactivity**

# 10.1. Reactivity

Strong oxidizing agents. Polymerises in presence of water.

# 10.2. Chemical stability

Stable under recommended storage conditions.

### 10.3. Possibility of hazardous reactions

See section reactivity

### 10.4. Conditions to avoid

No decomposition if used according to specifications.

#### **10.5. Incompatible materials**

See section reactivity.

#### 10.6. Hazardous decomposition products

Acetic acid is liberated slowly upon contact with moisture. At higher temperatures (>150C) may release formaldehyde (traces).

At higher temperatures (>150C) may release formaldeny de (traces).

# SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

#### General toxicological information:

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation (EC) No 1272/2008. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

#### **Oral toxicity:**

This material is considered to have low toxicity if swallowed.

#### Inhalative toxicity:

Acetic acid is liberated slowly upon contact with moisture. Inhalation of vapors in high concentration may cause irritation of respiratory system

#### Skin irritation:

Prolonged or repeated contact may cause skin irritation.

### Eye irritation:

Prolonged or repeated contact may cause eye irritation.

# **SECTION 12: Ecological information**

### General ecological information:

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation (EC) No 1272/2008. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

### 12.1. Toxicity

### Ecotoxicity:

Do not empty into drains / surface water / ground water.

### 12.2. Persistence and degradability

### Persistence and Biodegradability:

The product is not biodegradable.

#### 12.3. Bioaccumulative potential / 12.4. Mobility in soil

#### **Mobility:** Cured adhesives are immobile.

**Bioaccumulative potential:** 

No data available.

# 12.5. Results of PBT and vPvB assessment

No data available.

### **12.6.** Other adverse effects

No data available.

# **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

Product disposal: Dispose of in accordance with local and national regulations. Collection and delivery to recycling enterprise or other registered elimination institution.

# Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

Waste code

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances

	SECTION 14: Transport information
14.1.	UN number
	Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
14.2.	UN proper shipping name
	Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
14.3.	Transport hazard class(es)
	Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
14.4.	Packing group
	Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
14.5.	Environmental hazards
	Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
14.6.	S pecial precautions for user
	Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
14.7.	Transport in bulk according to Annex II of Marpol and the IBC Code
	not applicable

# **SECTION 15: Regulatory information**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC content (2010/75/EC)

< 5 %

# 15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

# **SECTION 16: Other information**

#### Further information:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.