



Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 17

LOCTITE EA 3421 DC50ML SE/FI

SDS No.: 178258

V003.0

Revision: 14.12.2020

printing date: 19.07.2021

Replaces version from: 03.11.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE EA 3421 DC50ML SE/FI

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Epoxy resin

1.3. Details of the supplier of the safety data sheet

Henkel Ltd

Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 1442 278000

Fax-no.: +44 1442 278071

ua-productsafety.uk@henkel.com

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Skin irritation

Category 2

H315 Causes skin irritation.

Serious eye irritation

Category 2

H319 Causes serious eye irritation.

Skin sensitizer

Category 1

H317 May cause an allergic skin reaction.

Chronic hazards to the aquatic environment

Category 2

H411 Toxic to aquatic life with long lasting effects.

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Contains

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)

p-tert-Butylphenyl 1-(2,3-epoxy)propyl ether
Bisphenol-F epichlorhydrin resin; MW<700

Signal word: Warning

Hazard statement: H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statement: P273 Avoid release to the environment.
Prevention P280 Wear protective gloves.

Precautionary statement: P302+P352 IF ON SKIN: Wash with plenty of soap and water.
Response P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.

2.3. Other hazards

None if used properly.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	01-2119456619-26	25- 50 %	Skin Irrit. 2 H315 Skin Sens. 1 H317 Eye Irrit. 2 H319 Aquatic Chronic 2 H411
Bisphenol-F epichlorhydrin resin; MW<700 9003-36-5	01-2119454392-40	25- 50 %	Skin Irrit. 2; Dermal H315 Skin Sens. 1A H317 Aquatic Chronic 2 H411
p-tert-Butylphenyl 1-(2,3-epoxy)propyl ether 3101-60-8	221-453-2 01-2119959496-20	1- < 5 %	Skin Sens. 1A H317 Aquatic Chronic 2 H411

For full text of the H - statements and other abbreviations see section 16 "Other information".

Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

EYE: Irritation, conjunctivitis.

SKIN: Redness, inflammation.

SKIN: Rash, Urticaria.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

water, carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

None known

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x) can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes.

Ensure adequate ventilation.

Wear protective equipment.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

Wash spillage site thoroughly with soap and water or detergent solution.

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Use only in well-ventilated areas.

Avoid skin and eye contact.

Prolonged or repeated skin contact should be avoided to minimise any risk of sensitisation.

See advice in section 8

Hygiene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

Good industrial hygiene practices should be observed.

7.2. Conditions for safe storage, including any incompatibilities

Store in a cool, well-ventilated place.

Refer to Technical Data Sheet

7.3. Specific end use(s)

Epoxy resin

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational Exposure Limits**

Valid for
Great Britain

None

Occupational Exposure Limits

Valid for
Ireland

None

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
reaction product: bisphenol-A- (epichlorhydrin) 25068-38-6	aqua (freshwater)		0,006 mg/l				
reaction product: bisphenol-A- (epichlorhydrin) 25068-38-6	aqua (marine water)		0,001 mg/l				
reaction product: bisphenol-A- (epichlorhydrin) 25068-38-6	sewage treatment plant (STP)		10 mg/l				
reaction product: bisphenol-A- (epichlorhydrin) 25068-38-6	sediment (freshwater)				0,341 mg/kg		
reaction product: bisphenol-A- (epichlorhydrin) 25068-38-6	sediment (marine water)				0,034 mg/kg		
reaction product: bisphenol-A- (epichlorhydrin) 25068-38-6	Soil				0,065 mg/kg		
reaction product: bisphenol-A- (epichlorhydrin) 25068-38-6	oral				11 mg/kg		
reaction product: bisphenol-A- (epichlorhydrin) 25068-38-6	aqua (intermittent releases)		0,018 mg/l				
reaction product: bisphenol-A- (epichlorhydrin) 25068-38-6	marine water - intermittent		0,002 mg/l				
Reaction product: bisphenol-F- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (old) 9003-36-5	aqua (freshwater)		0,003 mg/l				
Reaction product: bisphenol-F- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (old) 9003-36-5	aqua (marine water)		0,0003 mg/l				
Reaction product: bisphenol-F- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (old) 9003-36-5	sewage treatment plant (STP)		10 mg/l				
Reaction product: bisphenol-F- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (old) 9003-36-5	sediment (freshwater)				0,294 mg/kg		
Reaction product: bisphenol-F- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (old) 9003-36-5	sediment (marine water)				0,0294 mg/kg		
Reaction product: bisphenol-F- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (old) 9003-36-5	Soil				0,237 mg/kg		
Reaction product: bisphenol-F- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (old) 9003-36-5	aqua (intermittent releases)		0,0254 mg/l				
Reaction product: bisphenol-F- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (old) 9003-36-5	Air						no hazard identified
Reaction product: bisphenol-F- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (old) 9003-36-5	Predator						no potential for bioaccumulation
p-tert-Butylphenyl 1-(2,3-epoxy)propyl ether 3101-60-8	aqua (freshwater)		0,0075 mg/l				
p-tert-Butylphenyl 1-(2,3-epoxy)propyl ether 3101-60-8	aqua (marine water)		0,00075 mg/l				
p-tert-Butylphenyl 1-(2,3-epoxy)propyl ether 3101-60-8	sewage treatment plant (STP)		100 mg/l				

p-tert-Butylphenyl 1-(2,3-epoxy)propyl ether 3101-60-8	sediment (freshwater)				33,54 mg/kg		
p-tert-Butylphenyl 1-(2,3-epoxy)propyl ether 3101-60-8	sediment (marine water)				3,354 mg/kg		
p-tert-Butylphenyl 1-(2,3-epoxy)propyl ether 3101-60-8	Soil				11,4 mg/kg		

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
reaction product: bisphenol-A-(epichlorhydrin) 25068-38-6	Workers	dermal	Acute/short term exposure - systemic effects		8,33 mg/kg	
reaction product: bisphenol-A-(epichlorhydrin) 25068-38-6	Workers	Inhalation	Acute/short term exposure - systemic effects		12,25 mg/m3	
reaction product: bisphenol-A-(epichlorhydrin) 25068-38-6	Workers	dermal	Long term exposure - systemic effects		8,33 mg/kg	
reaction product: bisphenol-A-(epichlorhydrin) 25068-38-6	Workers	Inhalation	Long term exposure - systemic effects		12,25 mg/m3	
reaction product: bisphenol-A-(epichlorhydrin) 25068-38-6	General population	dermal	Acute/short term exposure - systemic effects		3,571 mg/kg	
reaction product: bisphenol-A-(epichlorhydrin) 25068-38-6	General population	dermal	Long term exposure - systemic effects		3,571 mg/kg	
reaction product: bisphenol-A-(epichlorhydrin) 25068-38-6	General population	oral	Acute/short term exposure - systemic effects		0,75 mg/kg	
reaction product: bisphenol-A-(epichlorhydrin) 25068-38-6	General population	oral	Long term exposure - systemic effects		0,75 mg/kg	
reaction product: bisphenol-A-(epichlorhydrin) 25068-38-6	General population	inhalation	Acute/short term exposure - systemic effects		0,75 mg/m3	
reaction product: bisphenol-A-(epichlorhydrin) 25068-38-6	General population	inhalation	Long term exposure - systemic effects		0,75 mg/m3	
Reaction product: bisphenol-F-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (old) 9003-36-5	Workers	dermal	Long term exposure - systemic effects		104,15 mg/kg	no hazard identified
Reaction product: bisphenol-F-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (old) 9003-36-5	Workers	Inhalation	Long term exposure - systemic effects		29,39 mg/m3	no hazard identified
Reaction product: bisphenol-F-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (old) 9003-36-5	General population	dermal	Long term exposure - systemic effects		62,5 mg/kg	no hazard identified
Reaction product: bisphenol-F-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (old) 9003-36-5	General population	Inhalation	Long term exposure - systemic effects		8,7 mg/m3	no hazard identified
Reaction product: bisphenol-F-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (old) 9003-36-5	General population	oral	Long term exposure - systemic effects		6,25 mg/kg	no hazard identified
Reaction product: bisphenol-F-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (old) 9003-36-5	Workers	dermal	Acute/short term exposure - local effects		8,3 µg/cm2	no hazard identified
p-tert-Butylphenyl 1-(2,3-epoxy)propyl ether 3101-60-8	Workers	inhalation	Long term exposure - systemic effects		19,6 mg/m3	
p-tert-Butylphenyl 1-(2,3-epoxy)propyl ether 3101-60-8	Workers	inhalation	Acute/short term exposure - systemic effects		19,6 mg/m3	
p-tert-Butylphenyl 1-(2,3-epoxy)propyl ether 3101-60-8	Workers	inhalation	Acute/short term exposure - local effects		19,6 mg/m3	
p-tert-Butylphenyl 1-(2,3-epoxy)propyl ether 3101-60-8	Workers	inhalation	Long term exposure - local effects		19,6 mg/m3	
p-tert-Butylphenyl 1-(2,3-epoxy)propyl ether 3101-60-8	Workers	dermal	Long term exposure - systemic effects		5,6 mg/kg	

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Wear protective glasses.

Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.

Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Appearance	paste white
Odor	odourless
Odour threshold	No data available / Not applicable
pH	Not applicable
Melting point	No data available / Not applicable
Solidification temperature	No data available / Not applicable
Initial boiling point	> 200 °C (> 392 °F)
Flash point	210 °C (410 °F)
Evaporation rate	No data available / Not applicable
Flammability	No data available / Not applicable
Explosive limits	No data available / Not applicable
Vapour pressure	0,001 mbar
(50 °C (122 °F))	
Relative vapour density:	No data available / Not applicable
Density	1,15 g/cm ³
()	

Bulk density	No data available / Not applicable
Solubility	No data available / Not applicable
Solubility (qualitative) (Solvent: Water)	Insoluble
Partition coefficient: n-octanol/water	No data available / Not applicable
Auto-ignition temperature	No data available / Not applicable
Decomposition temperature	No data available / Not applicable
Viscosity	No data available / Not applicable
Viscosity (kinematic)	No data available / Not applicable
Explosive properties	No data available / Not applicable
Oxidising properties	No data available / Not applicable

9.2. Other information

No data available / Not applicable

SECTION 10: Stability and reactivity**10.1. Reactivity**

Reaction with oxidants.
Reaction with strong acids.
Reaction with strong bases

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

No decomposition if used according to specifications.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

carbon oxides.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute oral toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) 25068-38-6	LD50	> 2.000 mg/kg	rat	OECD Guideline 420 (Acute Oral Toxicity)
Bisphenol-F epichlorhydrin resin; MW < 700 9003-36-5	LD50	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
p-tert-Butylphenyl 1-(2,3- epoxy)propylether 3101-60-8	LD50	> 2.000 mg/kg	rat	OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure)
p-tert-Butylphenyl 1-(2,3- epoxy)propylether 3101-60-8	Acute toxicity estimate (ATE)	2.500 mg/kg		Expert judgement

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Bisphenol-F epichlorhydrin resin; MW<700 9003-36-5	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
p-tert-Butylphenyl 1-(2,3- epoxy)propylether 3101-60-8	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)

Acute inhalative toxicity:

No data available.

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	moderately irritating	24 h	rabbit	Draize Test
Bisphenol-F epichlorhydrin resin; MW<700 9003-36-5	irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
p-tert-Butylphenyl 1-(2,3- epoxy)propylether 3101-60-8	not irritating	24 h	rat	other guideline:

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Bisphenol-F epichlorhydrin resin; MW<700 9003-36-5	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
p-tert-Butylphenyl 1-(2,3- epoxy)propylether 3101-60-8	not irritating	72 h	rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Bisphenol-F epichlorhydrin resin; MW<700 9003-36-5	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
p-tert-Butylphenyl 1-(2,3- epoxy)propylether 3101-60-8	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study/ Route of administration	Metabolic activation/ Exposure time	Species	Method
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 472 (Genetic Toxicology: Escherichia coli, Reverse Mutation Assay)
Bisphenol-F epichlorhydrin resin; MW<700 9003-36-5	positive	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
p-tert-Butylphenyl 1-(2,3- epoxy)propylether 3101-60-8	positive without metabolic activation	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
p-tert-Butylphenyl 1-(2,3- epoxy)propylether 3101-60-8	positive without metabolic activation	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
p-tert-Butylphenyl 1-(2,3- epoxy)propylether 3101-60-8	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
p-tert-Butylphenyl 1-(2,3- epoxy)propylether 3101-60-8	positive	sister chromatid exchange assay in mammalian cells	without		OECD Guideline 479 (Genetic Toxicology: In Vitro Sister Chromatid Exchange Assay in Mammalian Cells)
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	negative	oral: gavage		mouse	not specified
Bisphenol-F epichlorhydrin resin; MW<700 9003-36-5	negative	oral: gavage		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Bisphenol-F epichlorhydrin resin; MW<700 9003-36-5	negative	oral: gavage		rat	OECD Guideline 486 (Unscheduled DNA Synthesis (UDS) Test with Mammalian Liver Cells in vivo)
p-tert-Butylphenyl 1-(2,3- epoxy)propylether 3101-60-8	negative	oral: gavage		rat	OECD Guideline 489 (In Vivo Mammalian Alkaline Comet Assay)

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	not carcinogenic	dermal	2 y daily	mouse	male	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	not carcinogenic	oral: gavage	2 y daily	rat	male/female	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	NOAEL P >= 50 mg/kg NOAEL F1 >= 750 mg/kg NOAEL F2 >= 750 mg/kg	Two generation study	oral: gavage	rat	OECD Guideline 416 (Two-Generation Reproduction Toxicity Study)
Bisphenol-F epichlorhydrin resin; MW<700 9003-36-5	NOAEL P > 750 mg/kg NOAEL F1 750 mg/kg NOAEL F2 750 mg/kg	two-generation study	oral: gavage	rat	OECD Guideline 416 (Two-Generation Reproduction Toxicity Study)

STOT-single exposure:

No data available.

STOT-repeated exposure::

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	NOAEL 50 mg/kg	oral: gavage	14 w daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Bisphenol-F epichlorhydrin resin; MW<700 9003-36-5	NOAEL 250 mg/kg	oral: gavage	13 w daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
p-tert-Butylphenyl 1-(2,3-epoxy)propylether 3101-60-8	NOAEL 100 mg/kg	oral: gavage	90 d daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

Aspiration hazard:

No data available.

SECTION 12: Ecological information

General ecological information:

Do not empty into drains / surface water / ground water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight \leq 700) 25068-38-6	LC50	1,75 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Bisphenol-F epichlorhydrin resin; MW<700 9003-36-5	LC50	5,7 mg/l	96 h	Leuciscus idus	OECD Guideline 203 (Fish, Acute Toxicity Test)
p-tert-Butylphenyl 1-(2,3-epoxy)propylether 3101-60-8	LC50	7,5 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)

Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight \leq 700) 25068-38-6	EC50	1,7 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Bisphenol-F epichlorhydrin resin; MW<700 9003-36-5	EC50	2,55 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
p-tert-Butylphenyl 1-(2,3-epoxy)propylether 3101-60-8	EC50	67,9 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight \leq 700) 25068-38-6	NOEC	0,3 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Bisphenol-F epichlorhydrin resin; MW<700 9003-36-5	NOEC	0,3 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	EC50	> 11 mg/l	72 h	Scenedesmus capricornutum	OECD Guideline 201 (Alga, Growth Inhibition Test)
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	NOEC	4,2 mg/l	72 h	Scenedesmus capricornutum	OECD Guideline 201 (Alga, Growth Inhibition Test)
Bisphenol-F epichlorhydrin resin; MW<700 9003-36-5	EC50	1,8 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
p-tert-Butylphenyl 1-(2,3- epoxy)propylether 3101-60-8	EC50	9 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	IC50	> 100 mg/l	3 h	activated sludge, industrial	other guideline:
Bisphenol-F epichlorhydrin resin; MW<700 9003-36-5	IC50	> 100 mg/l	3 h	activated sludge, industrial	other guideline:
p-tert-Butylphenyl 1-(2,3- epoxy)propylether 3101-60-8	EC50	> 1.000 mg/l	3 h	activated sludge of a predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

12.2. Persistence and degradability

The product is not biodegradable.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight≤700) 25068-38-6	not readily biodegradable.	aerobic	5 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Bisphenol-F epichlorhydrin resin; MW<700 9003-36-5	not readily biodegradable.	aerobic	0 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
p-tert-Butylphenyl 1-(2,3- epoxy)propylether 3101-60-8	not readily biodegradable.	aerobic	1,1 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

Cured adhesives are immobile.

Hazardous substances CAS-No.	LogPow	Temperature	Method
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) 25068-38-6	3,242	25 °C	EU Method A.8 (Partition Coefficient)
Bisphenol-F epichlorhydrin resin; MW < 700 9003-36-5	2,7 - 3,6		OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
p-tert-Butylphenyl 1-(2,3-epoxy)propyl ether 3101-60-8	3,59	20 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)

12.5. Results of PBT and vPvB assessment

Hazardous substances CAS-No.	PBT/ vPvB
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) 25068-38-6	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Bisphenol-F epichlorhydrin resin; MW < 700 9003-36-5	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
p-tert-Butylphenyl 1-(2,3-epoxy)propyl ether 3101-60-8	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Dispose of in accordance with local and national regulations.

Do not empty into drains / surface water / ground water.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

Waste code

08 04 09* waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information

14.1. UN number

ADR	3082
RID	3082
ADN	3082
IMDG	3082
IATA	3082

14.2. UN proper shipping name

ADR	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol-F Epichlorhydrin resin, Bisphenol-A Epichlorhydrin resin)
RID	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol-F Epichlorhydrin resin, Bisphenol-A Epichlorhydrin resin)
ADN	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol-F Epichlorhydrin resin, Bisphenol-A Epichlorhydrin resin)
IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol-F Epichlorhydrin resin, Bisphenol-A Epichlorhydrin resin)
IATA	Environmentally hazardous substance, liquid, n.o.s. (Bisphenol-F Epichlorhydrin resin, Bisphenol-A Epichlorhydrin resin)

14.3. Transport hazard class(es)

ADR	9
RID	9
ADN	9
IMDG	9
IATA	9

14.4. Packing group

ADR	III
RID	III
ADN	III
IMDG	III
IATA	III

14.5. Environmental hazards

ADR	not applicable
RID	not applicable
ADN	not applicable
IMDG	Marine pollutant
IATA	not applicable

14.6. Special precautions for user

ADR	not applicable Tunnelcode:
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

The transport classifications in this section apply generally to packed and bulk goods alike. For containers with a net volume of no more than 5 L for liquid substances or a net mass of no more than 5 kg for solid substances per individual or inner package, the exemptions SP 375 (ADR), 197 (IATA), 969 (IMDG) may be applied, which can result in a deviation from the transport classification for packed goods.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Ozone Depleting Substance (ODS) (Regulation 1005/2009/EC):	Not applicable
Prior Informed Consent (PIC) (Regulation 649/2012/EC):	Not applicable
Persistent Organic Pollutants (POPs) (Regulation 2019/1021/EC) :	Not applicable

EU. REACH, Annex XVII, Marketing and Use Restrictions (Regulation 1907/2006/EC): Not applicable

VOC content < 3,00 %
(2010/75/EC)

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H411 Toxic to aquatic life with long lasting effects.

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (ua-productsafety.de@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.



Safety Data Sheet according to (EC) No 1907/2006 as amended

SDS No. : 152796

V003.0

LOCTITE EA 3421 DC50ML SE/FI

Revision: 14.12.2020

printing date: 19.07.2021

Replaces version from: 05.09.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE EA 3421 DC50ML SE/FI

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Epoxy Hardener

1.3. Details of the supplier of the safety data sheet

Henkel Ltd

Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 1442 278000

Fax-no.: +44 1442 278071

ua-productsafety.uk@henkel.com

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Skin corrosion

Sub-category 1B

H314 Causes severe skin burns and eye damage.

Serious eye damage

Category 1

H318 Causes serious eye damage.

Skin sensitizer

Category 1

H317 May cause an allergic skin reaction.

Chronic hazards to the aquatic environment

Category 2

H411 Toxic to aquatic life with long lasting effects.

2.2. Label elements

Label elements (CLP):

Hazard pictogram:**Contains**

Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine

C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer

3,6-diazoctanethylenediamine

2-piperazine-1-ylethylamine

3,6,9-triazaundecamethylenediamine

Signal word:

Danger

Hazard statement:

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statement:
Prevention

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statement:
Response

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER or doctor.

2.3. Other hazards

None if used properly.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine 68082-29-1	500-191-5 500-191-5	25- 50 %	Aquatic Chronic 2 H411 Eye Dam. 1 H318 Skin Irrit. 2 H315 Skin Sens. 1A H317
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer 68082-29-1	500-191-5 01-2119972320-44	20- 40 %	Skin Irrit. 2 H315 Eye Dam. 1 H318 Skin Sens. 1A H317 Aquatic Chronic 2 H411
Polyamide adduct 106906-26-7	500-296-6	10- 20 %	Aquatic Acute 1 H400
benzyl alcohol 100-51-6	202-859-9 01-2119492630-38	5- < 10 %	Acute Tox. 4; Oral H302 Acute Tox. 4; Inhalation H332 Eye Irrit. 2 H319
2,4,6-tris(dimethylaminomethyl)phenol 90-72-2	202-013-9 01-2119560597-27	1- < 5 %	Skin Corr. 1C H314 Acute Tox. 4; Oral H302 Eye Dam. 1 H318
3,6-diazaoctanethylenediamin 112-24-3	203-950-6 01-2119487919-13	1- < 5 %	Acute Tox. 4; Oral H302 Acute Tox. 4; Dermal H312 Skin Sens. 1 H317 Skin Corr. 1B H314 Aquatic Chronic 3 H412
2-piperazin-1-ylethylamine 140-31-8	205-411-0 01-2119471486-30	1- < 3 %	Acute Tox. 3; Dermal H311 Acute Tox. 4; Oral H302 Skin Corr. 1B H314 Aquatic Chronic 3 H412 Skin Sens. 1 H317 Repr. 2 H361
3,6,9-triazaundecamethylenediamine 112-57-2	203-986-2 01-2119487290-37	0,1- < 1 %	Acute Tox. 4; Dermal H312 Acute Tox. 4; Oral H302 Skin Sens. 1 H317 Aquatic Chronic 2 H411 Skin Corr. 1B H314

For full text of the H - statements and other abbreviations see section 16 "Other information".
Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

SKIN: Rash, Urticaria.

Causes burns.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x) can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes.

Wear protective equipment.

Ensure adequate ventilation.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

Wash spillage site thoroughly with soap and water or detergent solution.

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Use only in well-ventilated areas.

Avoid skin and eye contact.

Prolonged or repeated skin contact should be avoided to minimise any risk of sensitisation.

See advice in section 8

Hygiene measures:

Good industrial hygiene practices should be observed.

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

7.2. Conditions for safe storage, including any incompatibilities

Store in a cool, well-ventilated place.

Refer to Technical Data Sheet

7.3. Specific end use(s)

Epoxy Hardener

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational Exposure Limits**

Valid for
Great Britain

None

Occupational Exposure Limits

Valid for
Ireland

None

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer 68082-29-1	aqua (freshwater)		0,00434 mg/l				
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer 68082-29-1	aqua (marine water)		0,00043 mg/l				
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer 68082-29-1	aqua (intermittent releases)		0,0434 mg/l				
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer 68082-29-1	sewage treatment plant (STP)		3,84 mg/l				
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer 68082-29-1	sediment (freshwater)				434,02 mg/kg		
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer 68082-29-1	sediment (marine water)				43,4 mg/kg		
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer 68082-29-1	Soil				86,78 mg/kg		
Benzyl alcohol 100-51-6	Soil				0,456 mg/kg		
Benzyl alcohol 100-51-6	sewage treatment plant (STP)		39 mg/l				
Benzyl alcohol 100-51-6	sediment (freshwater)				5,27 mg/kg		
Benzyl alcohol 100-51-6	sediment (marine water)				0,527 mg/kg		
Benzyl alcohol 100-51-6	aqua (marine water)		0,1 mg/l				
Benzyl alcohol 100-51-6	aqua (intermittent releases)		2,3 mg/l				
Benzyl alcohol 100-51-6	aqua (freshwater)		1 mg/l				
Benzyl alcohol 100-51-6	Air						no hazard identified
Benzyl alcohol 100-51-6	Predator						no potential for bioaccumulation
2,4,6-Tris(dimethylaminomethyl)phenol 90-72-2	aqua (freshwater)		0,046 mg/l				
2,4,6-Tris(dimethylaminomethyl)phenol 90-72-2	aqua (marine water)		0,005 mg/l				
2,4,6-Tris(dimethylaminomethyl)phenol 90-72-2	freshwater - intermittent		0,46 mg/l				
2,4,6-Tris(dimethylaminomethyl)phenol 90-72-2	marine water - intermittent		0,046 mg/l				
2,4,6-Tris(dimethylaminomethyl)phenol 90-72-2	sewage treatment plant (STP)		0,2 mg/l				
2,4,6-Tris(dimethylaminomethyl)phenol 90-72-2	sediment (freshwater)				0,262 mg/kg		
2,4,6-Tris(dimethylaminomethyl)phenol 90-72-2	sediment (marine water)				0,026 mg/kg		
2,4,6-Tris(dimethylaminomethyl)phenol 90-72-2	Soil				0,025 mg/kg		
3,6-diazaoctanethylenediamin 112-24-3	aqua (freshwater)		0,027 mg/l				
3,6-diazaoctanethylenediamin 112-24-3	aqua (marine water)		0,003 mg/l				
3,6-diazaoctanethylenediamin 112-24-3	Sewage treatment plant		0,13 mg/l				
3,6-diazaoctanethylenediamin 112-24-3	sediment (freshwater)				8,572 mg/kg		
3,6-diazaoctanethylenediamin	sediment				0,857		

112-24-3	(marine water)				mg/kg		
3,6-diazaoctanethylenediamin 112-24-3	Soil				1,25 mg/kg		
3,6-diazaoctanethylenediamin 112-24-3	freshwater - intermittent		0,2 mg/l				
3,6-diazaoctanethylenediamin 112-24-3	marine water - intermittent		0,02 mg/l				
2-Piperazin-1-ylethylamine 140-31-8	aqua (freshwater)		0,058 mg/l				
2-Piperazin-1-ylethylamine 140-31-8	aqua (marine water)		0,0058 mg/l				
2-Piperazin-1-ylethylamine 140-31-8	sediment (freshwater)				215 mg/kg		
2-Piperazin-1-ylethylamine 140-31-8	sediment (marine water)				21,5 mg/kg		
2-Piperazin-1-ylethylamine 140-31-8	Soil				1 mg/kg		
2-Piperazin-1-ylethylamine 140-31-8	sewage treatment plant (STP)		250 mg/l				
2-Piperazin-1-ylethylamine 140-31-8	aqua (intermittent releases)		0,58 mg/l				
3,6,9-triazaundecamethylenediamine 112-57-2	Soil				0,683 mg/kg		
3,6,9-triazaundecamethylenediamine 112-57-2	aqua (freshwater)		0,0068 mg/l				
3,6,9-triazaundecamethylenediamine 112-57-2	aqua (marine water)		0,00068 mg/l				
3,6,9-triazaundecamethylenediamine 112-57-2	sediment (freshwater)				3,43 mg/kg		
3,6,9-triazaundecamethylenediamine 112-57-2	sediment (marine water)				0,343 mg/kg		
3,6,9-triazaundecamethylenediamine 112-57-2	sewage treatment plant (STP)		9,73 mg/l				

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer 68082-29-1	Workers	inhalation	Long term exposure - systemic effects		3,9 mg/m3	
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer 68082-29-1	Workers	dermal	Long term exposure - systemic effects		1,1 mg/kg	
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer 68082-29-1	General population	inhalation	Long term exposure - systemic effects		0,97 mg/m3	
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer 68082-29-1	General population	dermal	Long term exposure - systemic effects		0,56 mg/kg	
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer 68082-29-1	General population	oral	Long term exposure - systemic effects		0,56 mg/kg	
Benzyl alcohol 100-51-6	General population	oral	Acute/short term exposure - systemic effects		20 mg/kg	no hazard identified
Benzyl alcohol 100-51-6	General population	oral	Long term exposure - systemic effects		4 mg/kg	no hazard identified
Benzyl alcohol 100-51-6	Workers	inhalation	Acute/short term exposure - systemic effects		110 mg/m3	no hazard identified
Benzyl alcohol 100-51-6	Workers	inhalation	Long term exposure - systemic effects		22 mg/m3	no hazard identified
Benzyl alcohol 100-51-6	General population	inhalation	Acute/short term exposure - systemic effects		27 mg/m3	no hazard identified
Benzyl alcohol 100-51-6	General population	inhalation	Long term exposure - systemic effects		5,4 mg/m3	no hazard identified
Benzyl alcohol 100-51-6	Workers	dermal	Acute/short term exposure - systemic effects		40 mg/kg	no hazard identified
Benzyl alcohol 100-51-6	Workers	dermal	Long term exposure - systemic effects		8 mg/kg	no hazard identified
Benzyl alcohol 100-51-6	General population	dermal	Acute/short term exposure - systemic effects		20 mg/kg	no hazard identified
Benzyl alcohol 100-51-6	General population	dermal	Long term exposure - systemic effects		4 mg/kg	no hazard identified
2,4,6-Tris(dimethylaminomethyl)phenol 90-72-2	Workers	inhalation	Long term exposure - systemic effects		0,53 mg/m3	
2,4,6-Tris(dimethylaminomethyl)phenol 90-72-2	Workers	inhalation	Acute/short term exposure - systemic effects		2,1 mg/m3	
2,4,6-Tris(dimethylaminomethyl)phenol 90-72-2	Workers	dermal	Long term exposure - systemic effects		0,15 mg/kg	
2,4,6-Tris(dimethylaminomethyl)phenol 90-72-2	Workers	dermal	Acute/short term exposure - systemic effects		0,6 mg/kg	
2,4,6-Tris(dimethylaminomethyl)phenol 90-72-2	General population	inhalation	Long term exposure - systemic effects		0,13 mg/m3	
2,4,6-Tris(dimethylaminomethyl)phenol 90-72-2	General population	inhalation	Acute/short term exposure - systemic effects		0,13 mg/m3	
2,4,6-Tris(dimethylaminomethyl)phenol 90-72-2	General population	dermal	Long term exposure - systemic effects		0,075 mg/kg	
2,4,6-Tris(dimethylaminomethyl)phenol 90-72-2	General population	dermal	Acute/short term exposure -		0,075 mg/kg	

			systemic effects			
2,4,6-Tris(dimethylaminomethyl)phenol 90-72-2	General population	oral	Long term exposure - systemic effects		0,075 mg/kg	
3,6-diazaoctanethylenediamin 112-24-3	Workers	inhalation	Long term exposure - systemic effects		0,54 mg/m3	
3,6-diazaoctanethylenediamin 112-24-3	General population	inhalation	Long term exposure - systemic effects		0,096 mg/m3	
3,6-diazaoctanethylenediamin 112-24-3	General population	oral	Long term exposure - systemic effects		0,14 mg/kg	
2-Piperazin-1-ylethylamine 140-31-8	Workers	inhalation	Acute/short term exposure - local effects		80 mg/m3	
2-Piperazin-1-ylethylamine 140-31-8	Workers	inhalation	Long term exposure - local effects		0,015 mg/m3	
2-Piperazin-1-ylethylamine 140-31-8	Workers	Inhalation	Acute/short term exposure - systemic effects		10,6 mg/m3	
2-Piperazin-1-ylethylamine 140-31-8	Workers	dermal	Long term exposure - systemic effects		3,33 mg/kg	
2-Piperazin-1-ylethylamine 140-31-8	Workers	Inhalation	Long term exposure - systemic effects		10,6 mg/m3	
3,6,9-triazaundecamethylenediamine 112-57-2	Workers	dermal	Long term exposure - systemic effects		0,74 mg/kg	
3,6,9-triazaundecamethylenediamine 112-57-2	Workers	inhalation	Long term exposure - systemic effects		1,29 mg/m3	
3,6,9-triazaundecamethylenediamine 112-57-2	Workers	inhalation	Acute/short term exposure - systemic effects		6940 mg/m3	
3,6,9-triazaundecamethylenediamine 112-57-2	General population	dermal	Long term exposure - systemic effects		0,32 mg/kg	
3,6,9-triazaundecamethylenediamine 112-57-2	General population	inhalation	Long term exposure - systemic effects		0,38 mg/m3	
3,6,9-triazaundecamethylenediamine 112-57-2	General population	oral	Long term exposure - systemic effects		0,53 mg/kg	
3,6,9-triazaundecamethylenediamine 112-57-2	General population	oral	Acute/short term exposure - systemic effects		26 mg/kg	
3,6,9-triazaundecamethylenediamine 112-57-2	General population	inhalation	Acute/short term exposure - systemic effects		2071 mg/m3	
3,6,9-triazaundecamethylenediamine 112-57-2	General population	dermal	Acute/short term exposure - systemic effects		10 mg/kg	
3,6,9-triazaundecamethylenediamine 112-57-2	General population	dermal	Acute/short term exposure - local effects		1,29 mg/cm2	
3,6,9-triazaundecamethylenediamine 112-57-2	General population	dermal	Long term exposure - local effects		0,56 mg/cm2	
3,6,9-triazaundecamethylenediamine 112-57-2	Workers	dermal	Long term exposure - local effects		0,036 mg/cm2	

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.

Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Appearance	liquid Amber, clear
Odor	of amine
Odour threshold	No data available / Not applicable
pH	Not available.
Melting point	No data available / Not applicable
Solidification temperature	No data available / Not applicable
Initial boiling point	> 180 °C (> 356 °F)
Flash point	110 °C (230 °F)
Evaporation rate	No data available / Not applicable
Flammability	No data available / Not applicable
Explosive limits	No data available / Not applicable
Vapour pressure (50 °C (122 °F))	0,04 mbar
Relative vapour density:	No data available / Not applicable

Density	1,1 g/cm ³
()	
Bulk density	No data available / Not applicable
Solubility	No data available / Not applicable
Solubility (qualitative)	Insoluble
(Solvent: Water)	
Partition coefficient: n-octanol/water	No data available / Not applicable
Auto-ignition temperature	No data available / Not applicable
Decomposition temperature	No data available / Not applicable
Viscosity	No data available / Not applicable
Viscosity (kinematic)	No data available / Not applicable
Explosive properties	No data available / Not applicable
Oxidising properties	No data available / Not applicable

9.2. Other information

No data available / Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

Reaction with strong acids.

Reacts with strong oxidants.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

Stable under normal conditions of storage and use.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

carbon oxides.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine 68082-29-1	LD50	> 2.000 mg/kg	rat	OECD Guideline 423 (Acute Oral toxicity)
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer 68082-29-1	LD50	> 2.000 mg/kg	rat	OECD Guideline 423 (Acute Oral toxicity)
benzyl alcohol 100-51-6	LD50	1.620 mg/kg	rat	not specified
2,4,6-tris(dimethylaminomethyl)phenol 90-72-2	LD50	1.200 mg/kg	rat	not specified
3,6-diazaoctanethylenediamin 112-24-3	LD50	1.591 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
3,6,9-triazaundecamethylenediamine 112-57-2	LD50	1.716 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine 68082-29-1	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer 68082-29-1	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
benzyl alcohol 100-51-6	Acute toxicity estimate (ATE)	2.500 mg/kg		Expert judgement
3,6-diazaoctanethylenediamin 112-24-3	LD50	1.465 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
2-piperazin-1-ylethylamine 140-31-8	LD50	866 mg/kg	rabbit	Draize Test
3,6,9-triazaundecamethylenediamine 112-57-2	LD50	1.260 mg/kg	rabbit	not specified

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
benzyl alcohol 100-51-6	Acute toxicity estimate (ATE)	4,17 mg/l	dust/mist			Expert judgement
benzyl alcohol 100-51-6	LC50	> 4,178 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine 68082-29-1	irritating			OECD Guideline 439 (In Vitro Skin Irritation: Reconstructed Human Epidermis (RHE) Test Method)
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer 68082-29-1	irritating		In vitro	OECD Guideline 439 (In Vitro Skin Irritation: Reconstructed Human Epidermis (RHE) Test Method)
benzyl alcohol 100-51-6	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
2,4,6- tris(dimethylaminomethyl) phenol 90-72-2	corrosive	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
3,6- diazaoctanethylenediamin 112-24-3	corrosive		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
2-piperazin-1- ylethylamine 140-31-8	corrosive	20 min	rabbit	not specified
3,6,9- triazaundecamethylenedia mine 112-57-2	corrosive	4 h	rabbit	Draize Test

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine 68082-29-1	corrosive		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer 68082-29-1	Category 1 (irreversible effects on the eye)		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
benzyl alcohol 100-51-6	irritating	24 h	rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine 68082-29-1	Sensitizing	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer 68082-29-1	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
benzyl alcohol 100-51-6	not sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
2,4,6-tris(dimethylaminomethyl)phenol 90-72-2	not sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
2,4,6-tris(dimethylaminomethyl)phenol 90-72-2	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
3,6-diazaoctanethylenediamin 112-24-3	sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
2-piperazin-1-ylethylamine 140-31-8	sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
3,6,9-triazaundecamethylenediamine 112-57-2	sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study/ Route of administration	Metabolic activation / Exposure time	Species	Method
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer 68082-29-1	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer 68082-29-1	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
benzyl alcohol 100-51-6	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay)
2,4,6- tris(dimethylaminomethyl)phenol 90-72-2	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
2,4,6- tris(dimethylaminomethyl)phenol 90-72-2	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
2,4,6- tris(dimethylaminomethyl)phenol 90-72-2	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
3,6- diazaoctanethylenediamin 112-24-3	positive	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
3,6- diazaoctanethylenediamin 112-24-3	negative	DNA damage and repair assay, unscheduled DNA synthesis in mammalian cells in vitro	with and without		OECD Guideline 482 (Genetic Toxicology: DNA Damage and Repair, Unscheduled DNA Synthesis in Mammalian Cells In Vitro)
2-piperazin-1- ylethylamine 140-31-8	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
2-piperazin-1- ylethylamine 140-31-8	negative	DNA damage and repair assay, unscheduled DNA synthesis in mammalian cells in vitro	with and without		not specified
2-piperazin-1- ylethylamine 140-31-8	negative	mammalian cell gene mutation assay	with and without		not specified
3,6,9- triazaundecamethylenedia mine 112-57-2	positive	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
3,6,9- triazaundecamethylenedia mine 112-57-2	ambiguous	sister chromatid exchange assay in mammalian cells	with and without		OECD Guideline 479 (Genetic Toxicology: In Vitro Sister Chromatid Exchange Assay in Mammalian Cells)
3,6,9- triazaundecamethylenedia mine 112-57-2	negative	DNA damage and repair assay, unscheduled DNA synthesis in mammalian cells in vitro	with and without		OECD Guideline 482 (Genetic Toxicology: DNA Damage and Repair, Unscheduled DNA Synthesis in Mammalian Cells In Vitro)
benzyl alcohol 100-51-6	negative	intraperitoneal		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
3,6- diazaoctanethylenediamin 112-24-3	negative	intraperitoneal		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

2-piperazin-1-ylethylamine 140-31-8	negative	intraperitoneal		mouse	not specified
3,6,9-triazaundecamethylenediamine 112-57-2	negative	intraperitoneal		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
benzyl alcohol 100-51-6	not carcinogenic	oral: gavage	104 weeks once daily, 5 days/week	rat	male/female	equivalent or similar OECD Guideline 451 (Carcinogenicity Studies)

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
benzyl alcohol 100-51-6	NOAEL P 200 mg/kg	screening	oral: gavage	mouse	not specified
2-piperazin-1-ylethylamine 140-31-8	NOAEL P 8000 ppm NOAEL F1 8000 ppm	screening	oral: drinking water	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction/ Developmental Toxicity Screening Test)

STOT-single exposure:

No data available.

STOT-repeated exposure::

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
benzyl alcohol 100-51-6	NOAEL 400 mg/kg	oral: gavage	13 weeks once daily, 5 days/week	rat	equivalent or similar to OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
3,6- diazaoctanethylenediamin 112-24-3	LOAEL 50 mg/kg	oral: gavage	26 w daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
3,6- diazaoctanethylenediamin 112-24-3	NOAEL 50 mg/kg	oral: gavage	26 w daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
2-piperazin-1- ylethylamine 140-31-8	NOAEL 2000 ppm	oral: drinking water	>= 28 d daily	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
3,6,9- triazaundecamethylenedia mine 112-57-2	LOAEL 50 mg/kg	oral: gavage	26 w daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
3,6,9- triazaundecamethylenedia mine 112-57-2	NOAEL 50 mg/kg	oral: gavage	26 w daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

Aspiration hazard:

No data available.

SECTION 12: Ecological information

General ecological information:

Do not empty into drains / surface water / ground water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine 68082-29-1	LC50	7,07 mg/l	96 h	Danio rerio	OECD Guideline 203 (Fish, Acute Toxicity Test)
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer 68082-29-1	LC50	7,07 mg/l	96 h	Danio rerio	OECD Guideline 203 (Fish, Acute Toxicity Test)
benzyl alcohol 100-51-6	LC50	460 mg/l	96 h	Pimephales promelas	EPA OPP 72-1 (Fish Acute Toxicity Test)
2,4,6-tris(dimethylaminomethyl)phenol 90-72-2	LC50	153 mg/l	96 h	Brachydanio rerio (new name: Danio rerio)	ISO 7346-1 (Determination of the Acute Lethal Toxicity of Substances to a Freshwater Fish [Brachydanio rerio Hamilton-Buchanan (Teleostei, Cyprinidae)])
3,6-diazaoctanethylenediamine 112-24-3	LC50	570 mg/l	96 h	Poecilia reticulata	OECD Guideline 203 (Fish, Acute Toxicity Test)
2-piperazin-1-ylethylamine 140-31-8	LC50	> 100 mg/l	96 h	Salmo gairdneri (new name: Oncorhynchus mykiss)	OECD Guideline 203 (Fish, Acute Toxicity Test)
3,6,9-triazaundecamethylenediamine 112-57-2	LC50	420 mg/l	96 h	Poecilia reticulata	OECD Guideline 203 (Fish, Acute Toxicity Test)

Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine 68082-29-1	EC50	7,07 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer 68082-29-1	EC50	7,07 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
benzyl alcohol 100-51-6	EC50	230 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
3,6-diazaoctanethylenediamine 112-24-3	EC50	31 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
2-piperazin-1-ylethylamine 140-31-8	EC50	32 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
3,6,9-triazaundecamethylenediamine 112-57-2	EC50	24,1 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
benzyl alcohol 100-51-6	NOEC	51 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine 68082-29-1	EC50	4,34 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine 68082-29-1	NOEC	0,5 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer 68082-29-1	EC50	4,34 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer 68082-29-1	NOEC	0,5 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
benzyl alcohol 100-51-6	EC50	770 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
benzyl alcohol 100-51-6	NOEC	310 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
2,4,6-tris(dimethylaminomethyl)phenol 90-72-2	EC50	84 mg/l	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
2,4,6-tris(dimethylaminomethyl)phenol 90-72-2	NOEC	6,25 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
3,6-diazoctanethylenediamine 112-24-3	EC10	< 2,5 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
3,6-diazoctanethylenediamine 112-24-3	EC50	20 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
2-piperazin-1-ylethylamine 140-31-8	NOEC	31 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
2-piperazin-1-ylethylamine 140-31-8	EC50	495 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
3,6,9-triazaundecamethylenediamine 112-57-2	NOEC	0,5 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
3,6,9-triazaundecamethylenediamine 112-57-2	EC50	6,8 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine 68082-29-1	EC10	130 mg/l	3 h	activated sludge of a predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer 68082-29-1	EC10	130 mg/l	3 h	activated sludge of a predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
benzyl alcohol 100-51-6	EC10	658 mg/l	17 h	Pseudomonas putida	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm-Test)

2,4,6-tris(dimethylaminomethyl)phenol 90-72-2	EC0	27 mg/l	16 h	Pseudomonas putida	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm-Test)
3,6-diazaoctanethylenediamin 112-24-3	EC0	137 mg/l	30 min	Pseudomonas putida	DIN 38412, part 27 (Bacterial oxygen consumption test)
2-piperazin-1-ylethylamine 140-31-8	EC10	100 mg/l	17 h		not specified
3,6,9-triazaundecamethylenediamine 112-57-2	EC 50	1.600 mg/l	1 h		EU Method C.11 (Biodegradation: Activated Sludge Respiration Inhibition Test)

12.2. Persistence and degradability

The product is not biodegradable.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine 68082-29-1	not readily biodegradable.	no data	0 - 60 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer 68082-29-1	not readily biodegradable.	no data	0 - 60 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
benzyl alcohol 100-51-6	readily biodegradable	aerobic	92 - 96 %	14 d	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))
2,4,6-tris(dimethylaminomethyl)phenol 90-72-2	not readily biodegradable.	aerobic	4 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
3,6-diazaoctanethylenediamin 112-24-3	not inherently biodegradable	aerobic	0 %	28 d	OECD Guideline 302 B (Inherent biodegradability: Zahn-Wellens/EMPA Test)
3,6-diazaoctanethylenediamin 112-24-3	not readily biodegradable.	aerobic	0 %	162 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
2-piperazin-1-ylethylamine 140-31-8	under test conditions no biodegradation observed	aerobic	0 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
3,6,9-triazaundecamethylenediamine 112-57-2	under test conditions no biodegradation observed	aerobic	0 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

Cured adhesives are immobile.

Hazardous substances CAS-No.	LogPow	Temperature	Method
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine 68082-29-1	10,34		QSAR (Quantitative Structure Activity Relationship)
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer 68082-29-1	10,34		QSAR (Quantitative Structure Activity Relationship)
benzyl alcohol 100-51-6	1,05	20 °C	EU Method A.8 (Partition Coefficient)
2,4,6-tris(dimethylaminomethyl)phenol 90-72-2	-0,66	21,5 °C	EPA OPPTS 830.7550 (Partition Coefficient, n-octanol / H ₂ O, Shake Flask Method)
3,6-diazaoctanethylenediamine 112-24-3	-2,65		OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
2-piperazin-1-ylethylamine 140-31-8	-1,48		OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
3,6,9-triazaundecamethylenediamine 112-57-2	-3,16		not specified

12.5. Results of PBT and vPvB assessment

Hazardous substances CAS-No.	PBT/ vPvB
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine 68082-29-1	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer 68082-29-1	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Polyamide adduct 106906-26-7	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
benzyl alcohol 100-51-6	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
2,4,6-tris(dimethylaminomethyl)phenol 90-72-2	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
3,6-diazaoctanethylenediamine 112-24-3	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
2-piperazin-1-ylethylamine 140-31-8	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
3,6,9-triazaundecamethylenediamine 112-57-2	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Collection and delivery to recycling enterprise or other registered elimination institution.
Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.
Disposal must be made according to official regulations.

Waste code

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

08 04 09* waste adhesives and sealants containing organic solvents and other dangerous substances

SECTION 14: Transport information**14.1. UN number**

ADR	2735
RID	2735
ADN	2735
IMDG	2735
IATA	2735

14.2. UN proper shipping name

ADR	AMINES, LIQUID, CORROSIVE, N.O.S. (2,4,6-Tris(dimethylamino methyl) phenole, Triethylenetetramine)
RID	AMINES, LIQUID, CORROSIVE, N.O.S. (2,4,6-Tris(dimethylamino methyl) phenole, Triethylenetetramine)
ADN	AMINES, LIQUID, CORROSIVE, N.O.S. (2,4,6-Tris(dimethylamino methyl) phenole, Triethylenetetramine)
IMDG	AMINES, LIQUID, CORROSIVE, N.O.S. (2,4,6-Tris(dimethylamino methyl) phenole, Triethylenetetramine, C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer)
IATA	Amines, liquid, corrosive, n.o.s. (2,4,6-Tris(dimethylamino methyl) phenole, Triethylenetetramine)

14.3. Transport hazard class(es)

ADR	8
RID	8
ADN	8
IMDG	8
IATA	8

14.4. Packing group

ADR	III
RID	III
ADN	III
IMDG	III
IATA	III

14.5. Environmental hazards

ADR	Environmentally Hazardous
RID	Environmentally Hazardous

ADN	Environmentally Hazardous
IMDG	Marine pollutant
IATA	not applicable

14.6. Special precautions for user

ADR	not applicable Tunnelcode: (E)
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Ozone Depleting Substance (ODS) (Regulation 1005/2009/EC):	Not applicable
Prior Informed Consent (PIC) (Regulation 649/2012/EC):	Not applicable
Persistent Organic Pollutants (POPs) (Regulation 2019/1021/EC) :	Not applicable

EU. REACH, Annex XVII, Marketing and Use Restrictions (Regulation 1907/2006/EC): Not applicable

VOC content (2010/75/EC)	< 3,00 % Combined A/B
-----------------------------	-----------------------

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H302 Harmful if swallowed.
H311 Toxic in contact with skin.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H361 Suspected of damaging fertility or the unborn child.
H400 Very toxic to aquatic life.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (ua-productsafety.de@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.