SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Label Off Super Trade name or designation

of the mixture

Registration number

GJ9X-282V-3003-0C23 UFI:

Synonyms None.

BDS002624AE **Product code** 24-March-2022 Issue date

Version number 1.1

Revision date 12-May-2022 Supersedes date 24-March-2022

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Cleaners - Precision

Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

Company name CRC Industries Europe by

Address Touwslagerstraat 1

> 9240 Zele Belgium

Telephone +32(0)52/45.60.11 +32(0)52/45.00.34 Fax E-mail hse@crcind.com www.crcind.com Website

1.4. Emergency telephone

Tel.: +32(0)52/45.60.11 (office hours: 9-17h CET)

number

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification

Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards

Aerosols Category 1 H222 - Extremely flammable

aerosol.

H229 - Pressurized container: May

burst if heated.

Health hazards

Skin corrosion/irritation Category 2 H315 - Causes skin irritation.

Skin sensitisation H317 - May cause an allergic skin Category 1

reaction.

Specific target organ toxicity - single Category 3 narcotic effects H336 - May cause drowsiness or

exposure

dizziness.

Environmental hazards

Hazardous to the aquatic environment, H411 - Toxic to aquatic life with Category 2

long lasting effects. long-term aquatic hazard

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Cyclohexane, Hydrocarbons, C6-C7, n-alkanes,isoalkanes,cyclics,< 5% n-hexane, Hydrocarbons, Contains:

C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics, Orange, sweet, extract

Hazard pictograms



Material name: Label Off Super - Manufacturers

BDS002624AE Version #: 1.1 Revision date: 12-May-2022 Issue date: 24-March-2022

Signal word

Hazard statements

H222

H229

H315

H317

H336

H411

Danger

Extremely flammable aerosol.

Pressurized container: May burst if heated.

Causes skin irritation.

May cause an allergic skin reaction.

May cause drowsiness or dizziness.

Toxic to aquatic life with long lasting effects.

Precautionary statements

_					
Ρ	rev	ÆΙ	1ti	റ	n

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing mist/vapours.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves.

Response Not assigned.

Storage

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental label information Regulation (EC) No 648/2004 on detergents:

aliphatic hydrocarbons > 30 %

perfumes: d-limonene

2.3. Other hazardsThis mixture does not contain substances assessed to be vPvB / PBT according to Regulation

(EC) No 1907/2006, Annex XIII. The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or

Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

Mixture

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Hydrocarbons, C6-C7, n-alkanes,isoalkanes,cyclics,< 5% n-hexane	25 - 50	EC921-024-6 921-024-6	01-2119475514-35	-	
Classification	•	2;H225, Skin Irrit. 2;I quatic Chronic 2;H41	H315, STOT SE 3;H336, As _l 1	p. Tox.	
Cyclohexane	10 - <25	110-82-7 203-806-2	01-2119463273-41	601-017-00-1	#
Classification			H315, STOT SE 3;H336, As _l Aquatic Chronic 1;H410	p. Tox.	
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	10 - 25	EC919-857-5 919-857-5	01-2119463258-33	-	
Classification	: Flam. Liq.	3;H226, STOT SE 3;	H336, Asp. Tox. 1;H304		
Orange, sweet, extract	10 - 25	8028-48-6 232-433-8	01-2119493353-35	-	
Classification	•	3;H226, Skin Irrit. 2;l quatic Chronic 2;H41	H315, Skin Sens. 1;H317, A 1	sp. Tox.	
Carbon dioxide	1 - 5	124-38-9 204-696-9	-	-	#
Classification	: Press. Gas	s;H280			

List of abbreviations and symbols that may be used above

#: This substance has been assigned Union workplace exposure limit(s).

M: M-factor

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments The full text for all H-statements is displayed in section 16.

BDS002624AE Version #: 1.1 Revision date: 12-May-2022 Issue date: 24-March-2022

SDS GREAT BRITAIN

SECTION 4: First aid measures

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves. Wash contaminated clothing before reuse.

4.1. Description of first aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison

centre or doctor/physician if you feel unwell.

Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash

contaminated clothing before reuse.

Eye contact Ingestion

delayed

Rinse with water. Get medical attention if irritation develops and persists.

4.2. Most important symptoms and effects, both acute and

re

In the unlikely event of swallowing contact a physician or poison control centre. Rinse mouth. May cause drowsiness or dizziness. Headache. Nausea, vomiting. Skin irritation. May cause

redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Todiloco dila paili. May oddoo dil allorgio olili Todolloli. E

4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards

Extremely flammable aerosol.

5.1. Extinguishing media

Suitable extinguishing

media

Foam. Powder. Carbon dioxide (CO2).

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Contents under pressure. Pressurised container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Special protective equipment for firefighters

Special fire fighting procedures

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapour pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material.

For emergency responders

Keep unnecessary personnel away. Avoid breathing mist/vapours. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

6.2. Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up

Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. The product is immiscible with water and will spread on the water surface. Prevent product from entering drains. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

6.4. Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

Material name: Label Off Super - Manufacturers SDS GREAT BRITAIN

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Pressurised container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing mist/vapours. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS). Storage class (TRGS 510): 2B (Aerosol dispensers and lighters)

7.3. Specific end use(s)

Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

UK. EH40 Workplace Exposure Limits (WELs)

Components	Туре	Value	
Carbon dioxide (CAS 124-38-9)	STEL	27400 mg/m3	
		15000 ppm	
	TWA	9150 mg/m3	
		5000 ppm	
Cyclohexane (CAS 110-82-7)	STEL	1050 mg/m3	
		300 ppm	
	TWA	350 mg/m3	
		100 ppm	

Biological limit values

No biological exposure limits noted for the ingredient(s).

Follow standard monitoring procedures.

Recommended monitoring

procedures

Derived no effect levels (DNELs)

General	Population
General	robulation

Components	Value	Assessment factor	Notes
Cyclohexane (CAS 110-82-7)			
Long-term, Local, Inhalation Long-term, Systemic, Dermal Long-term, Systemic, Inhalation Long-term, Systemic, Oral Short-term, Local, Inhalation	206 mg/m3 1186 mg/kg bw/day 206 mg/m3 59.4 mg/kg bw/day 412 mg/m3	1.7 1.7 1.7 1.7 1.7	Repeated dose toxicity Repeated dose toxicity Repeated dose toxicity Repeated dose toxicity respiratory tract irritation
Short-term, Systemic, Inhalation	412 mg/m3	1.7	Neurotoxicity
Hydrocarbons, C6-C7, n-alkanes,isoalkanes,c	yclics,< 5% n-hexane (CAS E	C921-024-6)	
Long-term, Systemic, Dermal Long-term, Systemic, Inhalation Long-term, Systemic, Oral	699 mg/kg bw/day 608 mg/m3 699 mg/kg bw/day		
Hydrocarbons, C9-C11, n-alkanes, isoalkanes	, cyclics, < 2% aromatics (CA	S EC919-857-5)	
Long-term, Systemic, Dermal Long-term, Systemic, Inhalation Long-term, Systemic, Oral	300 mg/kg 900 mg/m3 300 mg/kg		
Orange, sweet, extract (CAS 8028-48-6)			
Long-term, Systemic, Dermal Long-term, Systemic, Inhalation	4.44 mg/kg bw/day 7.78 mg/m3	225 225	Repeated dose toxicity Repeated dose toxicity
<u>Workers</u>			
Components	Value	Assessment factor	Notes
Cyclohexane (CAS 110-82-7)			
Long-term, Local, Inhalation	700 mg/m3	1	Neurotoxicity
Long-term, Systemic, Dermal Long-term, Systemic, Inhalation	2016 mg/kg bw/day 700 mg/m3	1	Repeated dose toxicity Neurotoxicity

Material name: Label Off Super - Manufacturers

SDS GREAT BRITAIN

BDS002624AE Version #: 1.1 Revision date: 12-May-2022 Issue date: 24-March-2022

Short-term, Local, Inhalation 700 mg/m3 1 Neurotoxicity
Short-term, Systemic, Inhalation 700 mg/m3 1 Neurotoxicity

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane (CAS EC921-024-6)

Long-term, Systemic, Dermal 773 mg/kg bw/day Long-term, Systemic, Inhalation 2035 mg/m3

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics (CAS EC919-857-5)

Long-term, Systemic, Dermal 300 mg/kg Short-term, Systemic, Inhalation 1500 mg/m3

Orange, sweet, extract (CAS 8028-48-6)

Long-term, Systemic, Inhalation 31.1 mg/m3 112.5 Repeated dose toxicity Short-term, Local, Dermal 185.8 µg/cm² 30 Skin Sensitisation

Predicted no effect concentrations (PNECs)

Components	Value	Assessment factor Notes
Cyclohexane (CAS 110-82-7)		
Freshwater	0.207 mg/l	1
Sediment (freshwater)	3.627 mg/kg	1
Soil	2.99 mg/kg	1
STP	3.24 mg/l	1
Orange, sweet, extract (CAS 8028-48	8-6)	
Freshwater	5.4 µg/l	50
Sediment (freshwater)	1.3 mg/kg	
Soil	0.261 mg/kg	
STP	2.1 mg/l	10

8.2. Exposure controls

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

General information Use personal protective equipment as required. Personal protection equipment should be chosen

according to the CEN standards and in discussion with the supplier of the personal protective

equipment.

Eye/face protection Wear safety glasses with side shields (or goggles). Use eye protection conforming to EN 166.

Skin protection

- Hand protection When handling the product wear chemical-resistant gloves (standard EN 374). The breakthrough

time of the glove should be longer than the total duration of product use. If work lasts longer than

the breakthrough time, gloves should be changed part-way through. Nitrile gloves are

recommended. Suitable gloves can be recommended by the glove supplier.

- Other Wear appropriate chemical resistant clothing.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment. Chemical respirator with

organic vapour cartridge and full facepiece. (Filter type AX)

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

Hygiene measures When using do not smoke. Always observe good personal hygiene measures, such as washing

after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not

be allowed out of the workplace.

Environmental exposure

controls

Inform appropriate managerial or supervisory personnel of all environmental releases. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state Liquid.
Form Aerosol.

Colour Colourless to yellow.

Odour Citrus.
Odour threshold Not available.

pH Not applicable.

Material name: Label Off Super - Manufacturers

BDS002624AE Version #: 1.1 Revision date: 12-May-2022 Issue date: 24-March-2022

Melting point/freezing point -74 °C (-101.2 °F) estimated

Initial boiling point and boiling

range

Flash point < 0 °C (< 32.0 °F) **Evaporation rate** Not available. Not available. Flammability (solid, gas)

Upper/lower flammability or explosive limits Flammability limit - lower

0.6 % estimated

55 - 190

Flammability limit - upper

(%)

8.4 % estimated

Not available.

57300 hPa estimated Vapour pressure

0.75 g/cm3 at 20°C Relative density

Solubility(ies)

Vapour density

Insoluble in water Solubility (water) > 200 °C (> 392 °F) **Auto-ignition temperature** Not available. **Decomposition temperature** Not available. **Viscosity** Not explosive. **Explosive properties Oxidising properties** Not oxidising

9.2. Other information

VOC 718 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Material is stable under normal conditions. 10.2. Chemical stability

10.3. Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid Avoid high temperatures. Strong oxidising agents. 10.5. Incompatible materials

10.6. Hazardous

decomposition products

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

May cause drowsiness or dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be Inhalation

Carbon oxides.

Eye contact Direct contact with eyes may cause temporary irritation. Skin contact Causes skin irritation. May cause an allergic skin reaction.

Ingestion May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of

occupational exposure.

Symptoms May cause drowsiness or dizziness. Headache. Nausea, vomiting. Skin irritation. May cause

redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

11.1. Information on toxicological effects

Classification based on calculation method. Based on available data, the classification criteria are **Acute toxicity**

not met.

Components **Test Results Species**

Cyclohexane (CAS 110-82-7)

Acute

Dermal

LD50 Rabbit > 2000 mg/kg

Inhalation

LC50 Rat > 32.88 mg/l

Material name: Label Off Super - Manufacturers SDS GREAT BRITAIN

Test Results Components **Species** Oral LD50 Rat > 5000 mg/kg Hydrocarbons, C6-C7, n-alkanes,isoalkanes,cyclics,< 5% n-hexane **Dermal** LD50 Rat 2920 mg/kg bw/day, 24 h Inhalation LC50 Rat 25200 mg/m³, 4 h Oral LD50 Rat 5840 mg/kg bw/day Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics **Acute** Dermal LD50 Rabbit > 5000 mg/kg Oral LD50 Rat > 5000 mg/kg Orange, sweet, extract (CAS 8028-48-6) **Acute Dermal** LD50 Rabbit 5000 mg/kg bw/day Oral LD50 Rat > 2000 mg/kg/day Skin corrosion/irritation Causes skin irritation. Direct contact with eyes may cause temporary irritation. Serious eye damage/eye irritation Based on available data, the classification criteria are not met. Respiratory sensitisation Skin sensitisation May cause an allergic skin reaction. Germ cell mutagenicity Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. Specific target organ toxicity -May cause drowsiness or dizziness.

Carcinogenicity Reproductive toxicity

single exposure

Specific target organ toxicity -

repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard Not likely, due to the form of the product.

Mixture versus substance

information

Not available.

SECTION 12: Ecological information

12.1. Toxicity Very toxic to aquatic life with long lasting effects.

Components **Test Results Species** Cyclohexane (CAS 110-82-7) Aquatic Acute Algae EC50 3.4 mg/l, 72 hours Algae Crustacea EC50 Daphnia 0.9 mg/l, 48 hours Fish LC50 Fish 4.53 mg/l, 96 hours Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane Aquatic Acute Algae EC50 Algae > 30 - < 100 mg/l, 72 h Crustacea EC50 3 mg/l, 48 h Daphnia Fish LC50 Fish 11.4 mg/l, 96 h

Material name: Label Off Super - Manufacturers

SDS GREAT BRITAIN BDS002624AE Version #: 1.1 Revision date: 12-May-2022 Issue date: 24-March-2022

Components Species Test Results

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Acute

Other LC50 Pseudokirchnerella subcapitata > 1000 mg/l, 72 h

Aquatic

Acute

Fish LC50 Oncorhynchus mykiss > 1000 mg/l

12.2. Persistence and

degradability

No data is available on the degradability of any ingredients in the mixture.

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water (log Kow)

Cyclohexane 3.44

Bioconcentration factor (BCF) Not available.

12.4. Mobility in soil No data available.

12.5. Results of PBT and vPvB

assessment

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation

(EC) No 1907/2006, Annex XIII.

12.6. Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation

potential. GWP: 0

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

EU waste codeThe Waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Disposal methods/information Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international

regulations.

Special precautionsDispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADR

14.1. UN number UN1950

14.2. UN proper shipping AEROSOLS, flammable

name

14.3. Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

Hazard No. (ADR) Not available.

Tunnel restriction code D

14.4. Packing group Not available.

14.5. Environmental hazards yes

14.6. Special precautions

Read safety instructions, SDS and emergency procedures before handling.

for user

14.1. UN number UN1950

14.2. UN proper shipping AEROSOLS, flammable

name

14.3. Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

14.4. Packing group Not available.

14.5. Environmental hazards yes

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.

for user

ADN

14.1. UN number UN1950

14.2. UN proper shipping AEROSOLS, flammable

name

14.3. Transport hazard class(es)
Class 2.1
Subsidiary risk -

Label(s) 2.1

14.4. Packing group Not available.

14.5. Environmental hazards yes

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.

for user

IATA

14.1. UN number UN1950

14.2. UN proper shipping Aerosols, flammable

name

14.3. Transport hazard class(es)

Class 2.1 Subsidiary risk -

14.4. Packing group Not available.

14.5. Environmental hazards yes **ERG Code** 10L

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.

for user

Other information

Passenger and cargo Allowed with restrictions.

aircraft

Cargo aircraft only Allowed with restrictions.

IMDG

14.1. UN number UN1950

14.2. UN proper shipping Aerosols, flammable, MARINE POLLUTANT

Not established.

name

14.3. Transport hazard class(es)

Class 2.1 Subsidiary risk -

14.4. Packing group Not available.

14.5. Environmental hazards

Marine pollutant Yes
EmS F-D, S-U

14.6. Special precautions

for user

Read safety instructions, SDS and emergency procedures before handling.

14.7. Transport in bulk according to Annex II of

MARPOL 73/78 and the IBC

Code

ADN; ADR; IATA; IMDG; RID



Material name: Label Off Super - Manufacturers

BDS002624AE Version #: 1.1 Revision date: 12-May-2022 Issue date: 24-March-2022

Marine pollutant



SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture Retained direct EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended Not listed.

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Not listed

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended Carbon dioxide (CAS 124-38-9)

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA

Not listed

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended Cyclohexane (CAS 110-82-7)

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended Cyclohexane (CAS 110-82-7)

Other regulations

The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended.

This safety data sheet conforms to the following laws, regulations and standards:

Act on the management of packaging and packaging waste of June 13, 2013

Regulation of the Minister of Health of June 11, 2012 on the categories of dangerous substances and dangerous preparations whose packaging should be fitted with child-resistant closures and a tactile warning of danger

REGULATION OF THE MINISTER OF HEALTH of February 2, 2011 on tests and measurements of factors harmful to health in working environments

Regulation of Ministry of Labor and Social Policy of June 6, 2014. On the matter of maximum permissible concentrations and intensities of harmful factors in the work environment (Journal of Laws 2014, item. 817)

Chemical Safety at Workplace Ordinance Joint Decree No. 25/2000 (Annex 2): Permissible limit values of biological exposure (effect) indices Decree No. 25/2000. (IX. 30.) EüM-SzCsM of the Minister of Health and the Minister of Social and Family Affairs on chemical safety at work

Act No. 93 of 1993 on Labour Safety (1993.évi XCIII.), as amended

Government Decree No. 220 of 2004 (VII. 21.) providing rules on the protection of surface waters quality

Government Decree No. 98/2001 (VI. 15.), on the conditions of the activities related to hazardous waste, and Ministry of Environmental Affairs Decree No. 16/2001 (VII. 18.), on the register of wastes

Public Act No. XXV of 2000 on Chemical Safety, and Application Decree No. 44/2000. (XII.27.) EüM [of the Ministry of Health] Young people under 18 years old are not allowed to work with this product according to EU Directive 94/33/EC on the protection of young people at work, as amended

Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended.

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations

ADN: European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road. ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road.

ATE: Acute Toxicity Estimate according to REGULATION (EC) No 1272/2008 (CLP).

CAS: Chemical Abstract Service.

Ceiling: Short Term Exposure Limit Ceiling value.

CEN: European Committee for Standardization.

CLP: Classification, Labeling and Packaging REGULATION (EC) No 1272/2008 on classification,

labeling and packaging of substances and mixtures.

GWP: Global Warming Potential.

IATA: International Air Transport Association.

IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk.

IMDG: International Maritime Dangerous Goods.

MAK: Threshold limit values Germany (Maximale Arbeitsplatzkonzentration - DFG).

MARPOL: International Convention for the Prevention of Pollution from Ships.

PBT: Persistent, bioaccumulative and toxic.

REACH: Registration, Evaluation and Authorization of Chemicals (REGULATION (EC) No 1907/2006 concerning Registration, Evaluation Authorization and Restriction of Chemicals). RID: Regulations concerning the international carriage of dangerous goods by rail (Règlement International concernant le transport de marchandises dangereuses par chemin de fer). RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.

STEL: Short term exposure limit. TLV: Threshold Limit Value. TWA: Time Weighted Average.

VOC: Volatile organic compounds.

vPvB: Very persistent and very bioaccumulative.

STEL: Short-term Exposure Limit.

References

Information on evaluation method leading to the classification of mixture

Full text of any H-statements not written out in full under Sections 2 to 15

Not available.

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects.

Revision information

Training information

HazReg Data: Europe - EU

Follow training instructions when handling this material.

Disclaimer

CRC Industries Europe byba cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC.

Material name: Label Off Super - Manufacturers SDS GREAT BRITAIN

BDS002624AE Version #: 1.1 Revision date: 12-May-2022 Issue date: 24-March-2022