

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

| 1.1. Product identifier | |
|--|---|
| Trade name or designation of the mixture | Multi-Surface Citro CovKleen |
| Registration number | - |
| Synonyms | None. |
| Product code | BDS002616AE |
| Issue date | 17-June-2022 |
| Version number | 01 |
| 1.2. Relevant identified uses of t | he substance or mixture and uses advised against |
| Identified uses | Cleaners - Heavy duty Desinfectant |
| Uses advised against | None known. |
| 1.3. Details of the supplier of the | safety data sheet |
| Company name | CRC Industries Europe bv |
| Address | Touwslagerstraat 1 |
| | 9240 Zele |
| | Belgium |
| Telephone | +32(0)52/45.60.11 |
| Fax | +32(0)52/45.00.34 |
| E-mail | hse@crcind.com |
| Website | www.crcind.com |
| 1.4. Emergency telephone number | Tel.: +32(0)52/45.60.11 (office hours: 9-17h CET) |

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

| Physical hazards | | |
|--|-----------------------------|---|
| Aerosols | Category 1 | H222 - Extremely flammable aerosol. H229 - Pressurized container: May burst if heated. |
| Health hazards | | |
| Serious eye damage/eye irritation | Category 2 | H319 - Causes serious eye irritation. |
| Skin sensitisation | Category 1 | H317 - May cause an allergic skin reaction. |
| Specific target organ toxicity - single exposure | Category 3 narcotic effects | H336 - May cause drowsiness or dizziness. |
| Environmental hazards Hazardous to the aquatic environment, long-term aquatic hazard | Category 3 | H412 - Harmful to aquatic life with long lasting effects. |

2.2. Label elements

Contains:

_.

. . .

Label according to Regulation (EC) No. 1272/2008 as amended

Orange, sweet, extract, Propan-2-ol; Isopropyl alcohol; Isopropanol

Hazard pictograms

Hazard statements

Signal word

Danger

| H222 | Extremely flammable aerosol. |
|--------------------------------|--|
| H229 | Pressurized container: May burst if heated. |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H319 | Causes serious eye irritation. |
| H336 | May cause drowsiness or dizziness. |
| H412 | Harmful to aquatic life with long lasting effects. |
| Precautionary statements | |
| Prevention | |
| P102 | Keep out of reach of children. |
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P211 | Do not spray on an open flame or other ignition source. |
| P251 | Do not pierce or burn, even after use. |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection. |
| Response | Not assigned. |
| Storage | |
| P410 + P412 | Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. |
| Disposal | |
| P501 | Dispose of contents/container in accordance with local/regional/national/international regulations. |
| Supplemental label information | Regulation (EC) No 648/2004 on detergents: aliphatic hydrocarbons 5-15% perfumes: Limonene |
| 2.3. Other hazards | This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII. The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher. |

SECTION 3: Composition/information on ingredients

Mixture

General information

| Chemical name | % | CAS-No. / EC No. | REACH Registration No. | Index No. | Notes |
|--|---------------------|---|---------------------------------|--------------|-------|
| Propan-2-ol; Isopropyl alcohol; Isopropanol | 75 - 100 | 67-63-0 200-661-7 | 01-2119457558-25 | 603-117-00-0 | # |
| Classific | ation: Flam. Liq. 2 | 2;H225, Eye Irrit. 2;H | 319, STOT SE 3;H336 | | |
| Orange, sweet, extract | <25 | 8028-48-6 232-433-8 | 01-2119493353-35 | - | |
| Classific | • | ;H226, Skin Irrit. 2;F uatic Chronic 2;H41 | 1315, Skin Sens. 1;H317, A 1 | sp. Tox. | |
| Carbon dioxide | 1 - 5 | 124-38-9 204-696-9 | - | - | # |
| Classific | ation: Press. Gas | ;H280 | | | |
| ethanol; ethyl alcohol | 1 - 5 | 64-17-5 200-578-6 | 01-2119457610-43 | 603-002-00-5 | # |
| Classific | ation: Flam. Liq. 2 | 2;H225, Eye Irrit. 2;H | 319 | | |

List of abbreviations and symbols that may be used above

#: This substance has been assigned Union workplace exposure limit(s).

- ATE: Acute toxicity estimate.
- M: M-factor

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments

The full text for all H-statements is displayed in section 16.

SECTION 4: First aid measures

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

4.1. Description of first aid measures

| Inhalation | Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison centre or doctor/physician if you feel unwell. |
|--------------|---|
| Skin contact | Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse. |

Eye contact

Ingestion

4.2. Most important symptoms and effects, both acute and delayed

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

| SECTION 5. Thenghung in | ieasures |
|--|---|
| General fire hazards | Extremely flammable aerosol. |
| 5.1. Extinguishing media | |
| Suitable extinguishing media | Alcohol resistant foam. Powder. Carbon dioxide (CO2). |
| Unsuitable extinguishing media | Do not use water jet as an extinguisher, as this will spread the fire. |
| 5.2. Special hazards arising from the substance or mixture | Contents under pressure. Pressurised container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed. |
| 5.3. Advice for firefighters | |
| Special protective equipment for firefighters | Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. |
| Special fire fighting procedures | Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapour pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. |
| Specific methods | Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes. |

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

| · · · · · · · · · · · · · · · · · · · | |
|---|---|
| For non-emergency personnel | Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material. |
| For emergency responders | Keep unnecessary personnel away. Avoid breathing mist/vapours. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. Use personal protection recommended in Section 8 of the SDS. |
| 6.2. Environmental precautions | Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. |
| 6.3. Methods and material for containment and cleaning up | Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. This product is miscible in water. Prevent product from entering drains. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. |
| | Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. |
| 6.4. Reference to other sections | For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS. |
| SECTION 7: Handling and | storage |

SECTION 7: Handling and storage

| 7.1. Precautions for safe handling | Pressurised container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing mist/vapours. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices. |
|---|--|
| 7.2. Conditions for safe storage, including any incompatibilities | Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS). Storage class (TRGS 510): 2B (Aerosol dispensers and lighters) |
| 7.3. Specific end use(s) | Not available. |

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

In the unlikely event of swallowing contact a physician or poison control centre. Rinse mouth.

May cause drowsiness or dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

UK. EH40 Workplace Exposure Limits (WELs)

| Components | Туре | Value | |
|---|------|-------------|--|
| Carbon dioxide (CAS 124-38-9) | STEL | 27400 mg/m3 | |
| | | 15000 ppm | |
| | TWA | 9150 mg/m3 | |
| | | 5000 ppm | |
| ethanol; ethyl alcohol (CAS 64-17-5) | TWA | 1920 mg/m3 | |
| | | 1000 ppm | |
| Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0) | STEL | 1250 mg/m3 | |
| | | 500 ppm | |
| | TWA | 999 mg/m3 | |
| | | 400 ppm | |

Biological limit values No biological exposure limits noted for the ingredient(s).

Recommended monitoring

procedures

Follow standard monitoring procedures.

Derived no effect levels (DNELs)

| Components | Value | Assessment factor | Notes |
|---|-------------------|-------------------|------------------------------|
| ethanol; ethyl alcohol (CAS 64-17-5) | | | |
| Long-term, Systemic, Dermal | 206 mg/kg bw/day | 40 | Repeated dose toxicity |
| Long-term, Systemic, Oral | 87 mg/kg bw/day | 20 | Repeated dose toxicity |
| Short-term, Local, Inhalation | 950 mg/m3 | | respiratory tract irritation |
| Orange, sweet, extract (CAS 8028-48-6) | | | |
| Long-term, Systemic, Dermal | 4.44 mg/kg bw/day | 225 | Repeated dose toxicity |
| Long-term, Systemic, Inhalation | 7.78 mg/m3 | 225 | Repeated dose toxicity |
| Propan-2-ol; Isopropyl alcohol; Isopropanol | (CAS 67-63-0) | | |
| Long-term, Systemic, Dermal | 319 mg/kg bw/day | 2 | Repeated dose toxicity |
| Long-term, Systemic, Inhalation | 89 mg/m3 | 2 | Repeated dose toxicity |
| Long-term, Systemic, Oral | 26 mg/kg bw/day | 2 | Repeated dose toxicity |
| Workers | | | |
| Components | Value | Assessment factor | Notes |
| ethanol; ethyl alcohol (CAS 64-17-5) | | | |
| Long-term, Systemic, Dermal | 343 mg/kg bw/day | 24 | Repeated dose toxicity |
| Long-term, Systemic, Inhalation | 950 mg/m3 | | |
| Short-term, Local, Inhalation | 1900 mg/m3 | | respiratory tract irritation |
| Orange, sweet, extract (CAS 8028-48-6) | | | |
| Long-term, Systemic, Inhalation | 31.1 mg/m3 | 112.5 | Repeated dose toxicity |
| Short-term, Local, Dermal | 185.8 µg/cm² | 30 | Skin Sensitisation |
| Propan-2-ol; Isopropyl alcohol; Isopropanol | (CAS 67-63-0) | | |
| Long-term, Systemic, Dermal | 888 mg/kg bw/day | 1 | |
| Long-term, Systemic, Inhalation | 500 mg/m3 | 1 | |
| dicted no effect concentrations (PNECs) | | | |
| Components | Value | Assessment factor | Notes |
| ethanol; ethyl alcohol (CAS 64-17-5) | | | |
| Freshwater | 0.96 mg/l | 10 | |
| Sediment (marine water) | 2.9 mg/kg | | |
| Soil | 0.63 mg/kg | 1000 | |
| Orange, sweet, extract (CAS 8028-48-6) | | | |
| Freshwater | 5.4 µg/l | 50 | |
| Sediment (freshwater) | 1.3 mg/kg | | |
| Soil | 0.261 mg/kg | | |

Material name: Multi-Surface Citro CovKleen - Manufacturers BDS002616AE Version #: 01 Issue date: 17-June-2022

| STP | 2.1 mg/l | 10 | | | |
|---|--|-----------|------|--|--|
| Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0) | | | | | |
| Freshwater | 140.9 mg/l | 1 | | | |
| Secondary poisoning | 160 mg/kg | 30 | Oral | | |
| Sediment (freshwater) | 552 mg/kg | | | | |
| Soil | 28 mg/kg | | | | |
| 8.2. Exposure controls | | | | | |
| Appropriate engineering controls | Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower. | | | | |
| Individual protection measures, | , such as personal protective equipm | nent | | | |
| General information | Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment. | | | | |
| Eye/face protection | Wear safety glasses with side shields (or goggles). Use eye protection conforming to EN 166. | | | | |
| Skin protection | | | | | |
| - Hand protection | When handling the product wear chemical-resistant gloves (standard EN 374). The breakthrough time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be changed part-way through. Full contact: Glove material: nitrile. Use gloves with breakthrough time of 480 minutes. Minimum glove thickness 0.38 mm. | | | | |
| - Other | Wear appropriate chemical resistant | clothing. | | | |
| Respiratory protection | In case of insufficient ventilation, wear suitable respiratory equipment. Chemical respirator with organic vapour cartridge and full facepiece. (Filter type A) | | | | |
| Thermal hazards | Wear appropriate thermal protective clothing, when necessary. | | | | |
| Hygiene measures | When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace. | | | | |
| Environmental exposure controls | Inform appropriate managerial or supervisory personnel of all environmental releases. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to acceptable levels. | | | | |

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| Appearance | |
|---|---------------------------------|
| Physical state | Liquid. |
| Form | Aerosol. |
| Colour | Colourless. |
| Odour | Citrus. |
| Odour threshold | Not available. |
| рН | Not applicable. |
| Melting point/freezing point | -114.1 °C (-173.4 °F) estimated |
| Initial boiling point and boiling range | 78 °C (172.4 °F) estimated |
| Flash point | 12.0 °C (53.6 °F) Closed cup |
| Evaporation rate | Not available. |
| Flammability (solid, gas) | Not available. |
| Upper/lower flammability or expl | losive limits |
| Flammability limit - lower (%) | 0.7 % estimated |
| Flammability limit - upper (%) | 12 % estimated |
| Vapour pressure | Not available. |
| Vapour density | Not available. |
| Relative density | 0.8 g/cm3 at 20°C |

| Solubility(ies) | |
|---------------------------|---------------------|
| Solubility (water) | Soluble in water |
| Auto-ignition temperature | > 200 °C (> 392 °F) |
| Decomposition temperature | Not available. |
| Viscosity | Not available. |
| Explosive properties | Not explosive. |
| Oxidising properties | Not oxidising. |
| 9.2. Other information | |
| VOC | 780 g/l |
| | |

SECTION 10: Stability and reactivity

| 10.1. Reactivity | The product is stable and non-reactive under normal conditions of use, storage and transport. |
|---|---|
| 10.2. Chemical stability | Material is stable under normal conditions. |
| 10.3. Possibility of hazardous reactions | No dangerous reaction known under conditions of normal use. |
| 10.4. Conditions to avoid | Avoid high temperatures. |
| 10.5. Incompatible materials | Acids. Strong oxidising agents. Chlorine. Isocyanates. |
| 10.6. Hazardous decomposition products | Carbon oxides. |

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

| Inhalation | May cause drowsiness or dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful. |
|--------------|--|
| Eye contact | Causes serious eye irritation. |
| Skin contact | Causes skin irritation. May cause an allergic skin reaction. |
| Ingestion | May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure. |
| Symptoms | May cause drowsiness or dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash. |

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

| / louio louiony | | | |
|-----------------------------------|--------------------------------|-------------------------|--|
| Components | Species | Test Results | |
| ethanol; ethyl alcohol (CAS 64- | 17-5) | | |
| Acute | | | |
| Dermal | | | |
| LD50 | Rabbit | > 15800 mg/kg | |
| Inhalation | | | |
| LC50 | Rat | 116.8 - 133.8 mg/l, 4 h | |
| Oral | | | |
| LD50 | Rat | 10470 mg/kg | |
| Orange, sweet, extract (CAS 80 | 028-48-6) | | |
| <u>Acute</u> | | | |
| Dermal | | | |
| LD50 | Rabbit | 5000 mg/kg bw/day | |
| Oral | | | |
| LD50 | Rat | > 2000 mg/kg/day | |
| Propan-2-ol; Isopropyl alcohol; | Isopropanol (CAS 67-63-0) | | |
| <u>Acute</u> | | | |
| Inhalation | | | |
| LC50 | Rat | > 25000 mg/m3, 6 h | |
| Skin corrosion/irritation | Causes skin irritation. | | |
| Serious eye damage/eye irritation | Causes serious eye irritation. | | |

| Respiratory sensitisation | Based on available data, the classification criteria are not met. |
|--|---|
| Skin sensitisation | May cause an allergic skin reaction. |
| Germ cell mutagenicity | Based on available data, the classification criteria are not met. |
| Carcinogenicity | Based on available data, the classification criteria are not met. |
| Reproductive toxicity | Based on available data, the classification criteria are not met. |
| Specific target organ toxicity - single exposure | May cause drowsiness or dizziness. |
| Specific target organ toxicity - repeated exposure | Based on available data, the classification criteria are not met. |
| Aspiration hazard | Based on available data, the classification criteria are not met. |
| Mixture versus substance information | Not available. |

SECTION 12: Ecological information

| 12.1. Toxicity | Harmful to | o aquatic life with long lasting effects. | |
|---|-----------------------------------|---|------------------------------|
| Components | | Species | Test Results |
| ethanol; ethyl alcohol (CAS 64- | 17-5) | | |
| Acute | | | |
| | EC50 | Selenastrum capricornutum (new name Pseudokirchneriella subcapitata) | > 100 mg/l, 48 hours |
| Aquatic | | | |
| Acute | | | |
| Crustacea | EC50 | Daphnia magna | 12340 mg/l, 48 hours |
| Fish | LC50 | Leuciscus idus | > 100 mg/l, 48 hours |
| | | Oncorhynchus mykiss | 13000 mg/l, 96 hours |
| | | Oryzias latipes | 12000 - 16000 mg/l, 96 hours |
| | | Pimephales promelas | 14200 mg/l, 96 hours |
| Chronic | | | |
| Crustacea | NOEC | Daphnia magna | 9.6 mg/l, 9 days |
| ropan-2-ol; Isopropyl alcohol; I | sopropanol (C | AS 67-63-0) | |
| Aquatic | | | |
| Acute | | | |
| Crustacea | LC50 | Brine shrimp (Artemia salina) | > 10000 mg/l, 24 hours |
| Fish | LC50 | Bluegill (Lepomis macrochirus) | > 1400 mg/l, 96 hours |
| 2.2. Persistence and egradability | No data is | s available on the degradability of any ingredie | nts in the mixture. |
| 2.3. Bioaccumulative potenti | al | | |
| Partition coefficient -octanol/water (log Kow) | | | |
| ethanol; ethyl alcohol | | -0.31 | |
| Propan-2-ol; Isopropyl alco | | | |
| ioconcentration factor (BCF) | | | |
| 2.4. Mobility in soil | No data a | | |
| 2.5. Results of PBT and vPvB ssessment | | This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII. | |
| 2.6. Other adverse effects | The produ potential. GWP: 0 | | |
| SECTION 13: Disposal c | onsideratio | ons | |
| 3.1 Waste treatment method | e | | |

13.1. Waste treatment methods

| Residual waste | Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). |
|------------------------|--|
| Contaminated packaging | Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. |

EU waste code The Waste code should be assigned in discussion between the user, the producer and the waste disposal company. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents **Disposal methods/information** under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations. Dispose in accordance with all applicable regulations. **Special precautions SECTION 14: Transport information** ADR 14.1. UN number UN1950 AEROSOLS, flammable 14.2. UN proper shipping name 14.3. Transport hazard class(es) 2.1 Class Subsidiary risk 2.1 Label(s) Hazard No. (ADR) Not available. **Tunnel restriction code** D 14.4. Packing group Not available. 14.5. Environmental hazards No 14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling. for user RID 14.1. UN number UN1950 AEROSOLS, flammable 14.2. UN proper shipping name 14.3. Transport hazard class(es) 2.1 Class Subsidiary risk Label(s) 2.1 14.4. Packing group Not available. 14.5. Environmental hazards No. Read safety instructions, SDS and emergency procedures before handling. 14.6. Special precautions for user ADN UN1950 14.1. UN number 14.2. UN proper shipping AEROSOLS, flammable name 14.3. Transport hazard class(es) Class 2.1 Subsidiary risk 2.1 Label(s) Not available. 14.4. Packing group 14.5. Environmental hazards No. 14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling. for user ΙΑΤΑ 14.1. UN number UN1950 Aerosols, flammable 14.2. UN proper shipping name 14.3. Transport hazard class(es) 21 Class Subsidiary risk Not available. 14.4. Packing group 14.5. Environmental hazards No **ERG Code** 101 14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling. for user Other information Allowed with restrictions. Passenger and cargo aircraft Cargo aircraft only Allowed with restrictions. IMDG 14.1. UN number UN1950

| 14.2. UN proper shipping name | Aerosols, flammable |
|---|---|
| 14.3. Transport hazard class | (es) |
| Class | 2.1 |
| Subsidiary risk | - |
| 14.4. Packing group | Not available. |
| 14.5. Environmental hazards | |
| Marine pollutant | No |
| EmS | F-D, S-U |
| 14.6. Special precautions | Read safety instructions, SDS and emergency procedures before handling. |
| for user | |
| 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code | Not established. |
| ADN; ADR; IATA; IMDG; RID | |



SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Retained direct EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended Not listed.

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended Carbon dioxide (CAS 124-38-9)

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended ethanol; ethyl alcohol (CAS 64-17-5)

Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

ethanol; ethyl alcohol (CAS 64-17-5)

Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)

Other regulations

The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended.

Young people under 18 years old are not allowed to work with this product according to EU Directive 94/33/EC on the protection of young people at work, as amended Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended.

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations

| List of appreviations | |
|---|---|
| | ADN: European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways. |
| | ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road. |
| | ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road. AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert – Germany). |
| | ATE: Acute Toxicity Estimate according to REGULATION (EC) No 1272/2008 (CLP). |
| | CAS: Chemical Abstract Service. |
| | Ceiling: Short Term Exposure Limit Ceiling value. |
| | CEN: European Committee for Standardization. |
| | CLP: Classification, Labeling and Packaging REGULATION (EC) No 1272/2008 on classification, |
| | labeling and packaging of substances and mixtures. |
| | GWP: Global Warming Potential. |
| | IATA: International Air Transport Association. |
| | IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk. |
| | IMDG: International Maritime Dangerous Goods. |
| | MAC: Maximum Allowed Concentration. MAK: Threshold limit values Germany (Maximale Arbeitsplatzkonzentration - DFG). |
| | MARPOL: International Convention for the Prevention of Pollution from Ships. |
| | PBT: Persistent, bioaccumulative and toxic. |
| | REACH: Registration, Evaluation and Authorization of Chemicals (REGULATION (EC) No 1907/2006 concerning Registration, Evaluation Authorization and Restriction of Chemicals). RID: Regulations concerning the international carriage of dangerous goods by rail (Règlement |
| | International concernant le transport de marchandises dangereuses par chemin de fer). |
| | RID: Regulations concerning the International Carriage of Dangerous Goods by Rail. |
| | STEL: Short term exposure limit. |
| | TLV: Threshold Limit Value. |
| | TWA: Time Weighted Average. |
| | VLE: Exposure Limit Value. |
| | VME: Exposure Average Value. |
| | VOC: Volatile organic compounds. |
| | vPvB: Very persistent and very bioaccumulative. STEL: Short-term Exposure Limit. |
| References | Not available. |
| Information on evaluation method leading to the classification of mixture | The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available. |
| Full text of any H-statements not written out in full under | |
| Sections 2 to 15 | H225 Highly flammable liquid and vapour. |
| | H226 Flammable liquid and vapour. |
| | H280 Contains gas under pressure; may explode if heated. |
| | H304 May be fatal if swallowed and enters airways. |
| | H315 Causes skin irritation. |
| | H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. |
| | H336 May cause drowsiness or dizziness. |
| | H411 Toxic to aquatic life with long lasting effects. |
| Revision information | None. |
| Training information | Follow training instructions when handling this material. |
| Disclaimer | CRC Industries Europe byba cannot anticipate all conditions under which this information and its |
| | product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC. |
| | |