SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

SILICONE SPRAY Trade name or designation

of the mixture

Registration number

Synonyms None.

Product code BDS000414AE 16-June-2022 Issue date

1.0 Version number

16-June-2022 **Revision date**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Lubricants Uses advised against None known. 1.3. Details of the supplier of the safety data sheet

Company name CRC Industries Europe by

Address Touwslagerstraat 1

> 9240 Zele Belgium

Telephone +32(0)52/45.60.11 Fax +32(0)52/45.00.34 hse@crcind.com E-mail Website www.crcind.com

Tel.: +32(0)52/45.60.11 (office hours: 9-17h CET) 1.4. Emergency telephone

number

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards

Aerosols Category 1 H222 - Extremely flammable

aerosol.

H229 - Pressurized container: May

burst if heated.

Health hazards

Skin corrosion/irritation H315 - Causes skin irritation. Category 2

Specific target organ toxicity - single Category 3 narcotic effects H336 - May cause drowsiness or

exposure dizziness.

Environmental hazards

Hazardous to the aquatic environment, Category 2 H411 - Toxic to aquatic life with

long-term aquatic hazard long lasting effects.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane, Hydrocarbons, C7, Contains:

n-alkanes, isoalkanes, cyclic

Hazard pictograms



Signal word Danger

Hazard statements

Extremely flammable aerosol. H222

Pressurized container: May burst if heated. H229

Causes skin irritation. H315

May cause drowsiness or dizziness. H336

Toxic to aquatic life with long lasting effects. H411

Precautionary statements

Prevention

Keep out of reach of children. P102

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P210

Do not spray on an open flame or other ignition source. P211

Do not pierce or burn, even after use. P251

Avoid breathing mist/vapours. P261

Use only outdoors or in a well-ventilated area. P271

Response Not assigned.

Storage

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. P410 + P412

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations. P501

Supplemental label information

None.

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation 2.3. Other hazards

(EC) No 1907/2006, Annex XIII. The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or

Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

Mixture

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No	. Index No.	Notes
Hydrocarbons, C6-C7, n-alkanes,isoalkanes,cyclics,< 5% n-hexane	25 - 50	- 921-024-6	01-2119475514-35	-	
Classification		2;H225, Skin Irrit. 2;F quatic Chronic 2;H41	1315, STOT SE 3;H336, As 1	sp. Tox.	
Hydrocarbons, C7, n-alkanes,isoalkanes, cyclic	25 - 50	- 927-510-4	01-2119475515-33	649-328-00-1	
Classification		2;H225, Skin Irrit. 2;F quatic Chronic 2;H41	1315, STOT SE 3;H336, As 1	sp. Tox.	
Carbon dioxide	1 - 5	124-38-9 204-696-9	-	-	#
Classification	n: Press. Ga	s:H280			

List of abbreviations and symbols that may be used above

#: This substance has been assigned Union workplace exposure limit(s).

ATE: Acute toxicity estimate.

M: M-factor

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

The full text for all H-statements is displayed in section 16. **Composition comments**

SECTION 4: First aid measures

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves.

4.1. Description of first aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison

centre or doctor/physician if you feel unwell.

Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get Skin contact

medical advice/attention. Wash contaminated clothing before reuse.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

In the unlikely event of swallowing contact a physician or poison control centre. Rinse mouth. Ingestion 4.2. Most important symptoms

and effects, both acute and

delayed

May cause drowsiness or dizziness. Headache. Nausea, vomiting. Skin irritation. May cause redness and pain.

4.3. Indication of any immediate medical attention and special treatment needed Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards

Extremely flammable aerosol.

5.1. Extinguishing media

Suitable extinguishing

media

Unsuitable extinguishing

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

5.2. Special hazards arising

Do not use water jet as an extinguisher, as this will spread the fire.

from the substance or mixture

Contents under pressure. Pressurised container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Special protective equipment for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Special fire fighting procedures

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapour pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material.

For emergency responders

Keep unnecessary personnel away. Avoid breathing mist/vapours. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

6.2. Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up

Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. The product is immiscible with water and will spread on the water surface. Prevent product from entering drains. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

6.4. Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Pressurised container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing mist/vapours. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS). Storage class (TRGS 510): 2B (Aerosol dispensers and lighters)

7.3. Specific end use(s)

Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

UK. EH40 Workplace Exposure Limits (WELs)

Components	Туре	Value	
Carbon dioxide (CAS 124-38-9)	STEL	27400 mg/m3	
		15000 ppm	
	TWA	9150 mg/m3	
		5000 ppm	

Biological limit values

No biological exposure limits noted for the ingredient(s).

699 mg/kg bw/day

Recommended monitoring

procedures

Follow standard monitoring procedures.

Derived no effect levels (DNELs)

Long-term, Systemic, Oral

General Population

Components	Value		Notes				
Hydrocarbons, C6-C7, n-alkanes,isoalkanes,cyclics,< 5% n-hexane (CAS -)							
Long-term, Systemic, Dermal	699 mg/kg bw/day						
Long-term, Systemic, Inhalation	608 mg/m3						

Workers

Components Value Assessment factor Notes

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane (CAS -)

Long-term, Systemic, Dermal 773 mg/kg bw/day Long-term, Systemic, Inhalation 2035 mg/m3

Predicted no effect concentrations (PNECs)

Not available.

8.2. Exposure controls

Appropriate engineering

controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

General information Use personal protective equipment as required. Personal protection equipment should be chosen

according to the CEN standards and in discussion with the supplier of the personal protective

equipment.

Eye/face protection Wear safety glasses with side shields (or goggles). Use eye protection conforming to EN 166.

Skin protection

- Hand protection When handling the product wear chemical-resistant gloves (standard EN 374). The breakthrough

time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be changed part-way through. Suitable gloves can be

recommended by the glove supplier.

- Other Wear appropriate chemical resistant clothing.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment. Chemical respirator with

organic vapour cartridge and full facepiece. (Filter type AX)

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

Hygiene measures When using do not smoke. Always observe good personal hygiene measures, such as washing

after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

Environmental exposure

controls

Inform appropriate managerial or supervisory personnel of all environmental releases. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to acceptable

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

levels.

Appearance

Physical state Liquid.

Form Aerosol.

Colour Colourless.

Odour Solvent. **Odour threshold** Not available. Not applicable.

Melting point/freezing point -56.6 °C (-69.9 °F) estimated 60 - 100 °C (140 - 212 °F) Initial boiling point and boiling

range

-26.0 °C (-14.8 °F) Closed cup Flash point

Not available. **Evaporation rate** Not available. Flammability (solid, gas) Upper/lower flammability or explosive limits

Flammability limit - lower

8 % estimated

Flammability limit - upper

(%)

0.9 % estimated

Not available. Vapour pressure > 3 at 20°C Vapour density

Relative density 0.72 g/cm3 at 20°C

Solubility(ies)

Insoluble in water Solubility (water) > 200 °C (> 392 °F) **Auto-ignition temperature Decomposition temperature** Not available. Not available. Viscosity **Explosive properties** Not explosive. Oxidising properties Not oxidising

9.2. Other information

645 g/l VOC

SECTION 10: Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. 10.1. Reactivity

Material is stable under normal conditions. 10.2. Chemical stability

10.3. Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid Avoid high temperatures. 10.5. Incompatible materials Strong oxidising agents.

10.6. Hazardous

Carbon oxides.

decomposition products

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

May cause drowsiness or dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be Inhalation

harmful.

Eye contact Direct contact with eyes may cause temporary irritation.

Skin contact Causes skin irritation.

Ingestion May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of

occupational exposure.

Symptoms May cause drowsiness or dizziness. Headache. Nausea, vomiting. Skin irritation. May cause

redness and pain.

11.1. Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met.

Components **Species Test Results**

Hydrocarbons, C6-C7, n-alkanes,isoalkanes,cyclics,< 5% n-hexane

Acute Dermal

2920 mg/kg bw/day, 24 h LD50 Rat

Test Results Components **Species** Inhalation LC50 Rat 25200 mg/m3, 4 h Oral LD50 5840 mg/kg bw/day Rat Hydrocarbons, C7, n-alkanes, isoalkanes, cyclic Acute Dermal LD50 Rat 2920 mg/kg Inhalation LC50 Rat 23.3 mg/l Oral LD50 Rat 5840 mg/kg Skin corrosion/irritation Causes skin irritation. Serious eye damage/eye Direct contact with eyes may cause temporary irritation.

irritation

Respiratory sensitisation Based on available data, the classification criteria are not met. Skin sensitisation Based on available data, the classification criteria are not met. Germ cell mutagenicity Based on available data, the classification criteria are not met. Carcinogenicity Based on available data, the classification criteria are not met. Reproductive toxicity Based on available data, the classification criteria are not met.

Specific target organ toxicity -

single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity -

repeated exposure

Based on available data, the classification criteria are not met.

Not likely, due to the form of the product. **Aspiration hazard**

Mixture versus substance

information

Not available.

SECTION 12: Ecological information

12.1. Toxicity Toxic to aquatic life with long lasting effects.

Test Results Components **Species**

Hydrocarbons, C6-C7, n-alkanes,isoalkanes,cyclics,< 5% n-hexane

Aquatic

Acute

> 30 - < 100 mg/l, 72 hAlgae EC50 Algae

Crustacea EC50 Daphnia 3 mg/l, 48 h Fish LC50 Fish 11.4 mg/l, 96 h

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclic

Aquatic

Acute

Crustacea EC50 Daphnia 3 mg/l, 48 hours Fish LC50 Fish > 13.4 mg/l, 96 hours

Chronic

Crustacea **NOEC** Daphnia 0.17 mg/l, 21 days

12.2. Persistence and

degradability

No data is available on the degradability of any ingredients in the mixture.

12.3. Bioaccumulative potential No data available.

Partition coefficient

Not available.

n-octanol/water (log Kow)

Bioconcentration factor (BCF) Not available. No data available. 12.4. Mobility in soil

12.5. Results of PBT and vPvB

assessment

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation

(EC) No 1907/2006, Annex XIII.

The product contains volatile organic compounds which have a photochemical ozone creation 12.6. Other adverse effects

potential. GWP: 0

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

The Waste code should be assigned in discussion between the user, the producer and the waste EU waste code

disposal company.

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents Disposal methods/information

under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international

regulations.

Special precautions Dispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADR

14.1. UN number UN1950 **AEROSOLS** 14.2. UN proper shipping

name

14.3. Transport hazard class(es)

Class 2.1 Subsidiary risk 2.1 Label(s)

Not available. Hazard No. (ADR)

Tunnel restriction code D

Not available. 14.4. Packing group

14.5. Environmental hazards Yes

Read safety instructions, SDS and emergency procedures before handling. 14.6. Special precautions

for user

14.1. UN number UN1950

14.2. UN proper shipping **AEROSOLS**

name

RID

14.3. Transport hazard class(es)

Class Subsidiary risk Label(s) 2 1

14.4. Packing group Not available.

14.5. Environmental hazards Yes

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.

for user

ADN

14.1. UN number UN1950 **AEROSOLS** 14.2. UN proper shipping

14.3. Transport hazard class(es)

2.1 Class Subsidiary risk 2.1 Label(s)

Not available. 14.4. Packing group

14.5. Environmental hazards

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.

for user

IATA

14.1. UN number UN1950 **AEROSOLS** 14.2. UN proper shipping

14.3. Transport hazard class(es) Class

Material name: SILICONE SPRAY - Manufacturers

BDS000414AE Version #: 1.0 Revision date: 16-June-2022 Issue date: 16-June-2022

SDS GREAT BRITAIN

Subsidiary risk

Not available. 14.4. Packing group

14.5. Environmental hazards Yes **ERG Code** 10L

14.6. Special precautions

for user

Read safety instructions, SDS and emergency procedures before handling.

Passenger and cargo

aircraft

Allowed with restrictions.

Other information

Allowed with restrictions. Cargo aircraft only

IMDG

UN1950 14.1. UN number

14.2. UN proper shipping AEROSOLS, MARINE POLLUTANT

Not established.

14.3. Transport hazard class(es) 2.1 Class Subsidiary risk

Not available. 14.4. Packing group

14.5. Environmental hazards

Marine pollutant Yes F-D, S-U **EmS**

14.6. Special precautions

for user

Read safety instructions, SDS and emergency procedures before handling.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC

Code

ADN; ADR; IATA; IMDG; RID



Marine pollutant



SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture **Retained direct EU regulations**

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Carbon dioxide (CAS 124-38-9)

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended Not listed

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

Not listed

Other regulations

The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended.

Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended.

15.2. Chemical safety

No Chemical Safety Assessment has been carried out.

assessment

SECTION 16: Other information

List of abbreviations

ADN: European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road. ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road.

AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert – Germany).

ATE: Acute Toxicity Estimate according to REGULATION (EC) No 1272/2008 (CLP).

CAS: Chemical Abstract Service.

Ceiling: Short Term Exposure Limit Ceiling value.

CEN: European Committee for Standardization.

CLP: Classification, Labeling and Packaging REGULATION (EC) No 1272/2008 on classification, labeling and packaging of substances and mixtures.

GWP: Global Warming Potential.

IATA: International Air Transport Association.

IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk.

IMDG: International Maritime Dangerous Goods.

MAC: Maximum Allowed Concentration.

MAK: Threshold limit values Germany (Maximale Arbeitsplatzkonzentration - DFG).

MARPOL: International Convention for the Prevention of Pollution from Ships.

PBT: Persistent, bioaccumulative and toxic.

REACH: Registration, Evaluation and Authorization of Chemicals (REGULATION (EC) No 1907/2006 concerning Registration, Evaluation Authorization and Restriction of Chemicals). RID: Regulations concerning the international carriage of dangerous goods by rail (Règlement

International concernant le transport de marchandises dangereuses par chemin de fer). RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.

STEL: Short term exposure limit. TLV: Threshold Limit Value.

TWA: Time Weighted Average. VLE: Exposure Limit Value.

VME: Exposure Average Value. VOC: Volatile organic compounds.

vPvB: Very persistent and very bioaccumulative.

STEL: Short-term Exposure Limit.

References

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

Full text of any H-statements not written out in full under Sections 2 to 15

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

Material name: SILICONE SPRAY - Manufacturers

SDS GREAT BRITAIN

Not available

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Revision information Training information

Disclaimer

nic.

Follow training instructions when handling this material.

CRC Industries Europe byba cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC.

Material name: SILICONE SPRAY - Manufacturers