

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier Trade name or designation of the mixture	Silicone Grease
Registration number	-
Synonyms	None.
Product code	BDS000487AE
Issue date	20-June-2022
Version number	1.0
Revision date	20-June-2022
1.2. Relevant identified uses of t	he substance or mixture and uses advised against
Identified uses	Lubricants
Uses advised against	None known.
1.3. Details of the supplier of the	safety data sheet
Company name	CRC Industries Europe bv
Address	Touwslagerstraat 1
	9240 Zele
	Belgium
Telephone	+32(0)52/45.60.11
Fax	+32(0)52/45.00.34
E-mail	hse@crcind.com
Website	www.crcind.com
1.4. Emergency telephone number	Tel.: +32(0)52/45.60.11 (office hours: 9-17h CET)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards			
Aerosols		Category 1	H222 - Extremely flammable
			aerosol. H229 - Pressurized container: May burst if heated.
Health hazards			
Skin corrosion/irritation		Category 2	H315 - Causes skin irritation.
Specific target organ toxic exposure	tity - single	Category 3 narcotic effects	H336 - May cause drowsiness or dizziness.
Environmental hazards			
Hazardous to the aquatic long-term aquatic hazard	environment,	Category 2	H411 - Toxic to aquatic life with long lasting effects.
2.2. Label elements			
Label according to Regulation (E	EC) No. 1272/2008	as amended	
Contains:		6-C7, n-alkanes,isoalkanes,cyclics,< 5% n-h ,isoalkanes,< 5% n-hexane, Pentane	iexane,
Hazard pictograms			
Signal word	Danger		
Hazard statements			
H222	Extremely flamma	able aerosol.	
H229	Pressurized conta	ainer: May burst if heated.	

H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
Precautionary statements	
Prevention	
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P261	Avoid breathing mist/vapours.
P271	Use only outdoors or in a well-ventilated area.
Response	Not assigned.
Storage	
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Disposal	
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
Supplemental label information	None.
2.3. Other hazards	This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII. The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

Mixture

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
hydrocarbons,C6,isoalkanes,< 5% n-hexane	% 25 - 50	- 931-254-9	01-2119484651-34	649-328-00-1	
Classifica		2;H225, Skin Irrit. 2;H quatic Chronic 2;H41	H315, STOT SE 3;H336, As 1	р. Тох.	
Pentane	25 - 50	109-66-0 203-692-4	01-2119459286-30	601-006-00-1	#
Classifica	tion: Flam. Liq. Chronic 2;		H336, Asp. Tox. 1;H304, A	quatic	
Hydrocarbons, C6-C7, n-alkanes,isoalkanes,cyclics,< 5%	10 - 25 %	- 921-024-6	01-2119475514-35	-	
n-hexane		2;H225, Skin Irrit. 2;F quatic Chronic 2;H41	H315, STOT SE 3;H336, As 1	р. Тох.	
n-hexane				р. Тох. -	#

List of abbreviations and symbols that may be used above

#: This substance has been assigned Union workplace exposure limit(s).

- ATE: Acute toxicity estimate.
- M: M-factor

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments

The full text for all H-statements is displayed in section 16.

SECTION 4: First aid measures

General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.				
4.1. Description of first aid meas	4.1. Description of first aid measures				
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison centre or doctor/physician if you feel unwell.				
Skin contact	Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.				
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.				
Ingestion	In the unlikely event of swallowing contact a physician or poison control centre. Rinse mouth.				

Material name: Silicone Grease - Manufacturers

BDS000487AE Version #: 1.0 Revision date: 20-June-2022 Issue date: 20-June-2022

4.2. Most important symptoms and effects, both acute and delayed	May cause drowsiness or dizziness. Headache. Nausea, vomiting. Skin irritation. May cause redness and pain.
4.3. Indication of any immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards	Extremely flammable aerosol.
5.1. Extinguishing media Suitable extinguishing media	Foam. Powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
5.2. Special hazards arising from the substance or mixture	Contents under pressure. Pressurised container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
5.3. Advice for firefighters Special protective equipment for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Special fire fighting procedures	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapour pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material.
For emergency responders	Keep unnecessary personnel away. Avoid breathing mist/vapours. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
6.2. Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.
6.3. Methods and material for containment and cleaning up	Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. The product is immiscible with water and will spread on the water surface. Prevent entry into waterways, sewer, basements or confined areas. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
6.4. Reference to other sections	For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling	Pressurised container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing mist/vapours. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.
7.2. Conditions for safe storage, including any incompatibilities	Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS). Storage class (TRGS 510): 2B (Aerosol dispensers and lighters)
7.3. Specific end use(s)	Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Components	ure Limits (WE	Туре	Value	
Carbon dioxide (CAS		STEL	27400 mg/m3	
124-38-9)			J	
			15000 ppm	
		TWA	9150 mg/m3	
			5000 ppm	
Pentane (CAS 109-66-0)		TWA	1800 mg/m3	
			600 ppm	
ological limit values	-	exposure limits noted for th	ne ingredient(s).	
commended monitoring ocedures		ard monitoring procedures.		
rived no effect levels (DNELs) General Population				
Components		Value	Assessment factor	Notes
Hydrocarbons, C6-C7, n-alkar	nes.isoalkanes.			110100
Long-term, Systemic, Der		699 mg/kg bw/day	,	
Long-term, Systemic, Inha		608 mg/m3		
Long-term, Systemic, Ora		699 mg/kg bw/day		
hydrocarbons,C6,isoalkanes, Long-term, Systemic, Der		(CAS -) 1377 mg/kg bw/day		
Long-term, Systemic, Inh		1131 mg/kg bw/day		
Long-term, Systemic, Ora	l	1301 mg/kg bw/day		
Pentane (CAS 109-66-0)				
Long-term, Systemic, Der Long-term, Systemic, Inh		214 mg/kg bw/day 643 mg/m3	5 5	Repeated dose toxicity Repeated dose toxicity
<u>Workers</u> Components		Value	Assessment factor	Notes
Hydrocarbons, C6-C7, n-alkar	nes isoalkanes			Notes
Long-term, Systemic, Der Long-term, Systemic, Inha	mal	773 mg/kg bw/day 2035 mg/m3	0-)	
hydrocarbons,C6,isoalkanes,<		(CAS -)		
Long-term, Systemic, Der Long-term, Systemic, Inh		13964 mg/kg bw/day 5306 mg/m3		
Pentane (CAS 109-66-0)				
Long-term, Systemic, Der Long-term, Systemic, Inh		432 mg/kg bw/day 3000 mg/m3	3 3	Repeated dose toxicity Repeated dose toxicity
edicted no effect concentratio	ns (PNECs)			
Components		Value	Assessment factor	Notes
Pentane (CAS 109-66-0)				
Freshwater Sediment (freshwater)		230 μg/l 1.2 mg/kg	1 1	
Soil		0.55 mg/kg	1	
2. Exposure controls				
opropriate engineering ontrols	applicable, us maintain airb	se process enclosures, loca orne levels below recomme	al exhaust ventilation, or ot ended exposure limits. If ex	be matched to conditions. If her engineering controls to sposure limits have not been le eyewash station and safety
dividual protection measures, General information	Use personal according to		equired. Personal protectio	n equipment should be chose r of the personal protective
Eye/face protection	equipment. Wear safety (nlasses with side shields (o	r anaales). Lise eve protec	tion conforming to EN 166.
	Theat Salety		, 3033,007. 000 0yo pioleo	
Skin protection	\A/bon h====!!!	a the product wear abarris	al registert deuce (star-d-	and EN 271. The baselitheress
- Hand protection	time of the gl the breakthro	ove should be longer than t ugh time, gloves should be	he total duration of produc changed part-way through	rtd EN 374). The breakthroug t use. If work lasts longer tha n. Full contact: Glove materia n glove thickness 0.38 mm.

- Other	Wear appropriate chemical resistant clothing.
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment. Chemical respirator with organic vapour cartridge and full facepiece. (Filter type AX)
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
Hygiene measures	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.
Environmental exposure controls	Inform appropriate managerial or supervisory personnel of all environmental releases. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	
------------	--

• •			
Physical state	Liquid.		
Form	Aerosol.		
Colour	Colourless.		
Odour	Solvent.		
Odour threshold	Not available.		
рН	Not applicable.		
Melting point/freezing point	-129.7 °C (-201.5 °F) estimated		
Initial boiling point and boiling range	36 °C (96.8 °F) estimated		
Flash point	-45.0 °C (-49.0 °F) Closed cup		
Evaporation rate	Not available.		
Flammability (solid, gas)	Not available.		
Upper/lower flammability or explosive limits			
Flammability limit - lower (%)	1 % estimated		
Flammability limit - upper (%)	7.8 % estimated		
Vapour pressure	57300 hPa estimated		
Vapour density	Not available.		
Relative density	0.72 g/cm3 at 20°C		
Solubility(ies)			
Solubility (water)	Insoluble in water		
Auto-ignition temperature	> 200 °C (> 392 °F)		
Decomposition temperature	Not available.		
Viscosity	Not available.		
Explosive properties	Not explosive.		
Oxidising properties	Not oxidising.		
9.2. Other information			
Density	0.75 g/cm3 estimated		
Heat of combustion	12.79 kJ/g estimated		
VOC	564 g/l		

SECTION 10: Stability and reactivity

10.1. Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
10.2. Chemical stability	Material is stable under normal conditions.
10.3. Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
10.4. Conditions to avoid	Avoid high temperatures.
10.5. Incompatible materials	Strong oxidising agents.
10.6. Hazardous decomposition products	Carbon oxides.

SECTION 11: Toxicologica	al information			
General information	Occupational exposure to the substance or mixture may cause adverse effects.			
Information on likely routes of e	exposure			
Inhalation	May cause drowsiness or dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.			
Eye contact	Direct contact with eyes may cause temporary irritat	ion.		
Skin contact	Causes skin irritation.	Causes skin irritation.		
Ingestion	May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.			
Symptoms	May cause drowsiness or dizziness. Headache. Nausea, vomiting. Skin irritation. May cause redness and pain.			
11.1. Information on toxicologic	al effects			
Acute toxicity	Based on available data, the classification criteria ar	e not met.		
Components	Species	Test Results		
Hydrocarbons, C6-C7, n-alkanes,i	soalkanes,cyclics,< 5% n-hexane			
Acute				
Dermal	_			
LD50	Rat	2920 mg/kg bw/day, 24 h		
Inhalation				
LC50	Rat	25200 mg/m³, 4 h		
Oral LD50	Rat	5840 mg/kg bw/day		
hydrocarbons,C6,isoalkanes,< 5%		3040 mg/kg bw/day		
Acute				
Dermal				
LD50	Rabbit	3350 mg/kg, 4 h		
Inhalation				
LD50	Rat	259354 mg/m3		
Oral				
LD50	Rat	16750 mg/kg		
Pentane (CAS 109-66-0)				
Acute				
Dermal LD50	Rabbit	> 3000 mg/kg		
Inhalation	Kabat	2 3000 mg/kg		
LC50	Rat	364 mg/l, 4 Hours		
Oral				
LD50	Rat	> 5000 mg/kg		
Skin corrosion/irritation	Causes skin irritation.			
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.			
Respiratory sensitisation	Based on available data, the classification criteria are not met.			
Skin sensitisation	Based on available data, the classification criteria are not met.			
Germ cell mutagenicity	Based on available data, the classification criteria are not met.			
Carcinogenicity	Based on available data, the classification criteria are not met.			
Reproductive toxicity	Based on available data, the classification criteria are not met.			
Specific target organ toxicity - single exposure	May cause drowsiness or dizziness.			

Specific target organ toxicity -Based on available data, the classification criteria are not met. repeated exposure Not likely, due to the form of the product. Aspiration hazard Not available.

Mixture versus substance information

SECTION 12: Ecological information

12.1. Toxicity	Toxic to a	quatic life with long lasting effects.		
Components		Species	Test Results	
Hydrocarbons, C6-C7, n-alkan	es,isoalkanes,c	yclics,< 5% n-hexane		
Aquatic				
Acute				
Algae	EC50	Algae	> 30 - < 100 mg/l, 72 h	
Crustacea	EC50	Daphnia	3 mg/l, 48 h	
Fish	LC50	Fish	11.4 mg/l, 96 h	
ydrocarbons,C6,isoalkanes,<	5% n-hexane			
Acute				
Other	EC50	Pseudokirchnerella subcapitata	13.6 mg/l, 72 hours	
	NOEC	Pseudokirchnerella subcapitata	3 mg/l, 72 hours	
Aquatic				
Acute				
Crustacea	EC50	Daphnia magna	31.9 mg/l, 48 hours	
	NOEC	Daphnia magna	7.14 mg/l, 21 days	
Fish	EC50	Rainbow trout	18.3 mg/l, 96 hours	
	NOEC	Rainbow trout	4.09 mg/l, 28 days	
12.2. Persistence and degradability	No data is	available on the degradability of any ingre	edients in the mixture.	
12.3. Bioaccumulative poten	tial			
Partition coefficient n-octanol/water (log Kow) Pentane		3.39		
Bioconcentration factor (BC	F) Not availa	Not available.		
12.4. Mobility in soil	-	No data available.		
12.5. Results of PBT and vPv assessment		This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII.		
12.6. Other adverse effects	The produ potential. GWP: 2			

SECTION 13: Disposal considerations

13.1. Waste treatment methods	
Residual waste	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.
EU waste code	The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Disposal methods/information	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Special precautions	Dispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADR

14.1. UN number 14.2. UN proper shipping name	UN1950 AEROSOLS, flammable		
14.3. Transport hazard class(es)			
Class	2.1		
Subsidiary risk	-		
Label(s)	2.1		

Hazard No. (ADR) Not available. **Tunnel restriction code** D 14.4. Packing group Not available. 14.5. Environmental hazards Yes 14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling. for user RID 14.1. UN number UN1950 AEROSOLS. flammable 14.2. UN proper shipping name 14.3. Transport hazard class(es) Class 2.1 Subsidiary risk 2.1 Label(s) Not available. 14.4. Packing group 14.5. Environmental hazards Yes 14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling. for user ADN 14.1. UN number UN1950 14.2. UN proper shipping AEROSOLS, flammable name 14.3. Transport hazard class(es) Class 2.1 Subsidiary risk _ 2.1 Label(s) 14.4. Packing group Not available. 14.5. Environmental hazards Yes Read safety instructions, SDS and emergency procedures before handling. 14.6. Special precautions for user IATA UN1950 14.1. UN number 14.2. UN proper shipping Aerosols, flammable name 14.3. Transport hazard class(es) 2.1 Class Subsidiary risk Not available. 14.4. Packing group 14.5. Environmental hazards Yes **ERG Code** 101 14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling. for user Other information Allowed with restrictions. Passenger and cargo aircraft Allowed with restrictions. Cargo aircraft only IMDG UN1950 14.1. UN number 14.2. UN proper shipping Aerosols, flammable, MARINE POLLUTANT name 14.3. Transport hazard class(es) Class 2.1 Subsidiary risk Not available. 14.4. Packing group 14.5. Environmental hazards Marine pollutant Yes EmS F-D, S-U Read safety instructions, SDS and emergency procedures before handling. 14.6. Special precautions for user Not established. 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

ADN; ADR; IATA; IMDG; RID



Marine pollutant



General information

IMDG Regulated Marine Pollutant.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Retained direct EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended Not listed.

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended Carbon dioxide (CAS 124-38-9)

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended Not listed.

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

Pentane (CAS 109-66-0)

Other regulations

The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended.

Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended.

15.2. Chemical safety No Chemical Safety Assessment has been carried out.

assessment

SECTION 16: Other information

List of abbreviations

ADN: European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways. ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road. ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road. AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert - Germany). ATE: Acute Toxicity Estimate according to REGULATION (EC) No 1272/2008 (CLP). CAS: Chemical Abstract Service. Ceiling: Short Term Exposure Limit Ceiling value. CEN: European Committee for Standardization. CLP: Classification, Labeling and Packaging REGULATION (EC) No 1272/2008 on classification, labeling and packaging of substances and mixtures. GWP: Global Warming Potential. IATA: International Air Transport Association. IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk. IMDG: International Maritime Dangerous Goods. MAC: Maximum Allowed Concentration. MAK: Threshold limit values Germany (Maximale Arbeitsplatzkonzentration - DFG). MARPOL: International Convention for the Prevention of Pollution from Ships. PBT: Persistent. bioaccumulative and toxic. REACH: Registration, Evaluation and Authorization of Chemicals (REGULATION (EC) No 1907/2006 concerning Registration, Evaluation Authorization and Restriction of Chemicals). RID: Regulations concerning the international carriage of dangerous goods by rail (Règlement International concernant le transport de marchandises dangereuses par chemin de fer). RID: Regulations concerning the International Carriage of Dangerous Goods by Rail. STEL: Short term exposure limit. TLV: Threshold Limit Value. TWA: Time Weighted Average. VLE: Exposure Limit Value. VME: Exposure Average Value. VOC: Volatile organic compounds. vPvB: Very persistent and very bioaccumulative. STEL: Short-term Exposure Limit. Not available. The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available. H225 Highly flammable liquid and vapour. H280 Contains gas under pressure; may explode if heated. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects. None Follow training instructions when handling this material. CRC Industries Europe byba cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The

information in the sheet was written based on the best knowledge and experience currently available. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without

References

Information on evaluation method leading to the classification of mixture

Full text of any H-statements not written out in full under Sections 2 to 15

Revision information Training information Disclaimer

written permission from CRC.