#### English



#### **Important Notes**

- Quick-Switch® Tool Transfer Stations are suitable only for hand tools weighing 2.72 kg (6 lbs) or less, used on Quick-Switch® tool tether products only.
- This product is intended for use by personnel who are trained and knowledgeable regarding working with hand tools at height and/or near machinery.
- Quick-Switch® Tool Transfer Stations should only be attached to hand rails/railings with manufacturer's intended specifications that would support the impact forces of a drop.
- Only attach to hand rails/railings where the top and mid rail spacing allows for a form fitting installation where hook and loop and retention clips are fully engaged.
- Inspect before each use for damage and proper function:
  - Check all hardware for abrasion, deformity, cuts and sharp edges.
  - Check for tears, cuts, fraying, abrasion, discoloration, burns, holes, mold, unsplicing, pulled or broken stitches, or other signs of wear or damage.
  - Do not use and always quarantine if any of the above apply or if damaged or not functioning correctly.

#### **Safety Information**

- ▲ WARNING! Do not use near moving parts, mechanisms, running machinery or rotating equipment.
- May contain electrically conductive materials.
- ▲ Do not alter product in any way from its original state.

### **Applicable Safety Standards**

Meets or exceeds:

ANSI / ISEA 121-2018

#### **Materials**

Nylon, nickel-plated steel, and stainless steel.

#### **Product Weight**

1.6 lbs (0.73kg)

# Maintenance, Cleaning, and Storage

Clean with a damp cloth and mild soap, wipe off excess and thoroughly dry.

Store this product away from tools and other objects that could cause damage.

#### English

# GUARDIAN

Step 4

Adjust all hooks and loops as necessary to ensure a secure fit.

### Installation

#### Step 1

Place the Quick-Switch® Tool Transfer Station over the top of the handrail and temporarily attach the top hook and loop straps on the back.



#### Step 2

Connect the two carabiners to the small D-ring as shown below.



Step 3

Attach the bottom hook and



loop straps.



## Carry Handle

Comes with a carrying handle which allows the Quick-Switch® Tool Transfer Station to convert to a carrying case.

### **Specifications**

### Quick-Switch® Tool Transfer Station\*

Part #	Max. Tool Weight /	Max. Tool Weight /	Max. Tether	Dimensions
	Quick-Switch® Dock	side D-ring	Length	Length x Width
42145	2.72 kg (6 lbs)	2.72 kg (6 lbs)	122 cm (48")	81.3x45.7 cm (32"x18")