

# Fieldbus System (For Input/Output)



IP67

## Supports digital inputs/outputs, analogue inputs/outputs, and IO-Link units

**New**

An **IO-Link** unit compatible SI unit has been added (PROFINET).



### <Compatible Protocols>



DeviceNet

CC-Link

IO-Link

EtherNet/IP

EtherCAT

Made to order



CC-Link IE Field

Please contact SMC for details on compatible products.

### IO-Link unit

- 2 models (port class A and port class B)
  - Master/device diagnosis function
  - The data can be accessed from via PC (setting tool).
  - Device parameter setting function, Automatic saving/writing
- \* For the integrated SI unit, only PROFINET or EtherNet/IP™ can be selected.  
\* PROFINET: Up to 9 IO-Link unit modules can be connected.  
\* EtherNet/IP™: Up to 4 IO-Link unit modules can be connected. (Made to order)




### Self-diagnosis function

Equipped with an input/output open/short-circuit detection function and an input/output signal ON/OFF counter function

### Web server function<sup>\*1</sup>

Status checks and forced output are possible via web browser.

\* Parameter setting is only for EtherNet/IP™.



### Various connectors available

The following connectors are selectable for the input/output devices: M12 connectors, M8 connectors, D-sub connectors, and spring type terminal blocks.


### Up to 9 units<sup>\*1</sup> can be connected.

Up to 9 units can be connected in any order.


\*1 Excludes SI units

## EX600 Series


# Can be connected with digital, analogue and IO-Link Units



For detailed specifications of connectable devices, refer to the catalogue of each device and select the right device for your application. If anything is unclear, please contact SMC.



## IO-Link Unit / Port Class A Devices



## IO-Link Unit / Port Class B Device



## ■ Connectable Solenoid Valve Series

Series	Flow rate characteristics (4/2 → 5/3)		Q [l/min (ANR)]*4	Max. number of solenoids	Power consumption [W]	Applicable cylinder size
	C [dm <sup>3</sup> /(s-bar)]	b				
IP67 *1	CE cULus	SY3000	1.6	0.19	381	Ø 50 Ø 63 Ø 80
		SY5000	3.6	0.17	848	
		SY7000	5.9	0.20	1413	
IP67 *1, *3	CE cULus	JSY1000	0.91	0.48	263	Ø 40 Ø 50 Ø 80
		JSY3000	2.77	0.27	691	
		JSY5000	6.59	0.22	1597	
IP40	CE cULus	S0700*2	0.37	0.39	100	Ø 25
IP67 *1	CE cULus	SV1000*2	1.1	0.35	289	Ø 40 Ø 63 Ø 80
		SV2000*2	2.4	0.18	568	
		SV3000*2	4.3	0.21	1036	
IP67 *1	CE cULus	VQC1000	1.0	0.30	254	Ø 40 Ø 63 Ø 160 Ø 180
		VQC2000	3.2	0.30	814	
		VQC4000	7.3	0.38	1958	
		VQC5000	17	0.31	4350	

\*1 Units with a D-sub communication connector are IP40.

\*2 There is no manifold part number setting for the EX600-SPN3/4. (Order it separately.)

\*3 The JSY1000 is IP40.

\*4 These values have been calculated according to ISO 6358 and indicate the flow rate under standard conditions with an inlet pressure of 0.6 MPa (relative pressure) and a pressure drop of 0.1 MPa.

# IO-Link

IO-Link is a communication technology for sensors and actuators that is an international standard, IEC 61131-9.

This technology is used to send/receive device information such as manufacturer, product part number, parameters, and diagnostic data, as well as the control data including ON/OFF signals and measured values of the sensor, by connecting the IO-Link unit and sensor in a 1:1 configuration.

IO-Link enables condition monitoring and error detection of the sensor and equipment, and it can contribute to the reduction of startup labour and recovery time and the realisation of preventive and predictive maintenance.

## Reduced design and startup labour


- Batch setting of device parameters from the upper level
- Remote check of device information
- Detection and remote unified check of device misconnection/non-connection

## Minimum recovery time due to error detection


- Early detection of location where problem is occurring via communication
- Early obtaining of information on problem phenomenon via communication
- Early recovery during product replacement (automatic setting of device parameters)

## Preventive and predictive maintenance through condition monitoring

- Monitors changes in measured values of a sensor during signal ON/OFF
- Monitors the number of device operations and automatically notifies when the set number of operations has been exceeded
- Remote monitoring of device and equipment conditions via communication



## IO-Link System Configuration



### ① IO-Link unit

- Acts as a gateway between the IO-Link communication and the upper level communication

### ② IO-Link device

- A sensor/actuator connecting to an IO-Link unit in a 1:1 configuration

### ③ IODD file

- A file in which device properties and parameters are described
- Registered to the setting tool
- Provided by the device manufacturer

### ④ Communication cable

- A 4-wire or 5-wire general-purpose cable that is the same as the existing sensor cable (Unshielded cable)
- Max. cable length: 20 m


### ⑤ IO-Link setting tool software

- Software for the setting and monitoring of a master/device
- Provided by the master manufacturer\*

\*1 A setting tool compatible with the masters of every manufacturer is used for the SMC EX600 series IO-Link unit.  
(IO-Link Device Tool V5 manufactured by TMG Technologie und Engineering, Germany)


## IO-Link Interface

The connecting part between the IO-Link unit and the device is called a “port.” Each port can be switched between “IO-Link mode” for digital communication and “standard I/O mode” for conventional contact input/output.




### 2 types of interfaces

There are two methods for power supply: one is for sensors, and the other is for actuators.



Port class A

The control power supply wire and signal wire can be connected with one cable. (Mainly for sensors)



Port class B

The control power supply wire, external power supply wire, and signal wire can be connected with one cable. (Mainly for actuators)


## IO-Link Unit

### ■ Can be connected with digital, analogue, and IO-Link units


PROFINET: Up to **9** IO-Link units can be connected. (Total of 36 ports)

EtherNet/IP®: Up to **4** IO-Link units can be connected. (Total of 16 ports)

Digital units, analogue units, and IO-Link units can be mixed, and up to 9 units can be connected in any order.




### ■ Supports both port class A and port class B



For connecting IO-Link sensors  
Pressure sensors, flow sensors,  
actuator position sensors,  
electro-pneumatic regulators, etc.

For connecting IO-Link compatible  
SI units (for valve driving)

### ■ The data can be accessed from via PC (setting tool).



The setting and monitoring of the master and device are possible via PC, without using the PLC.

- Process data
- Device parameters, Master parameters
- Master information, Device information
- Port diagnosis, Device diagnosis


\* The PC setting tool is an IO-Link device tool manufactured by Technologie Management Gruppe (hereinafter referred to as TMG). It can be downloaded for free from the TMG website, however, for usage beyond 30 days, a license key is required.

## ■ Diagnosis function

Diagnosis on a master and device is possible from the upper level communication.

Master (port) diagnostic information can be obtained via PLC program or PC (web browser).

Device diagnostic information can be obtained via PC (setting tool).




Items of master (port) diagnosis
Detection of port short-circuit
Detection of non-connected device
Detection of misconnected device (check error)
Notification of port misconfiguration (excessively large input/output data)
Conditions of diagnostic event (port, device)
Items of device diagnosis
Diagnostic results (problem phenomenon) received from devices are shown in event codes.

## ■ Device parameter setting function, Automatic saving/writing

The parameter setting of devices is possible from the upper level communication.

Parameter setting is possible via PC (setting tool).

It is also possible to use output data or message data via PLC program.




## EtherNet Fieldbus Functions

PROFINET (EX600-SPN3/4) and EtherNet/IP™ (EX600-SEN3/4) support the following functions.


### Compatible topologies (Connection configuration)

The EX600-SEN3/4 and EX600-SPN3/4 support **star**, **linear**, and **ring** network topologies.

Linear type




Ring type




For ring networks, communication can be continued even if one of the communication cables in the network is disconnected or damaged. As the EX600-SEN3/4 supports Device Level Ring (DLR), and the EX600-SPN3/4 supports Media Redundancy Protocol (MRP), the disconnected point can be identified.

\* In order to use DLR or MRP, the PLC must be able to support it.

Normal flow of data



Data flow when the communication cable is disconnected



## ■ Supports the QuickConnect™ function and the Fast Start Up function

Time from power ON to communication connection


10 s

Approx.  
0.5 s

In the case of a tool changer, it takes about 10 seconds for communication to be connected in some products after the power to the device installed on the tool is turned ON.

As the EX600-SEN3/4 supports the QuickConnect™ function, and the EX600-SPN3/4 supports the Fast Start Up function, communication connection in only approx. 0.5 s is possible.


\* In order to use the QuickConnect™ function or the Fast Start Up function, the PLC must be able to support it.



## ■ Built-in web server function

The EX600-SEN3/4 and EX600-SPN3/4 have a built-in web server function, which enables status checks, parameter settings (EX600-SEN3/4 only), and forced output of the EX600 using general-purpose web browsers, such as Microsoft Edge.

Start-up of the system and maintenance can be performed efficiently.




## ■ Latest PROFINET Technology

### ■ System Redundancy S2

As the EX600-SPN3/4 supports System Redundancy S2, it can continue communication using the backup controller when the primary controller malfunctions. This allows for the prevention of problems caused by unexpected communication interruption.

\* In order to use System Redundancy S2, the PLC must be able to support this function.



# Fieldbus System EX600

## D-sub connector

IP40


These units are capable of connection using a D-sub connector. There are three types of units: for digital input, output, and input/output. The digital output unit can be connected with an SMC manifold solenoid valve F kit (D-sub connector).

**Manifold solenoid valves can be connected using a cable with a D-sub connector.**

- SY series      • S0700 series      • SJ series      • SQ series
- SV series      • VQC series      • VQ series      • JSY series

\* Please limit the number of valve connections to 16 stations for single and 8 stations for double. Refer to the catalogue of each product for pin assignment details.


VVZS3000-21A-□-X192 (Non-waterproof cable example)



## Spring type terminal block

IP40


These terminal block units are compatible with individual wiring configurations. There are three types of units: for digital input, output, and input/output. Wiring connection to a sensor connector box, etc., can be carried out easily using only a flat head screwdriver.



## Digital input unit

IP67


This unit is for inputting a digital signal (ON/OFF signal). The signal of a 2-wire/3-wire auto switch attached to the actuator can be acquired to feedback a signal to the PLC. The control signal of an entire system can be managed by a Fieldbus system.



## Analogue input/output unit

IP67

These units are for inputting or outputting an analogue signal (voltage/current). A single unit performs both input and output, allowing feedback control where analogue signals are received from a pressure sensor and sent to a pressure controller. Installation space is minimised as well.



## Self-diagnosis function

The following shows examples of the self-diagnosis function.

### Short/Open-circuit detection

It is possible to detect short or open circuits of input devices such as electronic 2-wire switches and 3-wire switches and output devices such as solenoid valves. The location of the error can be identified by the indicator light and the network.



Green ON Normal



Red ON Short circuit



Red flashing Open circuit

### Counter function

It is possible to ascertain the maintenance period and identify the parts that require maintenance by an input and output signal ON/OFF counter function. When the counter function is enabled and a certain number of contact operations is reached, the display of the counter will flash in red.

\* The counter function is not provided with analogue units.


## ■ Individual units can be connected and removed one by one.

A unique clamping method is adopted to prevent screws from falling out.

Units can be separated easily by loosening the joint bracket.

Up to 9 units can be connected in any order.



\* Excludes SI units



# CONTENTS

## Type 3 Integrated input-output type

### Fieldbus System (For Input/Output) EX600 Series



#### Parts Structure ..... p. 12

#### How to Order

SI Unit .....	p. 12
Digital Input Unit .....	p. 13
Digital Output Unit .....	p. 13
Digital Input/Output Unit .....	p. 13
Analogue Input Unit .....	p. 13
Analogue Output Unit .....	p. 13
Analogue Input/Output Unit .....	p. 14
IO-Link Unit .....	p. 14
End Plate (D side) .....	p. 14
Handheld Terminal .....	p. 14

#### Specifications

All Units Common .....	p. 15
SI Unit .....	p. 15
Digital Input Unit .....	p. 18
Digital Output Unit .....	p. 19
Digital Input/Output Unit .....	p. 19
Analogue Input Unit .....	p. 20
Analogue Output Unit .....	p. 20
Analogue Input/Output Unit .....	p. 21
IO-Link Unit .....	p. 22
End Plate .....	p. 22
Handheld Terminal .....	p. 22

#### Dimensions ..... p. 23

#### Parts Description ..... p. 29

#### LED Indicator ..... p. 31

#### Accessories

① End Plate Bracket .....	p. 35
② Valve Plate .....	p. 35
③ End Plate (U side) .....	p. 36
④ Reinforcing Brace .....	p. 36
⑤ Seal Cap (10 pcs.) .....	p. 36
⑥ Marker (1 sheet, 88 pcs.) .....	p. 36
⑦ Power Supply Cable (7/8 inch connector) .....	p. 37
⑧ Power Supply Field-wireable Connector (7/8 inch) .....	p. 37
⑨ Power Supply Cable (M12 connector, For EX600-ED2) .....	p. 37
⑩ Power Supply Cable (M12 connector, For EX600-ED4/5) .....	p. 38
⑪ Communication Cable .....	p. 39
⑫ Field-wireable Communication Connector .....	p. 44
⑬ I/O Cable with Connector, I/O Connector .....	p. 45

#### Made to Order

① Ethernet POWERLINK compatible .....	p. 46
② Modbus/TCP compatible .....	p. 46
③ CC-Link IE Field compatible .....	p. 46
Communication Cable .....	p. 47


#### Specific Product Precautions .....

p. 48

# Fieldbus System For Input/Output **EX600 Series**



## Parts Structure




\*1 The photo shows the analogue input unit.

## How to Order

### SI Unit

**EX600-S PR1A-**

#### Specifications



Symbol	Protocol	Output type	Note
<b>PR1A</b>	PROFIBUS DP	PNP (Negative common)	—
<b>PR2A</b>		NPN (Positive common)	—
<b>DN1A</b>	DeviceNet®	PNP (Negative common)	—
<b>DN2A</b>		NPN (Positive common)	—
<b>MJ1</b>	CC-Link	PNP (Negative common)	—
<b>MJ2</b>		NPN (Positive common)	—
<b>CF1-X60</b>	CC-Link IE Field	PNP (Negative common)	(Made to order)
<b>EN1</b>	EtherNet/IP®	PNP (Negative common)	1 port
<b>EN2</b>		NPN (Positive common)	1 port
<b>EN3</b>		PNP (Negative common)	2 ports
<b>EN4</b>		NPN (Positive common)	2 ports
<b>EN3-X80</b>		PNP (Negative common)	IO-Link unit (Made to order)
<b>EC1</b>	EtherCAT	PNP (Negative common)	—
<b>EC2</b>		NPN (Positive common)	—
<b>PN1</b>	PROFINET	PNP (Negative common)	—
<b>PN2</b>		NPN (Positive common)	—
<b>PN3</b>		PNP (Negative common)	IO-Link unit
<b>PN4</b>		NPN (Positive common)	IO-Link unit


● Made to order  
(Refer to page 46.)

Ethernet POWERLINK
Modbus TCP
CC-Link IE Field
NPN (Positive common)

# EX600 Series

## How to Order

### Digital Input Unit



**EX600-DX P D**


#### Input type

Symbol	Description
P	PNP
N	NPN

#### Number of inputs, open-circuit detection, and connector

Symbol	Number of inputs	Open-circuit detection	Connector
B	8 inputs	No	M12 connector (5 pins) 4 pcs.
C	8 inputs	No	M8 connector (3 pins) 8 pcs.
C1	8 inputs	Yes	M8 connector (3 pins) 8 pcs.
D	16 inputs	No	M12 connector (5 pins) 8 pcs.
E	16 inputs	No	D-sub connector (25 pins)
F	16 inputs	No	Spring type terminal block (32 pins)

### Digital Output Unit



**EX600-DY P B**


#### Output type

Symbol	Description
P	PNP
N	NPN

#### Number of outputs and connector

Symbol	Number of outputs	Connector
B	8 outputs	M12 connector (5 pins) 4 pcs.
E	16 outputs	D-sub connector (25 pins)
F	16 outputs	Spring type terminal block (32 pins)

### Digital Input/Output Unit



**EX600-DM P F**


#### Input/Output type

Symbol	Description
P	PNP
N	NPN

#### Number of inputs/outputs and connector

Symbol	Number of inputs	Number of outputs	Connector
E	8 inputs	8 outputs	D-sub connector (25 pins)
F	8 inputs	8 outputs	Spring type terminal block (32 pins)

### Analogue Input Unit




**EX600-AX A**

#### Analogue input

#### Number of input channels and connector

Symbol	Number of input channels	Connector
A	2 channels	M12 connector (5 pins) 2 pcs.

### Analogue Output Unit



**EX600-AY A**

#### Analogue output


#### Number of output channels and connector

Symbol	Number of output channels	Connector
A	2 channels	M12 connector (5 pins) 2 pcs.

## How to Order

### Analogue Input/Output Unit

### **EX600-AM B**




Analogue input/output

• Number of input/output channels and connector

Symbol	Number of input channels	Number of output channels	Connector
<b>B</b>	2 channels	2 channels	M12 connector (5 pins) 4 pcs.

### IO-Link Unit

### **EX600-L A B 1**



Port specification

Symbol	Description
<b>A</b>	Port class A
<b>B</b>	Port class B

• Number of ports and connector

Symbol	Number of ports	Connector
<b>B</b>	4 ports	M12 connector (5 pins) 4 pcs.


#### ⚠ Caution

The only available SI unit part numbers are "EX600-SEN3-X80" (EtherNet/IP® compatible) and "EX600-SPN3/4" (PROFINET compatible). Refer to page 12.

### End Plate (D side)

### **EX600-ED 2 - 2**

EX600-ED4/5 are not yet UL-compliant.



For M12

For 7/8 inch

End plate

End plate mounting position: D side

Power supply connector

Symbol	Power supply connector	Specifications
<b>2</b>	M12 (5 pins) B-coded	IN
<b>3</b>	7/8 inch (5 pins)	IN
<b>4</b>	M12 (4/5 pins) A-coded*1	IN/OUT
<b>5</b>	M12 (4/5 pins) A-coded*1	IN/OUT

• Mounting method

Symbol	Description	Note
—	Without DIN rail mounting bracket	—
<b>2</b>	With DIN rail mounting bracket	For SV, S0700, and VQC series
<b>3</b>	With DIN rail mounting bracket	For SY and JSY series

\* When the end plate (U side) is used, the symbol for the mounting method must be the same as the D side.

\*1 The pin layout for the "4" and "5" pin connectors is different.  
Refer to the dimensions on page 24.

### Handheld Terminal


### **EX600-HT1A - 3**

Handheld terminals are not yet UL-compliant.

Version

• Cable length

Symbol	Description
—	No cable
<b>1</b>	1 m
<b>3</b>	3 m



# EX600 Series

## Specifications

### All Units Common Specifications

<b>Environment</b>	<b>Operating temperature range</b>	Operating: -10 to 50 °C, Stored: -20 to 60 °C
	<b>Operating humidity range</b>	35 to 85 % RH (No condensation)
	<b>Withstand voltage*1</b>	500 VAC for 1 minute between external terminals and FE
	<b>Insulation resistance*1</b>	500 VDC, 10 MΩ or more between external terminals and FE

\*1 Except handheld terminals

### SI Unit (EX600-SPR□A)

Model	EX600-SPR1A	EX600-SPR2A
<b>Communication</b>	<b>Protocol</b>	PROFIBUS DP (DP-V0)
	<b>Device type</b>	PROFIBUS DP Slave
	<b>Communication speed</b>	9.6/19.2/45.45/93.75/187.5/500 kbps 1.5/3/6/12 Mbps
	<b>Configuration file</b>	GSD file*2
	<b>Occupation area (Number of inputs/outputs)</b>	Max. (512 inputs/512 outputs)
	<b>Terminating resistor</b>	Internally implemented
	<b>Internal current consumption (Power supply for Control/Input)</b>	80 mA or less
	<b>Output type</b>	Source/PNP (Negative common) Sink/NPN (Positive common)
	<b>Number of outputs</b>	32 outputs (8/16/24/32 outputs selectable)
	<b>Load</b>	Solenoid valve with surge voltage suppressor 24 VDC, 1.5 W or less (SMC)
<b>Output</b>	<b>Power supply</b>	24 VDC, 2 A
	<b>Fail safe</b>	HOLD/CLEAR/Forced power ON
	<b>Protection</b>	Short-circuit protection
	<b>Enclosure</b>	IP67 (Manifold assembly)
	<b>Standards</b>	CE marking (EMC directive/RoHS directive), UL (CSA)
	<b>Weight</b>	300 g

\*2 The configuration file can be downloaded from the SMC website: <https://www.smce.eu>

### SI Unit (EX600-SDN□A)


Model	EX600-SDN1A	EX600-SDN2A
<b>Communication</b>	<b>Protocol</b>	DeviceNet®: Volume 1 (Edition 2.1), Volume 3 (Edition 1.1)
	<b>Device type</b>	Group 2 Only Server
	<b>Communication speed</b>	125/250/500 kbps
	<b>Configuration file</b>	EDS file*3
	<b>Occupation area (Number of inputs/outputs)</b>	Max. (512 inputs/512 outputs)
	<b>Applicable messages</b>	Duplicate MAC ID Check Message, Group 2 Only Unconnected Explicit Message Explicit Message (Group 2), Poll I/O Message (Predefined M/S Connection set)
	<b>Applicable function</b>	QuickConnect™
	<b>DeviceNet® power supply</b>	11 to 25 VDC (Current consumption 50 mA or less)
	<b>Internal current consumption (Power supply for Control/Input)</b>	55 mA or less
<b>Output</b>	<b>Output type</b>	Source/PNP (Negative common) Sink/NPN (Positive common)
	<b>Number of outputs</b>	32 outputs (8/16/24/32 outputs selectable)
	<b>Load</b>	Solenoid valve with surge voltage suppressor 24 VDC, 1.5 W or less (SMC)
	<b>Power supply</b>	24 VDC, 2 A
	<b>Fail safe</b>	HOLD/CLEAR/Forced power ON
	<b>Protection</b>	Short-circuit protection
	<b>Enclosure</b>	IP67 (Manifold assembly)
	<b>Standards</b>	CE marking (EMC directive/RoHS directive), UL (CSA)
	<b>Weight</b>	300 g

\*3 The configuration file can be downloaded from the SMC website: <https://www.smce.eu>


### SI Unit (EX600-SMJ□)

Model	EX600-SMJ1	EX600-SMJ2
<b>Communication</b>	<b>Protocol</b>	CC-Link (Ver. 1.10, Ver. 2.00)
	<b>Station type</b>	Remote Device Station
	<b>Communication speed</b>	156/625 kbps 2.5/5/10 Mbps
	<b>Configuration file</b>	CSP+ file*4
	<b>Occupation area (Number of inputs/outputs)</b>	Max. (512 inputs/512 outputs) 1/2/3/4 stations occupied
	<b>Internal current consumption (Power supply for Control/Input)</b>	75 mA or less
	<b>Output type</b>	Source/PNP (Negative common) Sink/NPN (Positive common)
	<b>Number of outputs</b>	32 outputs (8/16/24/32 outputs selectable)
	<b>Load</b>	Solenoid valve with surge voltage suppressor 24 VDC, 1.5 W or less (SMC)
	<b>Power supply</b>	24 VDC, 2 A
<b>Output</b>	<b>Fail safe</b>	HOLD/CLEAR/Forced power ON
	<b>Protection</b>	Short-circuit protection
	<b>Enclosure</b>	IP67 (Manifold assembly)
	<b>Standards</b>	CE marking (EMC directive/RoHS directive), UL (CSA)
	<b>Weight</b>	300 g


\*4 The configuration file can be downloaded from the SMC website: <https://www.smce.eu>



EX600-SPR□A




EX600-SDN□A



EX600-SMJ□

## Specifications



**EX600-SCF1-X60**


### SI Unit (EX600-SCF1-X60)

Model	<b>EX600-SCF1-X60*</b>
Communication	Protocol CC-Link IE Field
	Station type Intelligent Device Station
	Communication speed 1 Gbps
	Allowable station number setting 1 to 120
	Allowable network number setting 1 to 239
	Transmission method Cyclic transmission
	Configuration file CSP+ file <sup>*2</sup>
	Occupied input size RX: 32 to 176 bits RWr: 32 to 608 words
Output	Occupied output size RY: 32 to 176 bits RWr: 32 to 608 words
	Internal current consumption (Power supply for Control/Input) 140 mA or less
	Output type Source/PNP (Negative common)
	Number of outputs 32 outputs
	Load Solenoid valve with surge voltage suppressor 24 VDC, 1.0 W or less (SMC)
	Power supply 24 VDC, 2 A
	Fail safe HOLD/CLEAR/Forced power ON
	Protection Short-circuit protection
Enclosure	IP67 (Manifold assembly)
Standards	CE marking (EMC directive/RoHS directive)
Weight	300 g


\*1 For details on this product, refer to the SMC website.

\*2 The configuration file can be downloaded from the SMC website: <https://www.smce.eu>

### SI Unit (EX600-SEN□)



**EX600-SEN1/2**




**EX600-SEN3/4(-X80)**

Model	<b>EX600-SEN1</b>	<b>EX600-SEN2</b>	<b>EX600-SEN3</b>	<b>EX600-SEN4</b>	<b>EX600-SEN3-X80</b>
Communication	Number of communication ports 1 port				2 ports
	Protocol EtherNet/IP® (Conformance version: Composite 6)				EtherNet/IP® (Conformance version: Composite 11)
	Communication speed 10/100 Mbps				
	Communication method Full duplex/Half duplex				
	Configuration file EDS file <sup>*3</sup>				
	Occupation area (Number of inputs/outputs)	Max. (512 inputs/512 outputs)			
	IP address setting range	SI Unit switch settings: 192.168.0 or 1.1 to 254 Through DHCP server: Optional address			
	Device information	Vendor ID: 7 (SMC Corporation) Device type: 12 (Communication Adapter) Product code: 126	Vendor ID: 7 (SMC Corporation) Device type: 12 (Communication Adapter) Product code: 203		
QuickConnect	—	●	●		
DLR	—	●	●		
Web server function	—	●	●		
IO-Link unit	—	—	—	●	
Internal current consumption (Power supply for Control/Input)	120 mA or less				
Output	Output type Source/PNP (Negative common)	Sink/NPN (Positive common)	Source/PNP (Negative common)	Sink/NPN (Positive common)	Source/PNP (Negative common)
	Number of outputs 32 outputs (8/16/24/32 outputs selectable)				32 outputs
	Load Solenoid valve with surge voltage suppressor 24 VDC, 1.5 W or less (SMC)				Solenoid valve with surge voltage suppressor 24 VDC, 1.0 W or less (SMC)
	Power supply 24 VDC, 2 A				
	Fail safe HOLD/CLEAR/Forced power ON				
	Protection Short-circuit protection				
	Enclosure IP67 (Manifold assembly)				
	Standards CE marking (EMC directive/RoHS directive), UL (CSA)				
Weight	300 g				

\*3 The configuration file can be downloaded from the SMC website: <https://www.smce.eu>

# EX600 Series

## Specifications




EX600-SEC□

SI Unit (EX600-SEC□)

Model	EX600-SEC1	EX600-SEC2
Communication	<b>Protocol</b>	EtherCAT (Conformance Test Record V.1.2)
	<b>Communication speed</b>	100 Mbps
	<b>Configuration file</b>	XML file*1
	<b>Occupation area (Number of inputs/outputs)</b>	Max. (512 inputs/512 outputs)
	<b>Internal current consumption (Power supply for Control/Input)</b>	100 mA or less
	<b>Output type</b>	Source/PNP (Negative common)      Sink/NPN (Positive common)
Output	<b>Number of outputs</b>	32 outputs (8/16/24/32 outputs selectable)
	<b>Load</b>	Solenoid valve with surge voltage suppressor 24 VDC, 1.5 W or less (SMC)
	<b>Power supply</b>	24 VDC, 2 A
	<b>Fail safe</b>	HOLD/CLEAR/Forced power ON
	<b>Protection</b>	Short-circuit protection
<b>Enclosure</b>		
<b>Standards</b>		
<b>Weight</b>		

\*1 The configuration file can be downloaded from the SMC website: <https://www.smc.eu>




EX600-SPN1/2

SI Unit (EX600-SPN□)


Model	EX600-SPN1	EX600-SPN2	EX600-SPN3	EX600-SPN4			
Communication	<b>Protocol</b>	PROFINET IO (Conformance Class B)	PROFINET IO (Conformance Class C)				
	<b>Communication speed</b>	100 Mbps					
	<b>Configuration file</b>	GSDML file*2					
	<b>Fast Start Up (Communication connection time)</b>	● (Approx. 2 s)	● (Approx. 500 ms)				
	<b>MRP</b>	—	●				
	<b>System Redundancy S2</b>	—	●				
Output	<b>Web server</b>	—	●				
	<b>IO-Link unit</b>	—	●				
	<b>Current consumption</b>	120 mA or less					
	<b>Output type</b>	Source/PNP (Negative common)	Sink/NPN (Positive common)	Source/PNP (Negative common)			
	<b>Number of outputs</b>	32 outputs					
<b>Load</b>							
Solenoid valve with surge voltage suppressor 24 VDC, 1.0 W or less (SMC)							
<b>Fail safe</b>							
HOLD/CLEAR/Forced power ON							
<b>Protection</b>							
Short-circuit protection							
<b>Enclosure</b>							
<b>Standards</b>							
<b>Weight</b>							

\*2 The configuration file can be downloaded from the SMC website: <https://www.smc.eu>




EX600-SPN3/4


## Specifications




**EX600-DX□B**




**EX600-DX□C□**



**EX600-DX□D**



**EX600-DX□E**



**EX600-DX□F**

### Digital Input Unit

Model	EX600-DXPB	EX600-DXNB	EX600-DXPC□	EX600-DXNC□	EX600-DXPD	EX600-DXND
<b>Input type</b>	PNP	NPN	PNP	NPN	PNP	NPN
<b>Input connector</b>	M12 (5-pin) socket*1	M8 (3-pin) socket*3			M12 (5-pin) socket*1	
<b>Number of inputs</b>	8 inputs (2 inputs/Connector)	8 inputs (1 input/Connector)			16 inputs (2 inputs/Connector)	
<b>Supplied voltage</b>			24 VDC			
<b>Max. supplied current</b>	0.5 A/Connector 2 A/Unit		0.25 A/Connector 2 A/Unit		0.5 A/Connector 2 A/Unit	
<b>Protection</b>			Short-circuit protection			
<b>Input current (at 24 VDC)</b>			9 mA or less			
<b>ON voltage</b>	17 V or more (At NPN input, between the pin for input terminal and supplied voltage of +24 V) (At PNP input, between the pin for input terminal and supplied voltage of 0 V)					
<b>OFF voltage</b>	5 V or less (At NPN input, between the pin for input terminal and supplied voltage of +24 V) (At PNP input, between the pin for input terminal and supplied voltage of 0 V)					
<b>Open circuit detection current</b>	2 wires 3 wires	—	0.5 mA/Input*2		—	
<b>Current consumption</b>		50 mA or less	55 mA or less		70 mA or less	
<b>Enclosure</b>			IP67 (Manifold assembly)			
<b>Standards</b>			CE marking (EMC directive/RoHS directive), UL (CSA)			
<b>Weight</b>	300 g		275 g		340 g	

\*1 M12 (4-pin) connector can be connected.


\*2 Function only applies to the EX600-DX□C1.

\*3 When connecting the M8 plug connector, the tightening torque must be 0.2 N·m ±10 %. If tightened with an excessive tightening torque, this may cause the connector thread of the unit to break.


Model	EX600-DXPE	EX600-DXNE	EX600-DXPF	EX600-DXNF
<b>Input type</b>	PNP	NPN	PNP	NPN
<b>Input connector</b>	D-sub socket (25 pins) Lock screw: No.4-40 UNC		Spring type terminal block (32 pins)	
<b>Number of inputs</b>	16 inputs		16 inputs (2 inputs x 8 blocks)	
<b>Supplied voltage</b>		24 VDC		
<b>Max. supplied current</b>		2 A/Unit	0.5 A/Block 2 A/Unit	
<b>Protection</b>			Short-circuit protection	
<b>Input current (at 24 VDC)</b>		5 mA or less		
<b>ON voltage</b>	17 V or more (At NPN input, between the pin for input terminal and supplied voltage of +24 V) (At PNP input, between the pin for input terminal and supplied voltage of 0 V)			
<b>OFF voltage</b>	5 V or less (At NPN input, between the pin for input terminal and supplied voltage of +24 V) (At PNP input, between the pin for input terminal and supplied voltage of 0 V)			
<b>Applicable wire</b>	—	0.08 to 1.5 mm <sup>2</sup> (AWG16 to 28)		
<b>Current consumption</b>	50 mA or less		55 mA or less	
<b>Enclosure</b>		IP40 (Manifold assembly)		
<b>Standards</b>		CE marking (EMC directive/RoHS directive), UL (CSA)		
<b>Weight</b>		300 g		

# EX600 Series


## Specifications



EX600-DY□B



EX600-DY□E  
EX600-DM□E



EX600-DY□F  
EX600-DM□F

### Digital Output Unit


Model	EX600-DYPB	EX600-DYNB	EX600-DYPE	EX600-DYNE	EX600-DYPF	EX600-DYNF
Output	<b>Output type</b>	PNP	NPN	PNP	NPN	PNP
	<b>Output connector</b>	M12 (5-pin) socket <sup>*1</sup>		D-sub socket (25 pins) Lock screw: No.4-40 UNC		Spring type terminal block (32 pins)
	<b>Number of outputs</b>	8 outputs (2 outputs/Connector)		16 outputs	16 outputs (2 outputs x 8 blocks)	
	<b>Supplied voltage</b>			24 VDC		
	<b>Max. load current</b>			0.5 A/Output 2 A/Unit		
	<b>Protection</b>			Short-circuit protection		
<b>Applicable wire</b>	—	—		0.08 to 1.5 mm <sup>2</sup> (AWG16 to 28)		
<b>Current consumption</b>			50 mA or less			
<b>Enclosure</b>	IP67 (Manifold assembly)			IP40 (Manifold assembly)		
<b>Standards</b>			CE marking (EMC directive/RoHS directive), UL (CSA)			
<b>Weight</b>			300 g			

\*1 M12 (4-pin) connector can be connected.

### Digital Input/Output Unit

Model	EX600-DMPE	EX600-DMNE	EX600-DMPF	EX600-DMNF
Input	<b>Input/Output type</b>	PNP	NPN	PNP
	<b>Connector</b>	D-sub socket (25 pins) Lock screw: No.4-40 UNC		Spring type terminal block (32 pins)
	<b>Number of inputs</b>	8 inputs		8 inputs (2 inputs x 4 blocks)
	<b>Supplied voltage</b>		24 VDC	
	<b>Max. supplied current</b>	2 A/Unit		0.5 A/Block 2 A/Unit
	<b>Protection</b>		Short-circuit protection	
<b>Input current (at 24 VDC)</b>		5 mA or less		
<b>ON voltage</b>	17 V or more (At NPN input, between the pin for input terminal and supplied voltage of +24 V) (At PNP input, between the pin for input terminal and supplied voltage of 0 V)			
<b>OFF voltage</b>	5 V or less (At NPN input, between the pin for input terminal and supplied voltage of +24 V) (At PNP input, between the pin for input terminal and supplied voltage of 0 V)			
Output	<b>Number of outputs</b>	8 outputs		8 outputs (2 outputs x 4 blocks)
	<b>Supplied voltage</b>		24 VDC	
	<b>Max. load current</b>		0.5 A/Output 2 A/Unit	
	<b>Protection</b>		Short-circuit protection	
	<b>Applicable wire</b>	—	0.08 to 1.5 mm <sup>2</sup> (AWG16 to 28)	
	<b>Current consumption</b>	50 mA or less		60 mA or less
<b>Enclosure</b>			IP40 (Manifold assembly)	
<b>Standards</b>		CE marking (EMC directive/RoHS directive), UL (CSA)		
<b>Weight</b>			300 g	

## Specifications




**EX600-AXA**

### Analogue Input Unit

Model		<b>EX600-AXA</b>	
Input	<b>Input type</b>	Voltage input	Current input
	<b>Input connector</b>	M12 (5-pin) socket*1	
	<b>Input channel</b>	2 channels (1 channel/Connector)	
	<b>Supplied voltage</b>	24 VDC	
	<b>Max. supplied current</b>	0.5 A/Connector	
	<b>Protection</b>	Short-circuit protection	
	<b>Input signal range</b>	0 to 10 V, 1 to 5 V, 0 to 5 V	0 to 20 mA, 4 to 20 mA
	12 bit resolution	-10 to 10 V, -5 to 5 V	-20 to 20 mA
	16 bit resolution	±15 V	±22 mA*2
	<b>Input impedance</b>	100 kΩ	50 Ω
	<b>Linearity (25 °C)</b>	±0.05 % F.S.	
	<b>Repeatability (25 °C)</b>	±0.15 % F.S.	
	<b>Absolute accuracy (25 °C)</b>	±0.5 % F.S.	±0.6 % F.S.
<b>Current consumption</b>		70 mA or less	
<b>Enclosure</b>		IP67 (Manifold assembly)	
<b>Standards</b>		CE marking (EMC directive/RoHS directive), UL (CSA)	
<b>Weight</b>		290 g	

\*1 M12 (4-pin) connector can be connected.

\*2 When input signal exceeds 22 mA, the protection function activates and the input signal is interrupted.



**EX600-AYA**


### Analogue Output Unit

Model		<b>EX600-AYA</b>	
Output	<b>Output type</b>	Voltage output	Current output
	<b>Output connector</b>	M12 (5-pin) socket*3	
	<b>Output channel</b>	2 channels (1 channel/Connector)	
	<b>Supplied voltage</b>	24 VDC	
	<b>Max. load current</b>	0.5 A/Connector	
	<b>Protection</b>	Short-circuit protection	
	<b>Output signal range</b>	0 to 10 V, 1 to 5 V, 0 to 5 V	0 to 20 mA, 4 to 20 mA
	12 bit resolution	1 kΩ or more	600 Ω or less
	<b>Load impedance</b>	±0.05 % F.S.	
	<b>Linearity (25 °C)</b>	±0.15 % F.S.	
	<b>Repeatability (25 °C)</b>	±0.5 % F.S.	±0.6 % F.S.
	<b>Absolute accuracy (25 °C)</b>		
<b>Current consumption</b>		70 mA or less	
<b>Enclosure</b>		IP67 (Manifold assembly)	
<b>Standards</b>		CE marking (EMC directive/RoHS directive), UL (CSA)	
<b>Weight</b>		290 g	

\*3 M12 (4-pin) connector can be connected.

# EX600 Series

## Specifications



**EX600-AMB**


### Analogue Input/Output Unit

Model		<b>EX600-AMB</b>	
Input	<b>Input type</b>	Voltage input	Current input
	<b>Input connector</b>	M12 (5-pin) socket*1	
	<b>Input channel</b>	2 channels (1 channel/Connector)	
	<b>Supplied voltage</b>	24 VDC	
	<b>Max. supplied current</b>	0.5 A/Connector	
	<b>Protection</b>	Short-circuit protection	
	<b>Input signal range</b>	12 bit resolution 0 to 10 V, 1 to 5 V, 0 to 5 V	0 to 20 mA, 4 to 20 mA
	<b>Max. rated input signal</b>	15 V	22 mA*2
	<b>Input impedance</b>	100 kΩ	250 Ω
	<b>Linearity (25 °C)</b>		±0.05 % F.S.
Output	<b>Repeatability (25 °C)</b>		±0.15 % F.S.
	<b>Absolute accuracy (25 °C)</b>	±0.5 % F.S.	±0.6 % F.S.
	<b>Output type</b>	Voltage output	Current output
	<b>Output connector</b>	M12 (5-pin) socket*1	
	<b>Output channel</b>	2 channels (1 channel/Connector)	
	<b>Supplied voltage</b>	24 VDC	
	<b>Max. load current</b>	0.5 A/Connector	
	<b>Protection</b>	Short-circuit protection	
	<b>Output signal range</b>	12 bit resolution 0 to 10 V, 1 to 5 V, 0 to 5 V	0 to 20 mA, 4 to 20 mA
	<b>Load impedance</b>	1 kΩ or more	600 Ω or less
<b>Linearity (25 °C)</b>			±0.05 % F.S.
<b>Repeatability (25 °C)</b>			±0.15 % F.S.
<b>Absolute accuracy (25 °C)</b>		±0.5 % F.S.	±0.6 % F.S.
<b>Current consumption</b>		100 mA or less	
<b>Enclosure</b>		IP67 (Manifold assembly)	
<b>Standards</b>		CE marking (EMC directive/RoHS directive), UL (CSA)	
<b>Weight</b>		300 g	

\*1 M12 (4-pin) connector can be connected.

\*2 When input signal exceeds 22 mA, the protection function activates and the input signal is interrupted.


## Specifications




**EX600-L□B1**

### IO-Link Unit


Model	EX600-LAB1	EX600-LBB1
<b>IO-Link version</b>	Version 1.1	
<b>IO-Link port class</b>	Class A	Class B
<b>Communication speed</b>		COM1 (4.8 kBaud) COM2 (38.4 kBaud) COM3 (230.4 kBaud)
* Changes automatically according to the connected device		
<b>Number of IO-Link ports</b>	4	
<b>Compatible SI unit (Protocol)</b>	EX600-SPN3/4 (PROFINET) EX600-SEN3-X80 (EtherNet/IP®)	
<b>Max. supply current</b>	<b>Device power supply (L+)</b>	0.5 A/Connector (2 A/Unit)
	<b>External power supply (P24)</b>	— 1.6 A/Connector (3 A/Unit)
<b>Input</b>	<b>Pin no.</b>	2      4
	<b>Input type</b>	PNP
	<b>Protection</b>	Short-circuit protection
	<b>Rated input current</b>	Approx. 2.5 mA      Approx. 5.8 mA
	<b>ON voltage</b>	13 V or more
	<b>OFF voltage</b>	8 V or less
<b>Output</b>	<b>Pin no.</b>	4
	<b>Output type</b>	PNP
	<b>Max. load current (C/Q line)</b>	0.25 A/Output (Supplied from the power supply for control/input)
	<b>Protection</b>	Short-circuit protection
<b>Current consumption</b>		50 mA or less
<b>Enclosure</b>		IP67 (Manifold assembly)
<b>Standards</b>		CE marking (EMC directive/RoHS directive), UL (CSA)
<b>Weight</b>		320 g



**EX600-ED2-□**




**EX600-ED4/5-□**



**EX600-ED3-□**

### End Plate

Model	EX600-ED2-□	EX600-ED3-□	EX600-ED4/5-□
<b>Power specifications</b>	<b>Power supply connector</b>	M12 (5-pin) plug	7/8 inch (5-pin) plug
	<b>PWR OUT</b>	—	— M12 (5-pin) socket
<b>Rated voltage</b>	Power supply for control/input		
	24 VDC ±10 %		
<b>Rated current</b>	<b>Power supply for output</b>	24 VDC +10/-5 %	
	<b>Power supply for control/input</b>	Max. 2 A	Max. 8 A
<b>Power supply for output</b>		Max. 4 A	
<b>Enclosure</b>		IP67 (Manifold assembly)	
<b>Standards*</b>		CE marking (EMC directive/RoHS directive), UL (CSA)	
<b>Weight</b>		170 g	175 g
*1 The EX600-ED4/5-□ is not compliant with UL (CSA) standards.		170 g	



**EX600-HT1A-□**

### Handheld Terminal

Model	EX600-HT1A-□
<b>Power supply</b>	Power supplied from SI unit connector (24 VDC)
<b>Current consumption</b>	50 mA or less
<b>Display</b>	LCD with backlight
<b>Connection cable</b>	Handheld terminal cable (1 m ... EX600-AC010-1, 3 m ... EX600-AC030-1)
<b>Enclosure</b>	IP20
<b>Standards*</b>	CE marking (EMC directive/RoHS directive)
<b>Weight</b>	160 g


\*1 The handheld terminal is not compliant with UL (CSA) standards.

\* Cannot be used with the EX600-SPN3/4 and EX600-LAB1/LBB1


# EX600 Series

## Dimensions

### SI Unit




EX600-SPN3/4




## Dimensions

### End Plate (D side)

**EX600-ED2**



**EX600-ED4/ED5**



**Power supply connector PWR IN:**  
M12 5-pin plug, B-coded

EX600-ED2		
Configuration	Pin no.	Description
1 24 V (for output)		
2 0 V (for output)		
3 24 V (for control/input)		
4 0 V (for control/input)		
5 FE		

**Power supply connector PWR IN:**  
M12 4-pin plug, A-coded

EX600-ED4 (Pin arrangement 1)		EX600-ED5 (Pin arrangement 2)		
Configuration	Pin no.	Description	Pin no.	Description
	1	24 V (for control/input)	1	24 V (for output)
	2	24 V (for output)	2	0 V (for output)
	3	0 V (for control/input)	3	24 V (for control/input)
	4	0 V (for output)	4	0 V (for control/input)

**Power supply connector PWR OUT:**  
M12 5-pin socket, A-coded


EX600-ED4 (Pin arrangement 1)		EX600-ED5 (Pin arrangement 2)		
Configuration	Pin no.	Description	Pin no.	Description
	1	24 V (for control/input)	1	24 V (for output)
	2	24 V (for output)	2	0 V (for output)
	3	0 V (for control/input)	3	24 V (for control/input)
	4	0 V (for output)	4	0 V (for control/input)
	5	Unused	5	Unused

# EX600 Series

## Dimensions

### End Plate (D side)

EX600-ED3



Power supply connector PWR: 7/8 inch 5-pin plug


Configuration	Pin no.	Description
1	1	0 V (for output)
2	2	0 V (for control/input)
3	3	FE
4	4	24 V (for control/input)
5	5	24 V (for output)




# EX600 Series

## Dimensions



### Digital Unit







**EX600-DX□C□**



**EX600-DX□D**




**EX600-DX□F  
EX600-DY□F  
EX600-DM□F**




## Dimensions

### Analogue Unit

**EX600-AXA**  
**EX600-AYA**




**EX600-AMB**



### IO-Link Unit


**EX600-LAB1**  
**EX600-LBB1**



# EX600 Series

## Parts Description

### SI Unit




No.	Name	Use
1	Status indication LED	Displays unit status
2	Indication cover	Open for setting the switch.
3	Indication cover set screw	Loosen for opening the indication cover.
4	Connector (BUS OUT)	Connects to the fieldbus output cable (SPEEDCON) <sup>*1</sup>
5	Marker groove	Can be used to mount a marker
6	Connector (PCI)	Connects to the handheld terminal cable (SPEEDCON)
7	Valve plate mounting holes	Fixes a valve plate in place
8	Valve plate mounting groove	Inserts a valve plate
9	Joint bracket	Links units to one another
10	Connector for unit (Plug)	Transmits signals to the neighbouring unit and supplies power
11	Connector (BUS IN)	Connects to the cable for fieldbus input (SPEEDCON) <sup>*1</sup>
12	MAC address name plate <sup>*2</sup>	Displays a unique 12-digit MAC address for each SI unit
13	Seal cap	Mounted on the connectors (BUS OUT and PCI) at the time of shipment

\*1 The EX600-SPN3/4 is not SPEEDCON compatible.

\*2 MAC address name plate is not provided on the EX600-SEC□.


### Digital Unit



No.	Name	Use
1	Status indication LED	Displays unit status
2	Connector	Connects with input or output devices (Only the EX600-D□□B and EX600-DX□D are SPEEDCON compatible.)
3	Marker groove	Can be used to mount a marker
4	Lock screw	Secures the D-sub connector in place (No.4-40 UNC)
5	Joint bracket	Links units to one another
6	Connector for unit (Plug)	Transmits signals to the neighbouring unit and supplies power


## Parts Description

### Analogue Unit




No.	Name	Use
1	Status indication LED	Displays unit status
2	Connector	Connects with input or output devices (SPEEDCON)
3	Marker groove	Can be used to mount a marker
4	Joint bracket	Links units to one another
5	Connector for unit (Plug)	Transmits signals to the neighbouring unit and supplies power

### IO-Link Unit



No.	Name	Use
1	Status indication LED	Displays unit status
2	Connector	Connects with IO-Link, input, or output devices (SPEEDCON)
3	Marker groove	Can be used to mount a marker
4	Joint bracket	Links units to one another
5	Connector for unit (Plug)	Transmits signals to the neighbouring unit and supplies power

### End Plate




No.	Name	Use
1	Power connector (PWR IN)	Supplies power to the unit and/or input/output device (Only the EX600-ED2/ED4/ED5-□ is SPEEDCON compatible.)
2	Fixing hole for direct mounting	Connects directly to equipment
3	Fixing hole for DIN rail	Converts to manifold or for DIN rail mounting
4	FE terminal	Used for grounding Ground this terminal securely to improve noise immunity.
5	Connector (Unused) Power connector (PWR OUT)	Supplies power to the device on the downstream side


# EX600 Series

## LED Indicator


### EX600-SPR□A




### EX600-SDN□A




### EX600-SEN1/SEN2




### EX600-SEN3/SEN4(-X80)



### EX600-SEC□




### EX600-SPN1/SPN2




## LED Indicator


### EX600-SPN3/SPN4




### EX600-SMJ□




### EX600-DX□B




### EX600-DX□C□



### EX600-DX□D




### EX600-DX□E




# EX600 Series

## LED Indicator


EX600-DX□F




EX600-DY□B




EX600-DY□E




EX600-DY□F



EX600-DM□E




EX600-DM□F




## LED Indicator


**EX600-AXA**




**EX600-AYA**




**EX600-AMB**




**EX600-LAB1**



**EX600-LBB1**



# EX600 Series Accessories



## ① End Plate Bracket

This bracket is used for the end plate of DIN rail mounting.



**EX600-ZMA2**

### Enclosed parts

Round head screw (M4 x 20)	1 pc.
P-tight screw (4 x 14)	2 pcs.


**EX600-ZMA3**  
(Specialised for SY series)

### Enclosed parts

Round head screw with washer (M4 x 20)	1 pc.
P-tight screw (4 x 14)	2 pcs.

## ② Valve Plate

**EX600-ZMV1**



### Enclosed parts

Round head screw (M4 x 6)	2 pcs.
Round head screw (M3 x 8)	4 pcs.

**EX600-ZMV2**  
(Specialised for SY series)



### Enclosed parts

Round head screw (M4 x 6)	2 pcs.
Round head screw (M3 x 8)	2 pcs.

### ③ End Plate (U side)

The end plate is for use when the manifold valve is not connected.

**EX600-EU1-2**

#### Mounting method

Symbol	Description	Note
—	Without DIN rail mounting bracket	—
2	With DIN rail mounting bracket	For EX600-ED□-2
3	With DIN rail mounting bracket	For EX600-ED□-3


\* Select in accordance with the symbol for the end plate (D side) mounting method.

#### Specification



Symbol	Specification
1	Waterproof cover

#### End plate mounting position: U side

#### End plate



**EX600-EU1**



#### Enclosed parts

Round head screw (M4 x 5) 2 pcs.

### ④ Reinforcing Brace

This bracket is used on the bottom of the unit at the intermediate position for connecting 6 units or more.

\* Be sure to attach this bracket to prevent connection failure between the units caused by deflection.


**For Direct mounting  
EX600-ZMB1**



#### Enclosed parts

Round head screw (M4 x 5) 2 pcs.

**For DIN rail mounting  
EX600-ZMB2**



#### Enclosed parts

Round head screw (M4 x 6) 2 pcs.

### ⑤ Seal Cap (10 pcs.)

Be sure to mount a seal cap on any unused I/O connectors. Otherwise, the specified enclosure cannot be maintained.

**EX9-AWES**  
For M8




**EX9-AWTS**  
For M12



### ⑥ Marker (1 sheet, 88 pcs.)

The signal name of I/O device and each unit address can be entered and mounted on each unit.

**EX600-ZT1**




# EX600 Series

## ⑦ Power Supply Cable (7/8 inch connector)

- PCA-1558810** Straight 2 m  
**PCA-1558823** Straight 6 m  
**PCA-1558836** Right angled 2 m  
**PCA-1558849** Right angled 6 m



### Straight connector type




Socket pin arrangement

### Core wire colour

1	Red/White: 0 V (For output)
2	Red: 0 V (For control and input)
3	Green: FE
4	Red/Orange: 24 VDC ±10 % (For control and input)
5	Red/Black: 24 VDC +10 %~-5 % (For output)

Connections

### Angled connector type



Socket pin arrangement

### Core wire colour

1	Red/White: 0 V (For output)
2	Red: 0 V (For control and input)
3	Green: FE
4	Red/Orange: 24 VDC ±10 % (For control and input)
5	Red/Black: 24 VDC +10 %~-5 % (For output)

Connections

Item	Specifications
<b>Cable O.D.</b>	Ø 12.58 mm
Conductor nominal cross section	1.5 mm <sup>2</sup> /AWG16
Wire O.D. (Including insulator)	2.35 mm
Min. bending radius (Fixed)	110 mm

## ⑧ Power Supply Field-wireable Connector (7/8 inch)

- PCA-1578081** Socket [compatible with AWG22-16]



### Applicable Cable

Item	Specifications
<b>Cable O.D.</b>	Ø 12.0 to 14.0 mm
Wire gauge (Stranded wire cross section)	0.34 to 1.5 mm <sup>2</sup> AWG22 to 16

## ⑨ Power Supply Cable (M12 connector, For EX600-ED2)


\* The shape of the M12 connector is B-coded (Reverse key).

- PCA-1564927** Straight 2 m  
**PCA-1564930** Straight 6 m  
**PCA-1564943** Right angled 2 m  
**PCA-1564969** Right angled 6 m




**SPEEDCON**

### Straight connector type



SPEEDCON


**Socket connector pin arrangement**  
B-coded (Reverse key)



Terminal no.      Core wire colour

1	Brown: 24 VDC +10 %~-5 % (For output)
2	White: 0 V (For output)
3	Blue: 24 VDC ±10 % (For control and input)
4	Black: 0 V (For control and input)
5	Grey: Functional earth

### Angled connector type



**Socket connector pin arrangement**  
B-coded (Reverse key)

Terminal no.      Core wire colour

1	Brown: 24 VDC +10 %~-5 % (For output)
2	White: 0 V (For output)
3	Blue: 24 VDC ±10 % (For control and input)
4	Black: 0 V (For control and input)
5	Grey: Functional earth

Item	Specifications
<b>Cable O.D.</b>	Ø 5.9 mm
Conductor nominal cross section	0.34 mm <sup>2</sup> /AWG22
Wire O.D. (Including insulator)	1.27 mm
Min. bending radius (Fixed)	59 mm

**⑩ Power Supply Cable (M12 connector, For EX600-ED4/5)**

\* The shape of the M12 connector is A-coded (Normal key).



**EX500-AP 050 - S**

Cable length (L)

010	1000 mm
050	5000 mm


Connector specification

S	Straight
A	Angled

**Straight connector type**Socket connector pin arrangement  
A-coded  
(Normal key)**Angled connector type**Socket connector pin arrangement  
A-coded  
(Normal key)

Item	Specifications
Cable O.D.	Ø 6 mm
Nominal cross section	0.3 mm <sup>2</sup> /AWG22
Wire diameter (Including insulator)	1.5 mm
Min. bending radius	40 mm (Fixed)

Item	Specifications
Cable O.D.	Ø 6 mm
Nominal cross section	0.3 mm <sup>2</sup> /AWG22
Wire diameter (Including insulator)	1.5 mm
Min. bending radius	40 mm (Fixed)

**Connections****SPEEDCON****PCA- 1401804**

Cable length (L)


1401804	1500 mm
1401805	3000 mm
1401806	5000 mm

Socket connector pin arrangement  
A-coded  
(Normal key)

Item	Specifications
Cable O.D.	Ø 5 mm
Nominal cross section	0.3 mm <sup>2</sup> /AWG22
Wire diameter (Including insulator)	1.27 mm
Min. bending radius	21.7 mm (Fixed)


Terminal no.

Cable core wire colours

**Connections****PCA- 1557769**

Cable length (L)

1557769	3000 mm
---------	---------



Terminal no.	Terminal no.
1	1
2	2
3	3
4	4
5	3


Socket connector pin arrangement  
A-coded  
(Normal key)Plug connector pin arrangement  
A-coded  
(Normal key)

# EX600 Series

## ⑪ Communication Cable


For CC-Link

**PCA-1567720**  
(Socket)



\*1 Number of holes: 5,  
Total number of pins: 4

**PCA-1567717**  
(Plug)




Made to Order

Cable length

10000 mm

p. 47



Terminal no.	Core wire colour
2	White: DB
1	Yellow: DG
3	Blue: DA
4	

Connections


Item	Specifications
<b>Cable O.D.</b>	Ø 7.7 mm
Conductor nominal cross section	0.5 mm <sup>2</sup> /AWG20
Drain	0.34 mm <sup>2</sup> /AWG22
Wire O.D. (Including insulator)	2.55 mm
Min. bending radius (Fixed)	77 mm

## EX9-AC 005 MJ-SSPS (With connector on both sides (Socket/Plug))

• Cable length (L)

<b>005</b>	500 mm
<b>010</b>	1000 mm
<b>020</b>	2000 mm
<b>030</b>	3000 mm
<b>050</b>	5000 mm
<b>100</b>	10000 mm

Item	Specifications
<b>Cable O.D.</b>	Ø 7.7 mm
Conductor nominal cross section	0.5 mm <sup>2</sup> /AWG20
Drain	0.34 mm <sup>2</sup> /AWG22
Wire O.D. (Including insulator)	2.55 mm
Min. bending radius (Fixed)	77 mm



Socket connector pin arrangement A-coded (Normal key)

\*1 Number of holes: 5,  
Total number of pins: 4

Core wire Signal name  
colour CC-Link  
Blue DA  
White DB  
Yellow DG  
Shield SLD


Plug connector pin arrangement A-coded (Normal key)

## EX9-AC 005 MJ-SAPA (With angled connector on both sides (Socket/Plug))

• Cable length (L)

<b>005</b>	500 mm
<b>010</b>	1000 mm
<b>020</b>	2000 mm
<b>030</b>	3000 mm
<b>050</b>	5000 mm
<b>100</b>	10000 mm

Item	Specifications
<b>Cable O.D.</b>	Ø 7.7 mm
Conductor nominal cross section	0.5 mm <sup>2</sup> /AWG20
Drain	0.34 mm <sup>2</sup> /AWG22
Wire O.D. (Including insulator)	2.55 mm
Min. bending radius (Fixed)	77 mm



Plug connector pin arrangement A-coded (Normal key)


Socket connector pin arrangement A-coded (Normal key)

\*1 Number of holes: 5,  
Total number of pins: 4


## ⑪ Communication Cable

For DeviceNet®

**PCA-1557633**  
(Socket)




**PCA-1557646**  
(Plug)



Made to Order

Cable length	10000 mm	p. 47
--------------	----------	-------



Terminal no.	Core wire colour
2 1	Red: V+ Black: V-
4 3	White: CAN H Blue: CAN L
5	: DRAIN



Connections

Item	Specifications
<b>Cable O.D.</b>	Ø 6.7 mm
Conductor nominal cross section	Power pair 0.34 mm <sup>2</sup> /AWG22 Data pair 0.25 mm <sup>2</sup> /AWG24
Wire O.D. (Including insulator)	Power pair 1.4 mm Data pair 1.95 mm
Min. bending radius (Fixed)	67 mm

### EX9-AC 005 DN-SSPS (With connector on both sides (Socket/Plug))

Cable length (L)	
<b>005</b>	500 mm
<b>010</b>	1000 mm
<b>020</b>	2000 mm
<b>030</b>	3000 mm
<b>050</b>	5000 mm
<b>100</b>	10000 mm



Item	Specifications
<b>Cable O.D.</b>	Ø 6.7 mm
Conductor nominal cross section	Power pair 0.34 mm <sup>2</sup> /AWG22 Data pair 0.25 mm <sup>2</sup> /AWG24
Wire O.D. (Including insulator)	Power pair 1.4 mm Data pair 1.95 mm
Min. bending radius (Fixed)	67 mm



### EX9-AC 005 DN-SAPA (With angled connector on both sides (Socket/Plug))

Cable length (L)	
<b>005</b>	500 mm
<b>010</b>	1000 mm
<b>020</b>	2000 mm
<b>030</b>	3000 mm
<b>050</b>	5000 mm
<b>100</b>	10000 mm

Item	Specifications
<b>Cable O.D.</b>	Ø 6.7 mm
Conductor nominal cross section	Power pair 0.34 mm <sup>2</sup> /AWG22 Data pair 0.25 mm <sup>2</sup> /AWG24
Wire O.D. (Including insulator)	Power pair 1.4 mm Data pair 1.95 mm
Min. bending radius (Fixed)	67 mm




# EX600 Series



## ⑪ Communication Cable

For PROFIBUS DP

**PCA-1557688**  
(Socket)



**PCA-1557691**  
(Plug)



Terminal no. Core wire colour  
2 1 Green: A Line  
4 3 Red: B Line

Shield line is connected to the knurl.  
**Connections**

Item	Specifications
<b>Cable O.D.</b>	Ø 7.8 mm
Conductor nominal cross section	0.34 mm <sup>2</sup> /AWG22
Wire O.D. (Including insulator)	2.55 mm
Min. bending radius (Fixed)	78 mm

For EtherCAT®

For PROFINET


For EtherNet/IP®

**EX9-AC 020 EN-PSRJ** (Plug/RJ-45 connector)

Cable length (L)	
010	1000 mm
020	2000 mm
030	3000 mm
050	5000 mm
100	10000 mm



Signal name Terminal no. Terminal no. Core wire colour




**Connections (Straight cable)**

Item	Specifications
<b>Cable O.D.</b>	Ø 6.4 mm
Conductor nominal cross section	0.14 mm <sup>2</sup> /AWG26
Wire O.D. (Including insulator)	0.98 mm
Min. bending radius (Fixed)	26 mm

**PCA-1446566** (Plug)

Plug connector pin arrangement D-coded



Terminal no. Wire guide colour  
1 Yellow: TD+  
2 White: RD+  
3 Orange: TD-  
4 Blue: RD-

**Connections**


Item	Specifications
<b>Cable O.D.</b>	Ø 6.5 mm
Conductor nominal cross section	AWG22
Wire O.D. (Including insulator)	1.55 mm
Min. bending radius (Fixed)	45.5 mm

## ⑪ Communication Cable

**For EtherCAT®** **For PROFINET** **For EtherNet/IP®**


### EX9-AC 005 EN-PSPS (With connector on both sides (Plug/Plug))

Cable length (L)	
005	500 mm
010	1000 mm
020	2000 mm
030	3000 mm
050	5000 mm
100	10000 mm



### EX9-AC 005 EN-PAPA (With angled connector on both sides (Plug/Plug))

Cable length (L)	
005	500 mm
010	1000 mm
020	2000 mm
030	3000 mm
050	5000 mm
100	10000 mm





## ⑫ Field-wireable Communication Connector

**Plug**

**For CC-Link** **For DeviceNet®**  
**PCA-1075526** **PCA-1075528**


**For PROFIBUS DP**  
**PCA-1075530**

**For EtherCAT®** **For PROFINET** **For EtherNet/IP®**  
**PCA-1446553**

**Socket**



**For CC-Link** **For DeviceNet®**  
**PCA-1075527** **PCA-1075529**

**For PROFIBUS DP**  
**PCA-1075531**



### Applicable Cable


Item	Specifications
Cable O.D.	4.0 to 8.0 mm
Wire gauge (Stranded wire cross section)	0.14 to 0.75 mm <sup>2</sup> /AWG26 to 18 (Solid cable/Flexible cable) 0.08 to 0.5 mm <sup>2</sup> /AWG28 to 20 (With ferrule)



### Applicable Cable


Item	Specifications
Cable O.D.	4.0 to 8.0 mm
Wire gauge (Stranded wire cross section)	0.14 to 0.34 mm <sup>2</sup> /AWG26 to 22

\* The table above shows the specifications for the applicable cable. Adaptation for the connector may vary on account of the conductor construction of the electric wire.



### Applicable Cable

Item	Specifications
Cable O.D.	4.0 to 8.0 mm
Wire gauge (Stranded wire cross section)	0.14 to 0.75 mm <sup>2</sup> /AWG26 to 18 (Solid cable/Flexible cable) 0.08 to 0.5 mm <sup>2</sup> /AWG28 to 20 (With ferrule)




# EX600 Series

## ⑬ I/O Cable with Connector, I/O Connector

For details, refer to the Web Catalogue.

Name	Use	Part no.	Description
Cable with connector	For sensor	<b>PCA-1557769</b>	Cable with M12 connector (4 pins/3 m)
		<b>PCA-1557772</b>	Cable with M8 connector (3 pins/3 m)
Field-wireable connector	For sensor	<b>PCA-1557730</b>	Field-wireable connector (M8/3 pins/Plug/Piercecon® connection)
		<b>PCA-1557743</b>	Field-wireable connector (M12/4 pins/Plug/QUICKON-ONE connection/SPEEDCON)
		<b>PCA-1557756</b>	
Y connector	For sensor	<b>PCA-1557785</b>	Y connector (2 x M12 (5 pins)-M12 (5 pins)/SPEEDCON)
		<b>PCA-1557798</b>	Y connector (2 x M8 (3 pins)-M12 (4 pins)/SPEEDCON)




\* When using the Y connector, connect it to the connector on the I/O unit through the sensor cable (PCA-1557769) with the M12 connector.



## For IO-Link Unit

### EX9-AC 005 -SSPS (With connector on both sides (Socket/Plug))

Cable length (L)	
005	500 mm
010	1000 mm
020	2000 mm
030	3000 mm
050	5000 mm
100	10000 mm



Terminal no.


1	○	○	1	Brown
2	○	○	2	White
3	○	○	3	Blue
4	○	○	4	Black
5	○	○	5	Grey

Connections

Item	Specifications
<b>Cable O.D.</b>	Ø 6 mm
Conductor nominal cross section	0.3 mm²/AWG22
Wire O.D. (including conductor)	1.5 mm
Min. bending radius (Fixed)	40 mm

## ⑬ I/O Cable with Connector, I/O Connector


### Port Class B EX260-SIL SI Unit and Port Class A IO-Link Master Connection Example





## Y Branch Connector for IO-Link

This connector is used to supply power to the valve manifold by branching the IO-Link communication cable in cases where a port class A IO-Link master is used.

**EX9-ACY02-S**



Socket connector pin arrangement A-coded (Normal key)



Socket connector pin arrangement A-coded (Normal key)


Solenoid valve power supply cable side pin arrangement when using a branch connector

1	—	Unused
2	SV24V	+24 V for solenoid valve
3	—	Unused
4	—	Unused
5	SV0V	0 V for solenoid valve

## ⑭ IO-Link Device Tool License Key

USB dongle

**EX9-ZSW-LDT1**





# **EX600 Series**

## **Made to Order**

Please contact SMC for detailed specifications and lead times.



### **SI Unit**

Prepare the SI unit, each type of unit, and the manifold valve (without SI unit) separately, and combine them before use.

#### **① Ethernet POWERLINK compatible**

**EX600-SPL1-X26**

- Dimensions are the same as those of the EX600-SEN3.


#### **② Modbus/TCP compatible**

**EX600-SMT1-X25**

- Dimensions are the same as those of the EX600-SEN3.

#### **③ CC-Link IE Field compatible**

**EX600-SCF1-X60**



# EX600 Series

## Communication Cable


With connector on one side (Socket)  
Cable length: 10000 mm

**For CC-Link** **For DeviceNet®**

**EX9-AC100 [MJ]-X12**

• Applicable protocol


MJ	CC-Link
DN	DeviceNet®



Socket connector  
pin arrangement  
A-coded (Normal key)

### For CC-Link

#### Dimensions



#### Connections

Terminal no.	Core wire colour: Signal name (CC-Link)
1	Shield: SLD
2	White: DB
3	Yellow: DG
4	Blue: DA


\*1 Number of holes: 5, Total number of pins: 4



Item	Specifications
Cable O.D.	Ø 7.7 mm
Conductor nominal cross section	0.5 mm <sup>2</sup> /AWG20
Drain	0.34 mm <sup>2</sup> /AWG22
Wire O.D. (Including insulator)	2.55 mm
Min. bending radius (Fixed)	77 mm

### For DeviceNet®

#### Dimensions



#### Connections

Terminal no.	Core wire colour: Signal name (DeviceNet™)
1	Shield: DRAIN
2	Red: V+
3	Black: V-
4	White: CAN H
5	Blue: CAN L

Socket connector  
pin arrangement  
A-coded (Normal key)

Item	Specifications
Cable O.D.	Ø 6.7 mm
Conductor nominal cross section	0.34 mm <sup>2</sup> /AWG22
Data pair	0.25 mm <sup>2</sup> /AWG24
Wire O.D. (Including insulator)	1.4 mm
Data pair	2.05 mm
Min. bending radius (Fixed)	67 mm



# EX600 Series

## Specific Product Precautions

Be sure to read this before handling the products. Refer to the back cover for safety instructions. For fieldbus system precautions, refer to the "Operation Manual" on the SMC website: <https://www.smc.eu>

### Mounting

#### ⚠ Caution

1. When handling and assembling units, do not touch the sharp metal parts of the connector or plug.
2. When connecting six stations or more, be sure to use the intermediate reinforcing brace (EX600-ZMB1 or EX600-ZMB2).

### Operating Environment

#### ⚠ Caution

1. Select the proper type of enclosure according to the operating environment.

IP65/67 is achieved when the following conditions are met.  
1) Provide appropriate wiring between all units using electrical wiring cables, communication connectors and cables with M12 connectors.  
2) Appropriately mount each unit and valve manifold.  
3) Be sure to mount a seal cap on any unused connectors.  
If using in an environment that is exposed to water splashes, please take measures such as using a cover.  
When the enclosure is IP40, do not use in an operating environment or atmosphere where it may come in contact with corrosive gas, chemical agents, seawater, water, or water vapour.

When connected to the EX600-D□□E or EX600-D□□F, manifold enclosure is IP40.

Also, the handheld terminal conforms to IP20, so prevent foreign matter from entering inside, and water, solvent or oil from coming in direct contact with it.

### Adjustment / Operation

#### ⚠ Warning

##### <Handheld Terminal>

1. Do not apply pressure to the LCD.  
There is a possibility of the crack of LCD and injuring.
2. The forced input/output function is used to change the signal status forcibly. When operating this function, be sure to check the safety of the surroundings and installation.  
This may cause injuries or equipment damage.
3. Incorrect setting of parameters can cause a malfunction. Be sure to check the settings before use.  
This may cause injuries or equipment damage.


#### ⚠ Caution

##### <Handheld Terminal>

1. Do not press the setting buttons with a sharp pointed object.  
This may cause damage or equipment failure.
2. Do not apply excessive load and impact to the setting buttons.  
This may cause damage, equipment failure or malfunction.

When the order does not include the SI unit, a valve plate which connects the manifold and SI unit, is not mounted. Use attached valve holding screws and mount the valve plate.

(Tightening torque: 0.6 to 0.7 N·m)



Screw tightened parts  
SV series: 2 places  
S0700 series: 2 places  
VQC1000 series: 2 places  
VQC2000 series: 3 places  
VQC4000 series: 4 places  
VQC5000 series: 4 places  
SY series: 2 places  
JSY series: 2 places

#### ■ Trademark

DeviceNet® is a trademark of ODVA.

EtherNet/IP® is a trademark of ODVA.

EtherCAT® is registered trademark and patented technology, licensed by Beckhoff Automation GmbH, Germany.

Modbus® is a registered trademark of Schneider Electric, licensed to the Modbus Organization, Inc.

QuickConnect™ is a trademark of ODVA.

## Safety Instructions

These safety instructions are intended to prevent hazardous situations and/or equipment damage. These instructions indicate the level of potential hazard with the labels of “**Caution**,” “**Warning**” or “**Danger**.” They are all important notes for safety and must be followed in addition to International Standards (ISO/IEC)<sup>1)</sup>, and other safety regulations.

- ⚠ Caution:** **Caution** indicates a hazard with a low level of risk which, if not avoided, could result in minor or moderate injury.
- ⚠ Warning:** **Warning** indicates a hazard with a medium level of risk which, if not avoided, could result in death or serious injury.
- ⚠ Danger:** **Danger** indicates a hazard with a high level of risk which, if not avoided, will result in death or serious injury.

- 1) ISO 4414: Pneumatic fluid power – General rules relating to systems.  
ISO 4413: Hydraulic fluid power – General rules relating to systems.  
IEC 60204-1: Safety of machinery – Electrical equipment of machines.  
(Part 1: General requirements)  
ISO 10218-1: Manipulating industrial robots - Safety etc.

## Warning

### **1. The compatibility of the product is the responsibility of the person who designs the equipment or decides its specifications.**

Since the product specified here is used under various operating conditions, its compatibility with specific equipment must be decided by the person who designs the equipment or decides its specifications based on necessary analysis and test results. The expected performance and safety assurance of the equipment will be the responsibility of the person who has determined its compatibility with the product. This person should also continuously review all specifications of the product referring to its latest catalogue information, with a view to giving due consideration to any possibility of equipment failure when configuring the equipment.

### **2. Only personnel with appropriate training should operate machinery and equipment.**

The product specified here may become unsafe if handled incorrectly. The assembly, operation and maintenance of machines or equipment including our products must be performed by an operator who is appropriately trained and experienced.

### **3. Do not service or attempt to remove product and machinery/equipment until safety is confirmed.**

1. The inspection and maintenance of machinery/equipment should only be performed after measures to prevent falling or runaway of the driven objects have been confirmed.
2. When the product is to be removed, confirm that the safety measures as mentioned above are implemented and the power from any appropriate source is cut, and read and understand the specific product precautions of all relevant products carefully.
3. Before machinery/equipment is restarted, take measures to prevent unexpected operation and malfunction.

### **4. Contact SMC beforehand and take special consideration of safety measures if the product is to be used in any of the following conditions.**

1. Conditions and environments outside of the given specifications, or use outdoors or in a place exposed to direct sunlight.
2. Installation on equipment in conjunction with atomic energy, railways, air navigation, space, shipping, vehicles, military, medical treatment, combustion and recreation, or equipment in contact with food and beverages, emergency stop circuits, clutch and brake circuits in press applications, safety equipment or other applications unsuitable for the standard specifications described in the product catalogue.
3. An application which could have negative effects on people, property, or animals requiring special safety analysis.
4. Use in an interlock circuit, which requires the provision of double interlock for possible failure by using a mechanical protective function, and periodical checks to confirm proper operation.

## Caution

### **1. The product is provided for use in manufacturing industries.**

The product herein described is basically provided for peaceful use in manufacturing industries.

If considering using the product in other industries, consult SMC beforehand and exchange specifications or a contract if necessary. If anything is unclear, contact your nearest sales branch.

## Limited warranty and Disclaimer/Compliance Requirements

The product used is subject to the following “Limited warranty and Disclaimer” and “Compliance Requirements”. Read and accept them before using the product.

### **Limited warranty and Disclaimer**

1. The warranty period of the product is 1 year in service or 1.5 years after the product is delivered, whichever is first.<sup>2)</sup> Also, the product may have specified durability, running distance or replacement parts. Please consult your nearest sales branch.
2. For any failure or damage reported within the warranty period which is clearly our responsibility, a replacement product or necessary parts will be provided. This limited warranty applies only to our product independently, and not to any other damage incurred due to the failure of the product.
3. Prior to using SMC products, please read and understand the warranty terms and disclaimers noted in the specified catalogue for the particular products.

2) Vacuum pads are excluded from this 1 year warranty.

A vacuum pad is a consumable part, so it is warranted for a year after it is delivered. Also, even within the warranty period, the wear of a product due to the use of the vacuum pad or failure due to the deterioration of rubber material are not covered by the limited warranty.

### **Compliance Requirements**

1. The use of SMC products with production equipment for the manufacture of weapons of mass destruction (WMD) or any other weapon is strictly prohibited.
2. The exports of SMC products or technology from one country to another are governed by the relevant security laws and regulations of the countries involved in the transaction. Prior to the shipment of a SMC product to another country, assure that all local rules governing that export are known and followed.

## Caution

### **SMC products are not intended for use as instruments for legal metrology.**

Measurement instruments that SMC manufactures or sells have not been qualified by type approval tests relevant to the metrology (measurement) laws of each country.

Therefore, SMC products cannot be used for business or certification ordained by the metrology (measurement) laws of each country.

## Safety Instructions

Be sure to read “Handling Precautions for SMC Products” (M-E03-3) before using.

## Revision History

<b>Edition B</b>	- The EtherNet/IP® communication protocol has been added. - An analog output unit and an input/output unit have been added. - A D-sub connector and a spring type terminal block have been added. - SY3000/5000 series valves have been added as applicable solenoid valves. - Number of pages has been decreased from 64 to 60.	OW
<b>Edition C</b>	- The EtherCAT® communication protocol has been added.	PX
<b>Edition D</b>	- The PROFINET communication protocol has been added.	RS
<b>Edition E</b>	- A dual port EtherNet/IP® product has been added. - SY7000 series valves have been added as applicable solenoid valves.	TS
<b>Edition F</b>	- The IO-Link Unit has been added. - JSY series valves have been added as connectable valves. --The "How to Order" and "Dimensions" pages of the connectable valves have been deleted. - An end plate (D side) and M12 (4/5 pins) A-coded power supply connectors have been added. - Number of pages has been decreased from 68 to 48.	YT
<b>Edition G</b>	- An IO-Link unit compatible SI unit has been added (PROFINET)	ZR

## SMC Corporation (Europe)

Austria	+43 (0)2262622800	www.smc.at	office@smc.at
Belgium	+32 (0)33551464	www.smc.be	info@smc.be
Bulgaria	+359 (0)2807670	www.smc.bg	office@smc.bg
Croatia	+385 (0)13707288	www.smc.hr	office@smc.hr
Czech Republic	+420 541424611	www.smc.cz	office@smc.cz
Denmark	+45 70252900	www.smcdk.com	smc@smcdk.com
Estonia	+372 6510370	www.smcpneumatics.ee	smc@info@smccee.ee
Finland	+358 207513513	www.smc.fi	smcfi@smc.fi
France	+33 (0)164761000	www.smc-france.fr	supportclient@smc-france.fr
Germany	+49 (0)61034020	www.smc.de	info@smc.de
Greece	+30 210 2717265	www.smchellas.gr	sales@smchellas.gr
Hungary	+36 23513000	www.smc.hu	office@smc.hu
Ireland	+353 (0)14039000	www.smcautomation.ie	sales@smcautomation.ie
Italy	+39 03990691	www.smcitalia.it	mailbox@smcitalia.it
Latvia	+371 67817700	www.smc.lv	info@smc.lv

Lithuania	+370 5 2308118	www.smclt.lt	info@smclt.lt
Netherlands	+31 (0)205318888	www.smc.nl	info@smc.nl
Norway	+47 67129020	www.smc-norge.no	post@smc-norge.no
Poland	+48 222119600	www.smc.pl	office@smc.pl
Portugal	+351 214724500	www.smc.eu	apoioclientept@smc.smces.es
Romania	+40 213205111	www.smcromania.ro	smcromania@smcromania.ro
Russia	+7 (812)3036600	www.smc.eu	sales@smc.com
Slovakia	+421 (0)413213212	www.smc.sk	office@smc.sk
Slovenia	+386 (0)73885412	www.smc.si	office@smc.si
Spain	+34 945184100	www.smc.eu	post@smc.smces.es
Sweden	+46 (0)86031240	www.smc.nu	smc@smc.nu
Switzerland	+41 (0)523963131	www.smc.ch	info@smc.ch
Turkey	+90 212 489 0 440	www.smcpnmatik.com.tr	info@smcpnmatik.com.tr
UK	+44 (0)845 121 5122	www.smc.uk	sales@smc.uk

South Africa +27 10 900 1233      www.smca.co.za      zasales@smca.co.za