# **3**M Cubitr⇒n<sup>™</sup> 3

Portable Bonded Wheels

# **Product Transition Guide**

A simple reference document to support the transition to a new upgraded range of products.

For over 40 years, 3M<sup>™</sup> Cubitron<sup>™</sup> Performance Abrasives have always delivered maximum productivity, but now the best have gotten even better! Introducing 3M<sup>™</sup> Cubitron<sup>™</sup> 3 Performance Abrasives — the next generation of awesome.

Our new product line uses groundbreaking advancements in precisionshaped grain to deliver 3X the performance in life and cut rate than ever before. Discover the difference with 3M<sup>™</sup> Cubitron<sup>™</sup> 3 Performance Abrasives and experience improvements in all areas of your shop through productivity, worker safety and sustainability.







Sustainability

# Our portable bonded wheels have evolved.

### 

Launched in 2012, this was the first range of cutting and grinding products using 3M's precision-shaped triangular grain abrasives.

This range will now be replaced by our latest and best offering.



# Cubitrn™ 3

Significantly raising the benchmark for cut rate and product life in heavy grinding and cutting applications.

We've re-engineered precisionshaped ceramic triangular grain using proprietary breakthroughs in **molecular bonding technology**.

## Up to 3X longer lasting.

Responding to industry requirements for better product productivity, worker safety and sustainability, 3M has developed abrasive wheel technologies that make portable bonded wheels work even faster and last even longer than our current best performing range. Performance is so good compared to existing 3M<sup>™</sup> Cubitron<sup>™</sup> II Performance Abrasives that we've established a new generation of products called 3M<sup>™</sup> Cubitron<sup>™</sup> 3 Performance Abrasives.

#### 3M<sup>™</sup> Cubitron<sup>™</sup> II Portable Bonded Wheels will be upgraded.

To maximize simplicity and value to our customers, the current 3M<sup>™</sup> Cubitron<sup>™</sup> II Portable Bonded Wheels range will be discontinued and replaced by 3M<sup>™</sup> Cubitron<sup>™</sup> 3 Performance Abrasives. Customers will benefit from a wider product choice, better performance and optimized sustainability with no change in list price.

#### What's New



#### 3M<sup>™</sup> Cubitron<sup>™</sup> 3 Cut and Grind Wheels

Here we've reformulated wheel composition to offer even better balance and a smoother action while maintaining best in class performance.



#### **Range Expansion**

We've added a 3.2mm option for applications requiring a thinner grinding profile. A thinner wheel also makes it grind faster too!



# **Product Transition Cross Reference Chart**

					-	Discontinued 3M <sup>™</sup> Cubitron <sup>™</sup> II Wheels		<b>Replacement</b> 3M <sup>™</sup> Cubitron <sup>™</sup> 3 Wheels	
	Wheel	Туре	Diameter (mm)	Thickness (mm)	Center Hole (mm)	Part No.	3M ID	Part No.	3M ID
		T27	100	6.0	16.00	66597	7000118427	99396	7100303984
	er els	T27	115	7.0	22.23	65510	7100074406	99306	7100303983
	Center Nheels	T27	125	7.0	22.23	65509	7100074405	98647	7100303982
	ΰÌ	T27	150	7.0	22.23	65492	7100074524	98452	7100303981
	ed	T27	180	7.0	22.23	65493	7100074407	98418	7100303980
	Depressed Center Grinding Wheels	T27	230	7.0	22.23	65494	7100074408	98291	7100303979
		Gouge Special Wheels							
	൭ഀൕ	T27	125	7.0	22.23		New!	43616	7100312955
	_	T27	150	7.0	22.23		New!	74433	7100303963
		T27	180	7.0	22.23		New!	97818	7100305453
		T27	100	3.2	22.23		New!	93314	7100305445
-	<u>s</u>	T27	115	3.2	22.23		New!	94159	7100305449
	Jee	T27	125	3.2	22.23		New!	93498	7100305448
	Grind Wheels	T27	150	3.2	22.23		New!	47563	7100305148
	פ	T27	180	3.2	22.23		New!	93473	7100305447
	i.	T27	230	3.2	22.23		New!	93395	7100305446
	р р	T27	100	4.2	22.23	81153	7100017401	95508	7100305450
	and (	T27	115	4.2	22.23	81157	7100017404	95344	7100303975
CONTRACT IN	Cut	T27	125	4.2	22.23	81149	7100017402	94946	7100303974
	O	T27	150	4.2	22.23	81152	7100017403	94888	7100303973
		T27	180	4.2	22.23	81148	7100017411	94542	7100303972
		T27	230	4.2	22.23	81154	7100017410	94343	7100303971
		T41	75	1.0	6.35	65450	7100094853	90230	7100303861
	<u>s</u>	T41	75	1.0	8.00	65170	7100094903	91045	7100304124
	hei	T41	75	1.0	9.53	65452	7100094854	90230	7100304121
	Cut-Off Wheels	T41	75	1.0	10.00	65171	7100094904	91045	7100304123
		T41	100	2.0	15.88	65501	7100228587	86997	7100303830
	Ļ	T41	115	0.8	22.23		New!	86581	7100304305
	Ö	T41	115	1.0	22.23	65513	7100094902	86616	7100304120
		T41	115	1.6	22.23	65454	7100231330	89573	7100304003
		T42	115	2.5	22.23	65472	7100228947	88383	7100303996
		T41	125	0.8	22.23		New!	86580	7100304127
		T41	125	1.0	15.88	65139	7100094908	47420	7100304303
		T41	125	1.0	22.23	65512	7100094901	86647	7100304306
		T41	125	1.0	22.23	91251	7100141201	86647	7100304306
		T41	125	1.3	22.23		New!	86457	7100304304
		T41	125	1.6	22.23		New!	86412	7100303829
		T41	125	2.0	22.23	65461	7100231343	88775	7100304000
		T42	125	2.5	22.23	65477	7100228958	87963	7100303995
		T42	125	3.0	22.23	65490	7100231332	87338	7100303831
		T41	150	1.6	22.23	65173	7100136996	90247	7100305353
		T41	150	2.0	22.23		New!	86542	7100304056
		T41	180	1.6	22.23	65456	7100136989	88912	7100305230
		T41	180	2.0	22.23	65462	7100136995	88768	7100303999
		T42	180	2.5	22.23	65479	7100136993	87396	7100303994
		T41	230	2.0	22.23	65463	7100136990	88732	7100303998
		T41	230	2.5	22.23	65471	7100136991	88404	7100303997
		T42	230	2.5	22.23	65481	7100136994	87378	7100303993
		T41	230	0.8	22.23	65487	7100136992	87671	7100303832







When will the new 3M <sup>™</sup> Cubitron <sup>™</sup> 3 Performance Abrasives replacement products be available?	3M <sup>™</sup> Cubitron <sup>™</sup> 3 Performance Abrasives will be available to our distribution partners from October 2023.
When will the discontinued 3M™ Cubitron™ II Performance Abrasives stop being supplied?	3M recommends switching to the new products as a priority as soon as they become available. Based on typical demand patterns, 3M anticipates stocks of some items will start to run out in November 2023.
How can customers access the new products to trial first?	Based on our own internal and field testing, most customers should be confident that running extensive testing should not be required. However, if a trial is required, please speak with your 3M Abrasives distributor.
Will the new upgraded 3M™ Cubitron™ 3 Performance Abrasives be sold at a higher price?	The country list prices will be similar to the existing 3M <sup>™</sup> Cubitron <sup>™</sup> II Performance Abrasives range.
Why has 3M introduced a special grinding wheel for gouging applications?	After listening to customers that do a lot of gouging and back grinding in their operations, the required performance parameters mean a dedicated product with a purpose made formulation optimized for this work. This helps deliver the high performance that 3M <sup>™</sup> Cubitron <sup>™</sup> 3 Portable Bonded Wheels represent.
Why won't 3M <sup>™</sup> Cubitron <sup>™</sup> II Performance Abrasives continue to be sold?	This helps with selection simplicity, which customers tell us is important. Thanks to the manufacturing technology advances we have made, the price/ performance differential between the two ranges means there is no need to retain the existing range.

#### Sustainability matters to 3M Abrasives.

When you buy from the SEAM value chain, you are helping to build a sustainable future for our industry, for people and for the planet.

3M is a founding member of the SEAM abrasives manufacturers program and aligns to the world's highest standards of quality, safety and performance in a sustainable environment. We commit to transparency, accountability, innovation and progress.

When buying from the SEAM value chain, customers are helping to build themselves a sustainable future.



Sustainable European Abrasive Manufacturers

Find out more at www.seam.earth



#### Learn more at 3M.com/Cubitron3Wheels



**3M Abrasive Systems** 3M Center, Building 223-6N-02 St. Paul, MN 55144 USA

1-866-279-1235 Phone Web 3M.com/abrasives

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application, iteraports is belowner is solely responsible for evaluating the product and etermining whether it is appropriate and suitable for customer's application, including conducting a myticate as result, customer is solely responsible for evaluating the product and etermining whether it is appropriate and suitable for customer's application, including conducting a myticate and particular is application including and applicate and particular is appropriate safety regulations, may result in injury, sickness, death, and/or harm to property. Disclaimer: 3M industrial and occupational products are intended, labeled, and packaged for sale to trained industrial and occupational customers for workplace use. Unless specifically stated otherwise on the applicable product packaging or literature, these products are intended, labeled, setting and use and used in compliance with applicable health and safety regulations and standards (e.g., US. CSHA, ANS), as well as all product literature, and must be selected and used in complication behavior asfety regulations and standards (e.g., US. CSHA, ANS), as well as all product information, workplace use, and must be applicable brother and settore subtractions, and ther limitations, and the user must take any action regulared under any recall, field action or other product use notice. Misuse of 3M product packaging or literature (in which case such or property damage. For help with product selection and use, consult your on-start safety professional, industrial and complication, and warranty owners). 3M warrants that each 3M product takes the applicable and product specification at the time 3M ships the product 3M product packaging or product literature (in which case such as warranty owners). 3M warrants that each 3M product takes the applicable 3M product specification at the time 3M ships the produc s at 3M sources of the profile of th