

# PC 621



by **Shurtape®**

## PROFESSIONAL GRADE, ALL-PURPOSE CLOTH DUCT TAPE

### TYPICAL APPLICATIONS

- For demanding HVAC applications to hold, seal and seam sheet metal and flex duct, exhaust vents and preformed insulation
- Also used in industrial applications for holding, splicing, protecting and packaging

### PRODUCT FEATURES

- Excellent tack, conformability and holding power
- Waterproof backing
- Easy to unwind and tear
- Will not twist or curl during application

### CONSTRUCTION

Overall Grade/Function: Professional

Backing: Waterproof polyethylene film with a cloth carrier

Adhesive: Natural rubber

### STANDARD WIDTH(S)

48 mm

### STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes

### STANDARD CORE SIZE

3 in

### APPLICABLE STANDARDS

Tested in accordance with UL 723

### STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

### COLOR(S)



**SILVER**  
(SIL)

PHYSICAL PROPERTIES	STANDARD	METRIC
---------------------	----------	--------

Tensile Strength	30 lbs/in width	52.5 N/10 mm
Adhesion to Stainless Steel	55 oz/in width	6.02 N/10 mm
Thickness	11 mils	0.28 mm
Elongation	18%	18%
Service Temperature Range	50 F to 200 F	10 C to 93 C

Physical and performance characteristics shown above are obtained from tests recommended by PTSC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent product specifications or a guarantee of product performance. Individual rolls may vary from these standards (or physical properties). The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.



With Globally Sourced Materials

