

TITAN Supersyn F Eco-FE SAE 0W-30

Ultra High Performance, extreme fuel-economy engine oil especially developed for modern Ford Diesel engines. Excellent cold starting and lower oil consumption.

Description

TITAN Supersyn F Eco-FE SAE 0W-30 is an extreme energy conserving multigrade passenger car engine oil suitable for modern Ford diesel engines. The result of the high quality base oils in combination with our most up to date additive technology is this ultra-high performance engine oil. The special composition of TITAN Supersyn F Eco-FE SAE 0W-30 ensures excellent aging stability, optimum wear protection and outstanding cold-start properties over the entire oil change interval and due to the optimized high temperature viscosity, TITAN Supersyn F Eco-FE SAE 0W-30 offers further potential for fuel savings and thus reduced CO₂ emissions.

Application

TITAN Supersyn F Eco-FE SAE 0W-30 has been developed for use in modern Ford diesel engines from model year 2014, which requires an oil according to the FORD WSS-M2C950-A specification. **TITAN Supersyn F Eco-FE SAE 0W-30 is not backward compatible with older Ford specifications!**

TITAN Supersyn F Eco-FE SAE 0W-30 is miscible and compatible with conventional branded engine oils. However, intermixtures with other engine oils should be avoided in order to fully utilize the product's benefits. Respectively a complete oil change is recommended when converting to TITAN Supersyn F Eco-FE SAE 0W-30. For information on product safety and proper disposal please refer to the latest Material Safety Data Sheet.

Advantages / Benefits

- Especially developed for modern Ford Diesel engines
- Outstanding cold-start properties
- Potential for fuel savings and thus reduced CO₂ emissions
- Suitable for extended oil change intervals
- Optimum wear protection

Specifications

- ACEA C2
- FORD WSS-M2C950-A

Approvals

- JAGUAR LAND ROVER STJLR.03.5007

FUCHS Recommendations

- -

TITAN Supersyn F Eco-FE SAE 0W-30

Handling and storage

Avoid skin contact. In the event of contact with skin, wash with soap and water. Dispose of used oil at a recycling station or equivalent. Safety data sheets are available on www.fuchs.com/se or supplied on request.

Typical data

Characteristics	Method	Value
Density at 15°C	DIN 51757	0.843 g/ml
SAE grade	SAE J300	0W-30
Kinematic Viscosity at 40°C	DIN 51562-1	45.8 mm ² /s
Kinematic Viscosity at 100°C	DIN 51562-1	9.6 mm ² /s
Viscosity Index	DIN ISO 2909	201
HTHS	CEC L-036-90	≥ 2.9 mPa*s
Pour Point	DIN ISO 3016	-45°C
Sulphated ash	ASTM D874	≤ 0.8 % m/m
Product dyeing	DIN 10964	none

The information contained in this product information is based on the experience and know-how of FUCHS in the development and manufacturing of lubricants and represents the current state-of-the-art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pre-treatment, possible external contamination, etc. For this reason, universally-valid statements about the function of our products are not possible. The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application.

We therefore recommend that you consult a FUCHS LUBRICANTS SWEDEN AB application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care.

Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without warning, unless otherwise provided in customer-specific agreements. With the publication of this product information, all previous editions cease to be valid.

Any form of reproduction requires express prior written permission from FUCHS LUBRICANTS SWEDEN AB
© FUCHS LUBRICANTS SWEDEN AB. All rights reserved.