



Reducing field installation time and improving effectiveness

DSG-Canusa brand kits combine a variety of different sizes, diameters and colours of our specially designed heat shrink tubing. Our sets are a convenient solution for distributors and craftsmen.

FEATURES AND BENEFITS

- Great selection of different diameters and colors suitable for various applications
- Refillable compartments
- Universal flame retardant flexible thin wall heat shrink
- Ready-to-use sections
- Customized sets available on request
- Shrink ratio: 2:1
- Continuous operating temperature: -55°C to 135°C
- Shrink temperature: 110°C min.

STANDARDS

- UL224

TYPICAL APPLICATIONS

- Electrical repair and maintenance
- Strain relief
- Insulation

2:1 & 3:1
SHRINK RATIO

-55°C to 135°C
(-67°F to 275°F)
CONTINUOUS OPERATING
TEMPERATURE

MARKETS:

Industrial, Commercial

STANDARDS:



DERAY®-SET SIX

DESCRIPTION

Small assortment box with flame retardant thin wall heat shrinkable tubing in different diameter and colors which allows use for various application.

STANDARD CONTENT

Ø 12-0.6 L: 50 mm 60 pcs blue, gray, black, brown	Ø 2.4-12 L: 50 mm 30 pcs blue, gray, black, brown	Ø 4.8-2.4 L: 50 mm 16 pcs blue, gray, black, brown	Ø 9.5-4.8 L: 50 mm 8 pcs blue, gray, black, brown	Ø 19.0-9.5 L: 50 mm 4 pcs blue, gray, black, brown	Ø 38.0-19.0 L: 50 mm, 1 pcs yellow-green
---	---	--	---	--	---



DERAY®-SET 2000

DESCRIPTION

Big assortment box with flame retardant thin wall heat shrinkable tubing in different diameter and colors which allows use for various application.

STANDARD CONTENT

Ø 12-0.6 L: 40 mm 125 pcs black, yellow, white, red, blue	Ø 16-0.8 L: 40 mm 125 pcs black, yellow, white, red, blue	Ø 2.4-12 L: 40 mm 125 pcs black, yellow, white, red, blue	Ø 3.2-16 L: 40 mm 80 pcs black, yellow, white, red, blue	Ø 4.8-2.4 L: 40 mm 40 pcs black, yellow, white, red, blue	Ø 6.4-3.2 L: 40 mm 20 pcs black, yellow, white, red, blue
Ø 12-0.6, L: 250 mm, 5 pcs, blue Ø 16-0.8, L: 250 mm, 5 pcs, red Ø 3.2-16, L: 250 mm, 5 pcs, blue			Ø 4.8-2.4, L: 250 mm, 5 pcs, yellow Ø 6.4-3.2, L: 250 mm, 5 pcs, black Ø 9.5-4.8, L: 250 mm, 5 pcs, black		
Ø 9.5-4.8, L: 250 mm, 4 pcs, yellow Ø 9.5-4.8, L: 250 mm, 4 pcs, red Ø 9.5-4.8, L: 250 mm, 4 pcs, blue			Ø 12.5-6.4, L: 250 mm, 3 pcs, yellow Ø 12.5-6.4, L: 250 mm, 3 pcs, red Ø 12.5-6.4, L: 250 mm, 3 pcs, blue		



DERAY®-SET 5000

DESCRIPTION

Assortment box with crimp connectors and flame retardant thin wall heat shrink tubing with shrink ratios 2:1 and 3:1.

STANDARD CONTENT

Crimp connector red - AWG 22-18 / 0.5-1.5mm² - 20 pieces Crimp connector blue - AWG 16-14 / 1.5-2.5mm² - 20 pieces Crimp connector yellow - AWG 12-10 / 4-6mm² - 5 pieces Crimp connector clear - AWG 28-22 / 0.1-0.5mm² - 5 pieces					
Ø 16-0.8 L: 70 mm 28 pcs blue, gray, black, brown	Ø 2.4-12 L: 70 mm 28 pcs blue, gray, black, brown	Ø 3.2-16 L: 70 mm 20 pcs blue, gray, black, brown	Ø 4.8-2.4 L: 70 mm 16 pcs blue, gray, black, brown	Ø 6.4-3.2 L: 70 mm 12 pcs blue, gray, black, brown	Ø 6.4-2.0 L: 70 mm, 5 pcs Ø 3.2-1.0 L: 70 mm 5 pcs yellow-green