

Unparalleled Performance For 30 Years

TAPE Dispensers

Electronic



zcM1000

Electronic Tape Dispenser

- Ideal for medium to high production of repetitive taping for industrial applications
- Program a defined length and automatically advance and cut tape
- Accepts tape widths from .28" to 2" (7 to 51mm)
- Cuts tape lengths from .79" to 39" (20 to 999mm)
- Made in Japan



Previous Model

Features

3-IN-1 CORE HOLDER

EASY TO OPERATE



Applications



Additional info for zcM1000

- Photocell actuated feed & cut or push-button feed & cut
- Guillotined cut for a straight edge piece of tape
- LED Digital length adjustment
- Manual override of preset lengths
- Blades good for up to 200,000 cuts (dependent on type of material)
- Steel frame for durability
- Cabinet made from flame retardant antistatic composite (auto ignition of 896° F/ 480°C)
- Comes with a 3-in-1 core (1" (25mm), 1.4" (35mm), 3" (76mm))
- Adjustable pressure roller for various thicknesses of tape
- Accuracy of tape length is +/- .04" (1mm) (dependent on type of material)
- Many available accessories fit this machine. See Accessories section.
- All 230V machines are CE Certified



Accessory Options

See page 30 or visit www.STARTinternational.com/TD/Accessories

Visit www.STARTinternational.com/Videos to see our dispensers in action.

For 230V machines, please add "-2" to the end of the model number. (Example: zcM1000-2)

MODEL #	Tape Width	Cut Length	Max. Outside Dia. of Roll	3-in-1 Core Holder	Accuracy of Cut**	Length Setting	Weight	Dimensions
zcM1000	.28 to 2.0" (7 to 51mm)	.79 to 39" (20 to 999mm)	7" (178mm)	1", 1.4", 3" (25, 35, 76mm)	+/- .04" (1mm)	digital (LED)	5.3 lbs (3.4 kg)	9.7"(L) x 5.4"(W) x 5.9"(H) 24.5cm(L) x 13.7cm(W) x 15cm(H)

Electrical requirements: 117V 50/60Hz, <1 amp (230V 50/60Hz CE available) ** dependent on material