

# BOAT SANITARY HOSE



**MARINE  
EQUIPMENT**

Boat equipment  
Water



## APPLICATIONS

Effluent hose for leisure boat toilet systems.

## ADVANTAGES

- Flexible.
- Kink resistant.
- Diffusion tight (will not be tainted by odour from the toilet system).


## TECHNICAL DESCRIPTION

Inner tube: chlorobutyl, black, smooth.

Reinforcement: synthetic textile with embedded steel helix.

Cover: EPDM, white, fabric impression.

Temperature range: -30 °C to +100 °C.



**MARINE EQUIPMENT****BOAT SANITARY HOSE**

ID mm	OD mm	WORKING PRESSURE bar	BURSTING PRESSURE bar	MAX. VACUUM bar	BENDING RADIUS mm	WEIGHT kg/m	LENGTH m	ARTICLE NUMBER	STOCK ( ) or min. order m
16.0	27.0 ±1.0	10	32	0.9	64	0.54	20	59013247	200
16.0	27.0 ±1.0	10	32	0.9	64	0.54	40	59013248	200
20.0	31.0 ±1.0	10	32	0.9	80	0.63	20	59013249	200
20.0	31.0 ±1.0	10	32	0.9	80	0.64	40	59013250	1
25.0	36.0 ±1.0	10	32	0.9	100	0.75	20	59013251	200
25.0	36.0 ±1.0	10	32	0.9	100	0.75	40	59013252	200
32.0	43.0 ±1.0	10	32	0.9	130	0.94	20	59013253	200
32.0	43.0 ±1.0	10	32	0.9	130	0.94	40	59013254	200
38.0	49.0 ±1.0	10	32	0.9	160	1.1	40	59013308	1

Tolerance on length: ±1% (ISO 1307 Standard).

Digital version



**TRELLEBORG**

[WWW.TRELLEBORG.COM/FLUIDHANDLING](http://WWW.TRELLEBORG.COM/FLUIDHANDLING)