

# TRELLVAC Extractor LD

CONSTRUCTION & ENVIRONMENT  
Evacuation and material handling hoses



## Applications

Universal ducting hose for dust, wood chips, small particles and various types of gas.

## Advantages

- n Light and flexible.
- n Excellent bending radius.
- n Especially useful when low weight and easy handling are valued.

## Technical description

Inner tube: wear resistant SBR/NR, black, smooth.

Reinforcement: synthetic textile with embedded steel helix.

Cover: wear and weather resistant SBR/NR, black, corrugated.

Temperature range: - 40 °C to + 90 °C.

Electrical properties: conductive tube and cover,  $R < 10^6 \Omega/m$ .



Complementary information  
OD measured on top of corrugation.



# TRELLVAC Extractor LD

12/01/2012

| ID<br>mm |       | OD<br>mm |       | Max. vacuum<br>bar | Bending radius<br>mm | Weight<br>kg/m | Length<br>m | Article number | Stock (n) or min.<br>order<br>m |
|----------|-------|----------|-------|--------------------|----------------------|----------------|-------------|----------------|---------------------------------|
| 38       | ± 1.5 | 43       | ± 1.0 | 0.9                | 45                   | 0.48           | 12          | 0025890        | n                               |
| 51       | ± 1.5 | 56       | ± 1.0 | 0.9                | 70                   | 0.63           | 12          | 0025908        | n                               |
| 63       | ± 1.5 | 68       | ± 1.0 | 0.9                | 95                   | 0.72           | 12          | 0025916        | n                               |
| 76       | ± 1.5 | 81       | ± 1.0 | 0.9                | 115                  | 0.86           | 12          | 0025932        | n                               |
| 90       | ± 1.5 | 96       | ± 1.0 | 0.9                | 125                  | 1.01           | 12          | 0025965        | n                               |
| 102      | ± 1.5 | 108      | ± 1.0 | 0.9                | 145                  | 1.32           | 12          | 0025973        | n                               |
| 113      | ± 1.5 | 120      | ± 1.0 | 0.9                | 155                  | 1.46           | 12          | 0025981        | n                               |
| 127      | ± 1.5 | 134      | ± 1.0 | 0.7                | 170                  | 1.63           | 12          | 0026005        | n                               |
| 152      | ± 1.5 | 159      | ± 1.0 | 0.4                | 195                  | 1.94           | 12          | 0026013        | n                               |
| 178      | ± 1.5 | 185      | ± 1.0 | 0.25               | 220                  | 2.28           | 12          | 0026021        | 12                              |
| 204      | ± 1.5 | 211      | ± 1.0 | 0.15               | 245                  | 2.58           | 12          | 0026039        | n                               |

Branding



Trelleborg Industrie SAS - ZI La Combaude - Rue de Chantemerle - 63050 Clermont-Ferrand Cedex 2 - France  
www.trelleborg.com/industrialhose