

MARINEFLEX 2W ISO 13363 TYPE 2 CLASS B

SUCTION AND DELIVERY HOSE FOR WATER AND EXHAUST GASSES ON LEISURE BOATS



APPLICATION

Suction and delivery hose for cooling water and exhaust gasses, for marine engines installed on leisure boats

TUBE

Black, smooth **NBR/PVC** rubber compound

REINFORCEMENT

High strength synthetic plies with steel wire spirals

COVER

Black, corrugated, cloth impression **CR** rubber compound, self extinguishing, resistant to heat, fuels, and weather

WORKING TEMPERATURE

-22°F +248°F

-30°C +120°C

SPECIFICATIONS

ISO 13363 2B, RINA DIPXXXXXXX approved

ID		WEIGHT	WP		BP		BENDING RADIUS	VACUUM	COIL LENGTH
mm	inch	kg/m	bar	psi	bar	psi	mm	bar	m
25	1	0.58	3	45	10	150	80	0.7	10/20/40
30	1 3/16	0.69	3	45	10	150	95	0.7	10/20/40
35	1 3/8	0.83	3	45	10	150	112	0.7	10/20/40
40	1 37/64	0.93	3	45	10	150	155	0.7	10/20/40
45	1 25/32	1.10	3	45	10	150	165	0.7	10/20/40
51	2	1.17	3	45	10	150	175	0.7	10/20/40
55	2 11/64	1.28	3	45	10	150	195	0.7	10/20/40
60	2 23/64	1.35	3	45	10	150	215	0.7	10/20/40
70	2 3/4	1.74	3	45	10	150	260	0.7	10/20/40
76	3	1.98	3	45	10	150	280	0.7	10/20/40
80	3 5/32	2.15	3	45	10	150	300	0.7	10/20/40
90	3 35/64	2.60	3	45	10	150	350	0.7	10/20/40
102	4	3.00	3	45	10	150	400	0.7	10/20/40
127	5	3.80	3	45	10	150	550	0.7	10/20/40
130	5 1/8	3.90	3	45	10	150	590	0.7	10/20/40
152	6	4.40	3	45	10	150	760	0.7	10/20/40
203	8	7.10	3	45	10	150	1000	0.7	10/20/40

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

