

WELBLU 20 ISO 3821 L/L

WELDING HOSE - OXYGEN AND ARGON



APPLICATION

Delivery hose, oxygen line in welding equipments

TUBE

Black, smooth, **SBR** rubber compound

REINFORCEMENT

High strength synthetic plies

COVER

Blue, smooth, **SBR/EPDM** rubber compound, abrasion and weather resistant







WORKING TEMPERATURE

-13°F +176°F

-25°C +80°C

SPECIFICATIONS

ISO 3821

									
ID		OD		WEIGHT	WP		BP		COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	m
6	1/4	13	1/2	0.16	20	300	60	900	100
8	5/16	15	19/32	0.18	20	300	60	900	100
9	23/64	16	5/8	0.20	20	300	60	900	100
10	3/8	17	43/64	0.21	20	300	60	900	100
13	1/2	23	29/32	0.40	20	300	60	900	50
16	5/8	26	1 5/16	0.53	20	300	60	900	50
19	3/4	30	1 3/16	0.62	20	300	60	900	50
25	1	37	1 29/64	0.86	20	300	60	900	50

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

TGT WELBLU W.P. 20 BAR ISO3821 ITALY