


INDUSTRIAL RUBBER PRODUCTS



REACH

MECHANICAL	Standard	Value	
Rubber compound		SBR/NR	
Density	ASTM D3575	1.50 +/-0.05	g/cm3
Hardness	ASTM D2240	70 ⁰ +/-5	Shore A
Tensile strength	ISO 37	3	MPa
Elongation at break	ISO 37	≥ 200	%
Tear resistance		0	N/mm
Compression set after 24h at 70°C		0	%

TEMPERATURE

Working temperature -30°C - +80°C

AGEING

Δ Hardness	0	%
Δ Tensile	0	N/mm
Δ Elongation at break	0	%

OIL RESISTANCE

Oil IRM 901, Δ volume after 72h at 100°C	0	%
Oil IRM 903, Δ volume after 72h at 100°C	0	%

CHEMICAL RESISTANCE

Diluted acids and bases	Medium
Concentrated acids and basis	Non suitable
Ozone and UV	Medium
Oils and hydrocarbons	Non suitable

DIMENSIONS

SKU	Thickness (mm)	Width (mm)	Length (m)	Inserts	Execution
4601000140	1	1400	20	0	2 sides smooth
4601500140	1,5	1400	15	0	2 sides smooth
4601510140	1,5	1400	15	1	2 sides smooth
4602000120	2	1200	10	0	2 sides smooth
4602000140	2	1400	10	0	2 sides smooth
4602010120	2	1200	10	1	2 sides smooth
4602010140	2	1400	10	1	2 sides smooth