

Nitril 150

NBR/SBR

Product features

- NBR/SBR, black
- Good quality for reasonable price
- Both sides smooth



Product specifications

• Colour	Black
• S.G. grs/cm ³	1.40
• Hardness °Shore A ± 5° (DIN 53519)	65
• Tensile strength MPa (DIN 53504)	5
• Elongation % (DIN 53504)	≥ 250
• Abrasion Resistance mm ³ (DIN 53516)	-
• Compression set % (DIN 53517)	-
• Tear Strength kN/m (DIN 53507)	≥ 17
• Temperature °C	-20/+80
• Change of volume	
o Oil ASTM nr 5 (72H/70°C)	-
o Oil IRM 903 (72H/70°C)	-

Sheeting

- After ageing - Hardness °Shore A (72H/70°C) - Tensile strength (72H/70°C) - Elongation (72H/70°C)	- - -
- Resistance to - Ozone - Diluted acids - Concentrated acids - Oil - Solvents	Not applicable Good Not applicable Satisfactory Satisfactory

Product versions

Colour	Thickness/ mm	Width / m	Length / m	Insertions
Black	1	1.40	10	0
Black	1.5	1.40	10	0
Black	1.5	1.40	10	1
Black	2	1.40	10	0
Black	2	1.40	10	1
Black	3	1.40	10	0
Black	3	1.40	10	1
Black	3	1.40	10	2
Black	4	1.40	10	0
Black	4	1.40	10	1

Sheeting

Black	4	1.40	10	2
Black	5	1.40	10	0
Black	5	1.40	10	2
Black	6	1.40	10	0
Black	6	1.40	10	2
Black	8	1.40	5	0
Black	8	1.40	5	2
Black	10	1.40	5	0
Black	10	1.40	5	2
Black	12	1.40	5	0
Black	15	1.40	5	0
Black	20	1.40	5	0