

## **Declaration of Compliance**

**Business Operator** 

Vikan A/S Rævevej 1 DK-7800 Skive (+45) 96 14 26 00

**Product name** 

Cleaning set w/3 Brushes, Ø2, Ø6, Ø6 mm, 150 mm, Soft, Blue

Item Number 53623

**Bristles** 

Polybutylene terephthalate (PBT)

Stainless steel

The stainless steel twisted wire is made from stainless steel Grade 1.4301 (AISI 304)

## **EU Compliance**

Regulation (EC) No 1935/2004

In accordance with EU Commission Regulation no. 1935/2004 the product is intended for food contact. The product is marked with the "glass & fork" symbol on the packaging or on the product itself through moulding.

The stainless steel complies with the French national requirements regarding composition of stainless steel, as defined in "Arrêté du 13 janvier 1976 relatif aux matériaux et objets en acier inoxydable au contact des denrées alimentaires." the specification for stainless steel in the DGCCRF "Fiche MCDA n"1 (V02 - 0I/04/2017) titled food contact suitability of metals and alloys".



Regulation (EC) No 2023/2006

The product is produced according to EU Commission Regulation no. 2023/2006 of 22. December 2006 on good manufacturing practices for materials and articles intended to come into contact with food (GMP).

Regulation (EU) No 10/2011

Monomers and intentionally added additives used to manufacture this product are listed in Annex I of Commission Regulation (EU) No. 10/2011 of 14. January 2011 on plastic materials and articles intended to come into contact with foodstuffs. Subsequent amendments up to (EU) 2024/3190 are included.

Monomers and/or additives with specific migration limit (SML) are used. The substances with a SML will not migrate in quantities that will exceed the SML, under the specified conditions of use. Upon request we will supply relevant information regarding these substances on a confidential basis.

Vikan A/S does not use multi-layer materials or articles with a functional barrier.

Regulations (EC) No 1333/2008 and (EC) No 1334/2008

This material contains intentionally added "dual use" additives for which restrictions or purity criteria are in place in accordance with Regulations (EC) 1333/2008 and (EC) 1334/2008. Upon request we will supply relevant information regarding these substances on a confidential basis.



US FDA Compliance All raw materials in this product are in compliance with FDA (Food and Drug

Administration in the USA) 21 CFR parts 170 to 199.

**UK Compliance** The product complies with The Materials and Articles in Contact with Food (Amendment)

(EU Exit) Regulations 2019 No. 704

**Danish Compliance** The product complies with the Danish consolidation Act no. 681 of 25/05/2020.

Migration analysis plastics Samples of the product, or a similar product made from identical plastic material, have

been tested for overall migration according to the test conditions specified in (EU) 10/2011 for repeated use, and the article comply with the overall migration limit of 10

mg/dm<sup>2</sup> or 60 mg/kg.

Test conditions for overall migration were OM3 (2 h at 70 °C)

Food simulants used for overall migration were 10 % ethanol (simulant A), 3 % acetic acid

(simulant B) and olive oil (simulant D2).

Compliance with specific migration limits, and other restrictions, has been documented

through testing, calculation or simulation.

Test conditions for specific migration was 30 min at 80 °C

Max ratio of food contact surface

area to volume

2.1 dm<sup>2</sup>/100 ml

Food contact types The product is suitable for contact with the following types of food under the intended and

foreseeable conditions of use:

✓ Aqueous

✓ Acidic

✓ Alcoholic

√ Fatty

✓ Dry

Food contact usage time and

temperature

Any food contact conditions up to 80 °C for 30 min

Non-food contact usage

temperature

Minimum temperature: -20 °C Maximum temperature: 100 °C



## General

Equipment should be cleaned, disinfected and sterilised, as appropriate to it's intended use, before use.

It is also important to clean, disinfect and sterilise equipment as appropriate after use, using the appropriate decontamination chemicals, concentrations, times and temperatures.

Appropriate equipment decontamination will minimise the risk of microbial growth and cross contamination and will maximise the efficiency and durability of the equipment.

Recommended sterilisation temperature (Autoclave): 121 °C

We will make the relevant background documentation available to the competent authorities, at their request.

Vikan A/S is registered with the Danish Veterinary and Food Administration (DVFA), and our mandatory Own Control System is subject to inspection by the DVFA.

**Date** 

Made By

2/23/2025

Kim Gerhardt Aakermann

Materials & Compliance Specialist