



Model No. 9125-1000
 Max. Pressure 1000 PSI
 Max. Flow Rate 2.0 GPM
 Max. Spray Length 100 ft.
 Max. Spray Width 10 ft.
 Max. Spray Height 10 ft.
 Max. Spray Depth 10 ft.
 Max. Spray Area 100 sq. ft.
 Max. Spray Volume 1000 GPM
 Max. Spray Pressure 1000 PSI
 Max. Spray Temperature 100°F
 Max. Spray Duration 100 min.
 Max. Spray Weight 100 lbs.
 Max. Spray Length 100 ft.
 Max. Spray Width 10 ft.
 Max. Spray Height 10 ft.
 Max. Spray Depth 10 ft.
 Max. Spray Area 100 sq. ft.
 Max. Spray Volume 1000 GPM
 Max. Spray Pressure 1000 PSI
 Max. Spray Temperature 100°F
 Max. Spray Duration 100 min.
 Max. Spray Weight 100 lbs.

- Räkän lukitusmekanismi kestää kiristysten aikana muodostuvat voimat momenttialueella, jolla työskentely on aiemmin ollut vaikeaa, vaarallista tai jopa mahdotonta.
- Liukupisteellä varustettu reaktiolevy mahdollistaa parhaan reaktiopisteen valitsemisen käsillä olevaan työhön+C5
- Momenttialue 9 500 Nm:iin saakka
- Käytä aina momenttiavaimen kanssa (myötä- ja vastapäivään), jotta momentinmuuntimen suurin sallittu momentti ei ylitä

- Tarkkuus $\pm 4\%$
- Toimitetaan kannettavassa kangaspussissa
3 400 Nm:n malliin saakka ja sitä suuremmat mallit
kovassa kotelossa
- Valmistettu Englannissa



TUOTEATTRIBUUTIT

Tuote: 9525-3400

	3400 N·m		1/2 in		27:1
	125 N·m		1 in		119 mm
	132 mm		355 mm	R2 min mm	86 mm
R2 max mm	263 mm		10.000 kg		

Tuote: 9625-9500

	9500 N·m		3/4 in		27:1
	351 N·m		1.1/2 in		184 mm
	162 mm		448 mm	R2 min mm	175 mm
R2 max mm	351 mm		25.700 kg		

Follow the Fish!

