



Printing date 23.01.2025 Version number 1 Revision: 23.01.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Redwing HD Tyre Sealant
- · Registration number Mixture
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Product category PC1 Adhesives, sealants
- · Application of the substance / the mixture Puncture-proofing tyre sealant for low speed applications.
- · Uses advised against The product is stictly intended for industrial or professional use only.
- · 1.3 Details of the supplier of the safety data sheet
- · Supplier:

Redstone (Tyres) Ltd

South Yard, Ford Lane, Arundel

West Sussex BN18 0DF

Tel: +44 (0)1243 558959 Email: sales@redstoneuk.com

- · Further information obtainable from: Product safety department.
- · 1.4 Emergency telephone number:

Members of the public seeking specific information on poisons should contact:

In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to GB-CLP The product is not classified, according to the GB CLP regulation.
- · 2.2 Label elements
- · Labelling according to GB-CLP Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void
- · Additional information:

EUH210 Safety data sheet available on request.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:			
CAS: 107-21-1	Ethanediol	♦ STOT RE 2, H373; ♦ Acute Tox. 4, H302	2.5 – < 10%
EINECS: 203-473-3			
Index number: 603-027-00-1			
Reg.nr.: 01-2119456816-28-XXXX			

· Additional information: For the wording of the listed hazard phrases refer to section 16.





Printing date 23.01.2025 Version number 1 Revision: 23.01.2025

Trade name: Redwing HD Tyre Sealant

(Contd. of page 1)

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eve contact:

Check for and remove any contact lenses.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Wash mouth out with water

Do not induce vomiting; call for medical help immediately.

If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

· Information for doctor:

Contains ethanediol.

If ingested, early diagnosis and treatment is essential.

Refer to section 11.

Treat symptomatically and supportively.

- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire extinguishing methods suitable to surrounding conditions.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- · 5.3 Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

Wear fully protective suit.

· Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Particular danger of slipping on leaked/spilled product.

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Do not allow to penetrate the ground/soil.

Do not allow product to reach sewage system or any water course.

(Contd. on page 3)





Printing date 23.01.2025 Version number 1 Revision: 23.01.2025

Trade name: Redwing HD Tyre Sealant

(Contd. of page 2)

· 6.3 Methods and material for containment and cleaning up:

Contain and collect spillage with non-combustible, absorbent material e.g.sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Avoid direct contact (skin/eye contact, ingestion and/or inhalation of fume/mist/dust) with the product in the undiluted form.

- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Prevent any seepage into the ground.
- · Information about storage in one common storage facility: Store away from oxidising agents.
- Further information about storage conditions: Store in cool, dry conditions in well sealed receptacles.
- · Storage class: 12
- \cdot 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredien	· Ingredients with limit values that require monitoring at the workplace:		
CAS: 107	CAS: 107-21-1 Ethanediol		
	WEL Short-term value: 104** mg/m³, 40** ppm		
	Long-term value: 10* 52** mg/m³, 20** ppm		
Sk ³	Sk *particulate **vapour		
· DNELs	· DNELs		
CAS: 107	CAS: 107-21-1 Ethanediol		
Dermal	Dermal Long-term systemic effects 53 mg/kg bw/day (general population)		
		106 mg/kg bw/day (worker)	
Inhalative	Long-term local effects	7 mg/m³ (general population)	
		35 mg/m³ (worker)	

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Take note of assigned Workplace Exposure Limits.

Avoid contact with the eyes and skin.

Do not eat or drink while working.

Wash hands before breaks and at the end of work.





Printing date 23.01.2025 Version number 1 Revision: 23.01.2025

Trade name: Redwing HD Tyre Sealant

(Contd. of page 3)

Do not carry product impregnated cleaning cloths in trouser pockets.

- **Respiratory protection:** When dust/mist are present use a Particulate filter, type P2.
- · Hand protection



Protective gloves.

Use gloves tested and approved under appropriate government standards such as NIOSH (US) or EN374

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

PVC gloves

Natural rubber, NR

Neoprene gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Safety glasses with side-shields conforming to EN166.

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

· Body protection:



Protective work clothing

Body protection must be chosen depending on product properties, activity and possible exposure.

· Environmental exposure controls Do not allow to enter drains, sewers or watercourses.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Liquid · Colour: Pale blue/green Characteristic · Odour: · Odour threshold: Not determined. · Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and boiling range 100 °C (CAS: 7732-18-5 Water)

· Flammability

Not applicable.

· Lower and upper explosion limit

· Lower: Not determined. · Upper: Not determined. · Flash point: Not applicable. · Decomposition temperature: Not determined.

· pH at 20 °C

· Viscosity:

· Kinematic viscosity Not determined.

(Contd. on page 5)





Printing date 23.01.2025 Version number 1 Revision: 23.01.2025

Trade name: Redwing HD Tyre Sealant

(Contd. of page 4)

	(Contain of Page 1)
· Dynamic:	Not determined.
· Solubility	
· water:	Partly soluble.
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure:	Not determined.
· Density and/or relative density	
· Density at 20 °C:	1.05 g/cm^3
· Relative density	Not determined.
· Vapour density	Not determined.
· 9.2 Other information	
· Appearance:	
· Form:	Liquid
· Important information on protection of health an	ıd
environment, and on safety.	
Ignition temperature:	Product is not self-igniting.
· Explosive properties:	Product does not present an explosion hazard.
· Solvent content:	•
· VOC (EC)	0.00 %
Change in condition	
· Evaporation rate	Not determined.
· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gas	es
in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- \cdot 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid Heat and static discharge.
- \cdot 10.5 Incompatible materials:

Strong acids.

Strong bases.

Strong oxidising agents.





Printing date 23.01.2025 Version number 1 Revision: 23.01.2025

Trade name: Redwing HD Tyre Sealant

(Contd. of page 5)

· 10.6 Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Toxic fumes and gases

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:		
CAS: 1	CAS: 107-21-1 Ethanediol	
Oral	LD50	7,712 mg/kg (rat)
Dermal	LD50	3,500 mg/kg (mouse)

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eve damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · Subacute to chronic toxicity: Prolonged or repeated skin contact may irritate and cause dermatitis.
- · Additional toxicological information:

Contains ethanediol. Ingestion of large quantities may cause damage to the kidneys.

· 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients are listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

CAS: 107-21-1 Ethanediol

EC50 (96 h) > 100 mg/l (Bacteria)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential Product is not expected to bioaccumulate.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties The product does not contain substances with endocrine disrupting properties.
- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.





Printing date 23.01.2025 Version number 1 Revision: 23.01.2025

Trade name: Redwing HD Tyre Sealant

(Contd. of page 6)

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Recommended Hierarchy of Controls:

- Minimise waste;
- Reuse if not contaminated;
- Recycle, if possible; or
- Safe disposal (if all else fails).

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact waste processors for recycling information.

Used, degraded or contaminated product may be classified as hazardous waste. Anyone classifying hazardous waste and determining its fate must be qualified in accordance with state and international legislation.

- · Uncleaned packaging:
- · Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning. Disposal must be made according to official regulations.

Containers, even those that are "empty," may contain residues that can develop flammable and/or hazardous vapours upon heating. Do not cut, drill, grind, weld, or perform similar operations on or near empty containers.

· Recommended cleansing agents: Water, if necessary together with cleansing agents.

SECTION 14: Transport information

· 14.1 UN number or ID number · ADR/RID/ADN, IMDG, IATA	Not applicable	
· 14.2 UN proper shipping name · ADR/RID/ADN, IMDG, IATA	Not applicable	
· 14.3 Transport hazard class(es) · ADR/RID/ADN, ADN, IMDG, IATA · Class	Not applicable	
· 14.4 Packing group · ADR/RID/ADN, IMDG, IATA	Not applicable Not applicable	
· 14.5 Environmental hazards:	Not applicable.	
· 14.6 Special precautions for user	Not applicable.	
· 14.7 Maritime transport in bulk according to IMO instruments Not applicable.		
· UN "Model Regulation":	Not applicable	

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act

· Regulated explosives precursors	
None of the ingredients are listed.	

(Contd. on page 8)





Printing date 23.01.2025 Version number 1 Revision: 23.01.2025

Trade name: Redwing HD Tyre Sealant

(Contd. of page 7)

· Regulated poisons

None of the ingredients are listed.

· Reportable explosives precursors

None of the ingredients are listed.

· Reportable poisons

None of the ingredients are listed.

- · Control Of Major Accident Hazards Regulations 2015 (COMAH)
- · Named dangerous substances ANNEX I None of the ingredients are listed.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This Safety Data Sheet is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

· Relevant phrases

H302 Harmful if swallowed.

H373 May cause damage to organs through prolonged or repeated exposure.

· Department issuing SDS: Product safety department.

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

ATE: Acute toxicity estimate values

Acute Tox. 4: Acute toxicity - Category 4

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

* Data compared to the previous version altered.