

# Technical Data Sheet

**Product:** **ADHESIVE NET PAPER (4610)**

**Product Description:** **Double sided tape**

**Adhesive:** The NH is a solvent free modified acrylic adhesive with a high initial tack and high peel strength on most surfaces, even on those with a low surface energy. .

<b>Product structure:</b>	<b>Support</b>	PES/PVA scrim
	<b>Interliner</b>	Release paper, yellow, 90 g/m <sup>2</sup>
	<b>Adhesive weight</b>	90 g/m <sup>2</sup>
	<b>Total thickness</b>	0,10 mm

**Characteristics:** **Temperature resistance** from -40 °C to +100 °C  
(in accordance with ATP trial regulation 07)

<b>Adhesive strength</b> (According to AFERA 5001)	min 18 N/25 mm	Contact time: 1 h
---	----------------	-------------------

**Note:**

All our products are subjected to a strict quality control by our QM-System, which is in accordance with ISO/TS 16949, DIN EN ISO 9001 and DIN EN ISO 14001. The information is based on our present knowledge and our experience. Because of the large number of possible influences during the processing and application of our products, this information does not release the user from the obligation to conduct his own tests and trials. Users of our products are responsible for observing any patent rights that may exist and for following existing regulations. Our applications technology section is always pleased to give advice about suitability tests on original materials.

Created on:  
R.F. / 1999-03-10  
Last modification:  
. / 2005-08-04