

Product Datasheet uvex i-3 add 1.0 Material No. 6108.210



UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189, D-90766 Fürth

Productcharacteristic	* Innovative spectacle with invisible integrated dioptrre correction for near vision, +1,0 dpt. * Patented lens technology * Free-form lens design, manufactured in accordance with standard parameters and designed for a distance of approx. 64mm between the eyes * Extremely good coverage and fit all the way to the side area * Individually adjustable side arms with variable inclination * Integrated Softflex zone ensures outstanding wearer comfort for all head sizes * Softflex adjustable nose piece ensures comfortable, pressure-free fit and remain firmly in place
Technical details Frame Material Features Colour	TPU/TPE Variable inclination, individually adjustable grey/lime

Manufacturer	Marking
EN Standard	W
Low-energy impact	166
Resistance to high speed particles at extremes of temperat.	F (45 m/sec) EN 166
Conformity symbol	T
	CE
Lens	
Material	PC
Coating	supravision HC-AF
Colour	clear
Feature	integrated dioptrre correction; +1,0 dpt.
	Marking
Filter	2C-1,2 (DIN EN 170)
Manufacturer	W
Optical class	1
Low-energy impact	F (45 m/sec)
Resistance to high speed particles at extremes of temperature	T
Surface resistance to fine particles	K
Antifog	N
Conformity symbol	CE
Corr./PD	i-3 add 1.0, PD 64 / Add. 1,0 dpt.
Miscellaneous	
Weight	38g
Packing	1 piece in soft spectacles case with microfiber cloth
Standards	DIN EN 166 + DIN EN 170