

LIERIÖERISTIMET

Tyyppi A

Tekniset tiedot

NR: 55°/60 shore°

Mitat leveys/korkeus	Kierre ulkokierre	PURISTUSVOIMA			LEIKKAUSVOIMA		
		F (max) N	F (max) Kg	S (max) mm	F (max) N	F (max) Kg	S (max) mm
A 10/10	M4	40	4,08	0,90	20	2,04	2,00
A 10/15	M4	40	4,08	1,20	15	1,53	3,10
A 15/10	M4	120	12,23	0,90	35	3,57	2,80
A 15/15	M4	100	10,19	1,50	40	4,08	3,20
A 20/10	M6	170	17,33	0,50	70	7,14	1,40
A 20/15	M6	160	16,31	1,20	70	7,14	2,60
A 20/20	M6	160	16,31	1,70	70	7,14	4,50
A 20/25	M6	150	15,29	2,10	60	6,12	6,20
A 25/10	M6	300	30,58	0,80	120	12,23	1,50
A 25/15	M6	290	29,56	1,50	110	11,21	2,50
A 25/20	M6	280	28,54	2,60	110	11,21	3,80
A 25/25	M6	260	26,50	2,70	105	10,70	5,40
A 25/30	M6	250	25,48	3,40	90	9,17	6,70
A 30/15	M8	500	50,97	0,90	170	17,33	2,60
A 30/20	M8	440	44,85	1,70	170	17,33	3,90
A 30/25	M8	400	40,77	2,10	160	16,31	5,30
A 30/30	M8	380	38,74	2,90	150	15,29	6,60
A 30/40	M8	300	30,58	4,00	100	10,19	10,00
A 40/20	M8	900	91,74	1,50	300	30,58	3,80
A 40/30	M8	700	71,36	2,40	300	30,58	6,60
A 40/40	M8	650	66,26	3,50	260	26,50	9,00
A 50/20	M10	2000	203,87	2,10	500	50,97	3,60
A 50/25	M10	1400	142,71	2,50	500	50,97	4,60
A 50/30	M10	1400	142,71	3,20	500	50,97	6,40
A 50/35	M10	1300	132,52	3,50	500	50,97	8,00
A 50/40	M10	1100	112,13	3,80	450	45,87	8,50
A 50/45	M10	1050	107,03	4,10	450	45,87	10,10
A 50/50	M10	1050	107,03	4,80	420	42,81	11,70
A 70/35	M10	2400	244,65	4,50	900	91,74	9,00
A 70/45	M10	2300	234,45	4,2	900	91,74	9,9
A 75/40	M12	2900	295,62	3,60	1000	101,94	4,90
A 75/50	M12	2800	285,42	5,20	1000	101,94	11,20
A 75/55	M12	2500	254,84	5,20	1000	101,94	12,50
A 100/40	M16	6600	672,78	3,90	2000	203,87	8,20
A 100/55	M16	5100	519,88	6,10	2000	203,87	12,40

Tyyppi B
Tekniset tiedot
NR: 55°/60 shore°

Mitat	Kierre Ulko/Sisäkierre	PURISTUSVOIMA			LEIKKAUSVOIMA		
		F (max)	F (max)	S (max)	F (max)	F (max)	S (max)
		N	Kg	mm	N	Kg	mm
B 10/10	M4	56	5,71	0,90	10	1,02	2,30
B 10/15	M4	52	5,30	1,50	23	2,34	3,80
B 15/15	M4	115	11,72	1,40	50	5,10	3,80
B 20/15	M6	160	16,31	0,90	105	10,70	3,80
B 20/20	M6	160	16,31	1,20	90	9,17	5,00
B 20/25	M6	150	15,29	2,50	90	9,17	6,30
B 25/15	M6	290	29,56	1,30	160	16,31	3,80
B 25/20	M6	280	28,54	2,10	145	14,78	5,00
B 25/25	M6	260	26,50	2,90	135	13,76	6,30
B 25/30	M6	250	25,48	3,20	135	13,76	7,50
B 30/15	M8	676	68,91	1,40	208	21,20	3,40
B 30/20	M8	380	38,74	1,60	210	21,41	5,00
B 30/25	M8	370	37,72	2,30	200	20,39	6,30
B 30/30	M8	355	36,19	2,80	190	19,37	7,50
B 30/40	M8	300	30,58	3,20	100	10,19	8,00
B 40/30	M8	600	61,16	2,40	340	34,66	7,50
B 40/40	M8	600	61,16	3,80	330	33,64	10,00
B 50/20	M10	1300	132,52	1,00	455	46,38	4,00
B 50/30	M10	1200	122,32	2,60	500	50,97	7,00
B 50/40	M10	1100	112,13	3,60	315	32,11	10,00
B 50/50	M10	1050	107,03	5,10	505	51,48	12,50
B 60/40	M10	1750	178,39	4,60	700	71,36	6,30
B 75/50	M12	2600	265,04	4,30	1185	120,80	12,50
B 75/55	M12	2400	244,65	4,70	1170	119,27	13,80
B 100/40	M16	6500	662,59	3,20	2310	235,47	10,00
B 100/55	M16	5100	519,88	5,00	2180	222,22	13,80
B 100/60	M16	5000	509,68	5,60	2125	216,62	15,00

Tyyppi C
Tekniset tiedot
NR: 55°/60 shore°

Mitat	Kierre Ulko/Sisäkierre	PURISTUSVOIMA			LEIKKAUSVOIMA		
		F (max)	F (max)	S (max)	F (max)	F (max)	S (max)
		N	Kg	mm	N	Kg	mm
C 10/10	M4	96	9,79	1,60	12	1,22	1,20
C 15/15	M4	120	12,23	1,50	40	4,08	2,00
C 20/20	M6	170	17,33	1,60	50	5,10	2,50
C 20/25	M6	150	15,29	2,20	40	4,08	2,70
C 25/20	M6	280	28,54	1,70	90	9,17	3,00
C 25/25	M6	260	26,50	2,20	80	8,15	3,50
C 30/25	M8	370	37,72	2,20	120	12,23	3,60
C 30/30	M8	355	36,19	2,60	110	11,21	4,10
C 30/35	M8	436	44,44	3,10	208	21,20	9,40
C 30/40	M8	429	43,73	3,60	208	21,20	10,90
C 40/30	M8	700	71,36	2,70	250	25,48	5,20
C 40/40	M8	650	66,26	3,90	250	25,48	7,40
C 50/30	M10	1200	122,32	2,40	400	40,77	5,20
C 50/35	M10	1150	117,23	2,90	400	40,77	6,40
C 50/40	M10	1100	112,13	3,30	400	40,77	7,40
C 50/45	M10	1050	107,03	4,10	400	40,77	8,60
C 50/50	M10	1050	107,03	4,90	400	40,77	9,70
C 75/40	M12	2900	295,62	3,20	900	91,74	7,00
C 75/50	M12	2600	265,04	4,10	900	91,74	9,00
C 75/55	M12	2400	244,65	4,60	900	91,74	10,10
C 100/40	M16	6500	662,59	2,90	1500	152,91	5,60
C 100/55	M16	5100	519,88	4,90	1500	152,91	9,10

LIERIÖERISTIMET

Tyyppi D

Tekniset tiedot

NR: 55°/60 shore°

Mitat	Kierre Internal Thread	PURISTUSVOIMA		
		F (max) N	F (max) Kg	S (max) mm
D 10/10	M4	59	6,01	1,00
D 15/15	M4	115	11,72	2,00
D 20/10	M6	170	17,33	1,10
D 20/15	M6	160	16,31	1,40
D 20/20	M6	160	16,31	1,90
D 20/25	M6	150	15,29	2,80
D 25/10	M6	300	30,58	0,80
D 25/15	M6	290	29,56	1,50
D 25/20	M6	280	28,54	2,30
D 30/15	M8	350	35,68	3,10
D 30/20	M8	350	35,68	4,40
D 30/25	M8	350	35,68	5,80
D 30/30	M8	350	35,68	7,20
D 40/25	M8	1044	106,42	2,00
D 40/30	M8	660	67,28	3,30
D 40/40	M8	600	61,16	4,60
D 50/20	M10	1500	152,91	2,00
D 50/30	M10	1200	122,32	3,30
D 50/40	M10	1100	112,13	4,30
D 50/45	M10	1050	107,03	5,10
D 75/25	M12	5446	555,15	2,50
D 75/40	M12	2900	295,62	4,00
D 100/40	M16	6600	672,78	3,60
D 100/50	M16	5400	550,46	5,00

