



	1	2	3	4	5	6	7	8							
A	Profil <i>Profile</i> 5M <table><tr><th>t [mm]</th><th>h_s [mm]</th><th>h_t [mm]</th></tr><tr><td>5,00</td><td>3,40 ±0,25</td><td>1,90</td></tr></table> Prinzip-Skizze <i>Principle sketch</i> 			t [mm]	h _s [mm]	h _t [mm]	5,00	3,40 ±0,25	1,90						
	t [mm]	h _s [mm]	h _t [mm]												
	5,00	3,40 ±0,25	1,90												
B	Aufbau <i>Construction</i> - Zahnseitiges Gewebe: Polyamid - Elastomer: CR-Mischung - Zugstrang: Glascord - Härte: 72 ±5 Shore A - <i>Fabric on teeth: Polyamide</i> - <i>Elastomer: CR compound</i> - <i>Tension cord: Glass cord</i> - <i>Hardness: 72 ±5 Shore A</i>														
C	Eigenschaften <i>Characteristics</i> - Antistatisch nach ISO 9563: nein - Scheibenprofile: HTD und RPP nach ISO 13050 - Temperaturbeständigkeit: -30° C bis +100° C - Metergewicht: 0,035 kg/m für 10 mm Breite - <i>Antistatic to ISO 9563: no</i> - <i>Pulley profile: HTD and RPP to ISO 13050</i> - <i>Temperature resistance: -30° C to +100° C</i> - <i>Weight per meter: 0,035 kg/m for 10 mm width</i>														
D	Mindestzähnezahl der Scheibe: z_{min} = 14 Wirkdurchmesser: d_w = 22,28 mm Minstdurchmesser der Außenrolle: d_{min} = 25,00 mm Minimum no. of teeth pulley: z_{min} = 14 Pitch diameter: d_w = 22,28 mm Minimum diameter of backside idler: d_{min} = 25,00 mm 														
Wir beraten Sie gerne über die Produkteigenschaften und -anpassungen bei besonderen Anforderungen. Bitte beachten Sie auch die Hinweise in den Optibelt Dokumentationen. Irrtümer und technische Änderungen vorbehalten. www.optibelt.com, © Arntz Optibelt Gruppe We would be pleased to offer advice about technical characteristics and drive design as well as special requirements. Further information can be found in Optibelt documentation. Subject to technical modification and change, errors and omissions excepted. www.optibelt.com, © Arntz Optibelt Group															
	1	2	3	4	5	6	7	8							